


# HiLo PowerTilt



(HiLo Multipro top shown; PowerTilt has the same top sections but adjusts w/ hand control)


## TOP:

Top design	Four-piece adjustable top with round corners, three-layer foam, 3/4" plywood
Standard size top	30" x 73"
Foam	2" firm bottom layer + 1- 3/4" medium-density layer of urethane polymer
Polyester batting	1/2" fluffy polyester Dacron top layer
Frame	3/4" plywood frame reinforced for arm rests and face cradle
Adjustments	Motorized adjustment of height from 17" to 36" (ADA compliant), and motorized adjustments of torso, knee, and upper body sections
Back tilt angle	0 to 60°
Knee tilt angle	0 to 30°




## BASE & FRAME:

Carbon steel base	Sleek, contemporary design with white powder-coat finish
8" leg recess	8" recess from ends of table
Height range - standard	17" to 36" (infinite motorized adjustment)
Lifting weight	Lifting weight capacity 325 lbs.
Capacity	Static weight capacity 600 lbs.



## MOTORS & CONTROLS

PowerTilt motors	Two 24v DC, 5 amp max motor/actuators, UL recognized; powered through a 110v, 5 amp transformer
Main lift mechanism	One 24v DC, 5 amp max motor/actuator, UL recognized (uses the same transformer as the top motor/actuators)
Controls	Hand control




## VINYL:

Ultra-Soft Touch - standard	Lightly textured, super-soft PU vinyl, fabric backed, environmentally friendly
-----------------------------	--------------------------------------------------------------------------------

## ACCESSORIES:

Sidearms	60-degree Sidearms
Face support	Deluxe FaceSpace II
Foot extension	Salon Footrest or Full Footrest
Neck bolster	Facial Neck Bolster



## GUARANTEES:

Structure	10 yrs.
Foam & vinyl	Guaranteed to arrive in good condition
Motor & controls	1 yr.

## WEIGHTS:

Table weight	245 lbs.
Shipping weight - boxed	300 lbs. (83" x 35" x 39" = 66 cu ft)

Rev 1/09

www.TouchAmerica.com  
 (800) 678-6824 · (919) 732-6968  
 PO Box 1304 · Hillsborough · NC 27278

  
**TouchAmerica**  
 evolving the spa experience