

# **Material Safety Data Sheet**

Section 1: Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: Soak Off Gel Polish

 Chemical Name: Gel Polish
 MSDS Prepared By/Date:
 11/14/2013

 Updated
 11/14/2013

Family: Soak Off Gel Polish

Manufacture: Hand & Nail Harmony Inc
1545 Moonstone Brea, CA 92821

Product Use: cosmetics Emergency Phone Number: (800) 535-5053

Information Contacts: (714) 773-9758

Product #s:

01852 / 01856 /01857 / 01858

**Description: Various Shades** 

# Section 2: Hazards Identification

## **EMERGENCY OVERVIEW**

This information is based on findings from related or similar materials

Flammable Liquid

May be slightly toxic.

May cause moderate skin injury (reddening & swelling).

May cause eye irritation

Potential Health Effects, Signs and Symptoms of Exposure:

Eye Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering Skin May be irritating to skin in some individuals, especially after prolonged and/or repeated contact

Ingestion If product is swallowed, may cause nausea, vomiting, and/or diarrhea

Inhalation Vapors of this product may be slightly irritating to the nose, throat and other tissue of the respiratory systems. Systems of overexposure can include

coughing ,wheezing, nasal congestion, and difficulty breathing.

NOTE: Refer to Section II, Toxicological Information for Details

Section 3: Composition/Information on Ingredients

INCI NAME	CAS#	EINECS#	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
	41137-60-4 /72869-		N/E	N/E	Not Listed	
Di-HEMA Trimethylhexyl Dicarbamate	86-4	276-957-5	IN/L	IN/L	Not Listed	30.0 - 55.0
Hydroxypropyl Methacrylate	27813-02-1	248-666-3	N/E	N/E	Not Listed	30.0 - 55.0
Isobornyl Methacrylate	7534-94-3	231-403-1	N/E	N/E	Not Listed	5.0-20.0
Ethyl Acetate	141-78-6	205-500-4	400ppm	400ppm	Not Listed	5.0-20.0
Butyl Acetate	123-86-4	204-658-1	150ppm	150ppm	Not Listed	5.0-20.0
HEMA	868-77-9	212-782-2	N/E	N/E	Not Listed	1.0-5.0
Trimethylolpropane Trimethacrylate	3290-92-4	221-950-4	N/E	N/E	Not Listed	1.0-5.0
Nitrocellulose	9004-70-0	N/A	N/E	N/E	Not Listed	1.0-5.0
Adipic Acid/Neopentyl Glycol/Trimellitic Anhydride Copolymer	28407-73-0	N/A	N/E	N/E	Not Listed	1.0-5.0
Isopropyl Alcohol	67-63-0	200-661-7	400 ppm	200 ppm	Not Listed	1.0-5.0
Trimethyl Pentanyl Diisobutyrate	6846-50-0	229-934-9	N/E	N/E	Not Listed	1.0-5.0
Triphenyl Phosphate	115-86-6	204-112-2	N/E	N/E	Not Listed	1.0-5.0
Propyl Acetate	109-60-4	203-686-1	N/E	N/E	Not Listed	1.0-5.0
n-Butyl Alcohol	71-36-3	200-751-6	N/E	N/E	Not Listed	1.0-5.0
Ethyl Trimethylbenzoyl Phenylphosphinate	84434-11-7	282-810-6	N/E	N/E	Not Listed	1.0-5.0
Clay	N/A	N/A	N/E	N/E	Not Listed	1.0-5.0
Stearalkonium Hectorite	12691-60-0	305-633-9	N/E	N/E	Not Listed	1.0-5.0
Stearalkonium Bentonite	130501-87-0	N/A	N/E	N/E	Not Listed	1.0-5.0
Diacetone Alcohol	123-42-2	204-626-7	N/E	N/E	Not Listed	1.0-5.0
Hydroxycylohexyl Phenyl Ketone	947-19-3	213-426-9	N/E	N/E	Not Listed	1.0-5.0
Acrylates Copolymer	9010-88-2	N/A	N/E	N/E	Not Listed	1.0-5.0
Ethylene /VA Copolymer	24937-78-8	N/A	N/E	N/E	Not Listed	1.0-5.0
PEG/PPG 27/27 Dimethicone	N/A	N/A	N/E	N/E	Not Listed	<1.0
Benzophenone-1	131-56-6	205-029-4	N/E	N/E	Not Listed	<1.0
Dimethicone	9006-65-9	N/A	N/E	N/E	Not Listed	<1.0
Citric Acid	77-92-9	201-069-1	N/E	N/E	Not Listed	<1.0
Sucrose Acetate Isobutyrate	126-13-6	204-771-6	N/E	N/E	Not Listed	<1.0
p-Hydroxyanisole	150-76-5	205-769-8	N/E	N/E	Not Listed	≤0.02
May Contain						
Titanium Dioxide (CI 77891)	13463-67-7	236-675-5	15 mg/m3	10 mg/m3	Not Listed	

N/E - None Established N/DA - No Data Available \*See section 16
N/R - Not Reviewed N/A - Not Applicable

Di-Hema Trimethylhexyl Dicarbamate Hazard Symbol: Xi Risk Phrases: R36/37/38

Butyl Acetate Hazard Symbol: Xi Risk Phrases: R36/38, R43

Ethyl Acetate Hazard Symbol: Xi Risk Phrases: R36/38, R43

Hydroxypropyl Methacrylate: Hazard Symbol: Xi Risk Phrases: R36/37/38, R43

Isobomyl Methacrylate: Hazard Symbol: Xi Risk Phrases: R36/37/38

Safety Phrases: S14, S3/7, S62 Safety Phrases: S2, S26 Safety Phrases: S2, S26 Safety Phrases: S26, S36/37

Safety Phrases: S26, S36/37 Page 1 of 5 Safety Phrases: S26,S27,S28,S29,S30,S33,S35,S36 Triphenyl Phosphate Hazard Symbol: N Risk Phrases: R50/53 Safety Phrases: S16/23/25/29/33

TPO-L: Hazard Symbol: Risk Phrases: R99 Safety Phrases:

Isopropyl Alcohol: Hazard Symbols: Xi, F Risk Phrases: R11, R36, R67 Safety Phrases: S2, S7, S16, S24/25, S26

See Section 15 for Risk and Safety Phrase Key

### **Section 4: First Aid Measures**

First Aid for Eye Splashes are not likely, however, if product gets into the eyes, flush with plenty of water for at least 15 minutes.

If irritation occurs, seek medical attention immediately.

First Aid for Skin Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer

artificial respiration and seek medical attention.

First Aid for Ingestion If appreciable quantities are swallowed, seek medical attention.

### **Section 5: Fire Fighting Measures**

Flash Point ( °F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
> 35°F / 1.6°C estimated	No Data	No Data

Method:

First Aid for Inhalation

WARNING: Flammable. Keep away from heat, lit cigarettes, sparks & open flame .Keep containers closed

Extinguishing Media: Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.

Fire Fighting Instructions: Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering

confined areas where potential for exposure to vapors or products of combustion exists.

### Section 6: Accidental Release Measures

Spill: Before cleaning any spills or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

Dike and contain spill with inert material (e.g. sand or earth). Use ONLY non sparking tools for recovery and clean-up. Transfer liquid to containers for recovery or disposal and solid diking material to separated containers for proper disposal. Remove contaminated clothing promptly and wash

affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water

US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations

reportable quantities. The foil free number for the US Coast Guard National Response Center is (800) 424-8602. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

## Section 7: Handling and Storage

Handling: Keep container closed when not in use. Avoid prolong contact with the product. Avoid breathing vapors of this product. Use in a well ventilated location.

Storage: Product is extremely light sensitive. If exposed to natural light, LED, UVA, UVB or UV any light, material will cure very quickly.

Store in a cool, dry place, away from heat and all types of light.

Store away from incompatible materials

Special precautions Keep this materials away from heat, sparks, and open flame. Keep containers tightly closed when not in use.

# Section 8: Exposure Controls / Personal Protection

Engineering Controls When working with large quantities of product, provide adequate ventilation. Ensure that an eyewash station, sink or washbasin

is available in case of exposure to eyes. Personal Protective Equipment

General: To identify additional Personal protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance

with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron

boots, or whole body suits. Nitrile rubber is better than PVC.

Eye / Face Protection: Wear chemical splash goggles
Skin Protection: Wear impervious gloves (Neoprene)

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain

limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations

found in 29 CFR 1910.134 or European Standard EN 149.

### **Section 9: Physical and Chemical Properties**

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	%Volatile
viscous liquid	characteristic acrylate odor	NA	(H20=1): 1.15	N/DA	By Volume: <7.0

Boiling Point/Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (	(20°C)
N/A	N/A	N/A	(mm Hg) @ 20 C:<0.01	No Data	No Data	No Data	Insoluble	

Flash Point ( °F/ °C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
> 35°F / 1.6°C estimated	No Data	No Data

Stability Incapability (Material to Avoid):

Normally Stable Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust

and strong bases.

**Hazardous Polymerization: Hazardous Decomposition Products:** 

Fumes produced when heated to May occur --- Uncontrolled polymerization may cause rapid evolution of heat and increased pressure that could

decomposition may include: result in violent rupture of sealed storage vessels or containers.

carbon monoxide, carbon dioxide

Conditions to Avoid:

Storage>100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization, contamination with incompatible materials.

## Section 11: Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
No info available	No info available	No info available	No info available	No info available
	•			

Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	N/DA	N/DA

## Section 12: Ecological Information

#### Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria	
No Information Available	No Information Available	No Information Available	No Information Available	No Information Available	

#### **Environmental Stability:**

Ethyl Acetate: removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.			
Butyl Acetate:	compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hc		
Isopropyl Alcohol:	or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days, Isopropyl alcohol is not expected to bioconcentrate.		
Chemical Fate Information			
Biodegradability No Information Available			
Chemical Oxygen Demand No Information Available			

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated.

Do not allow to enter drinking water supplies, wastewater, or soil.

## Section 13: Disposal Considerations

Waste disposal must be in accordance with appropriate Federal, State and local regulations. US. EPA Waste #: D001

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member State, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

### Section 14: Transport Information

DOT (49 CFR 172)

UN 1263, Paint Related Material, 3, II Proper Shipping Name:

UN1263 Identification Number:

Marine Pollutant: Yes, Triphenyl Phosphate

Consumer Commodity ORM-D (≤1.0 L)

## Emergency Response Guidebook (ERG) #:

IATA (DGR):

Proper Shipping Name: UN 1263, Paint Related Material, 3, II 3

Class or Division:

UN 1263 UN or ID Number: Consumer Commodity. 9, ID8000 (≤ 0.5 L)

Emergency Response Guidance (ICAO)#:

IMO (IMDG):

Proper Shipping Name: UN 1263.Paint Related Material.3.II

Class or Division:

UN or ID Number: UN1263 Special Provisions & Stowage/Segregation:

Emergency Schedule (EmS)#:

TDGR (Cabdian GND): Mark Package "Limited Quantity" or "Quantite Limitee" or "LTD QTY" or "Quant Ltee" (≤ 1.0 L)

UN1263, Paint, 3, II, (>1.0 L)

ADR/RID (EU): UN 1263, Paint Related Material, 3, II, ADR

Other Information: MEXICO (SCT):

UN1263, Pintura,3,II, Cantidad Limitada (≤ 1.0L)

ADGR(AUS): UN1263, Paint, 3, II LTD QTY (≤ 1.0L)

## Section 15: Regulatory Information

Page 3 of 5

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act:
	• NONE
	This product does not contain any Class I or Class 2 ODS
Clean Water Act: Priority Pollutant	This product contains the following Hazardous Substances as defined by the CWA:
	NONE
	This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and /or other applications as an indirect food
	additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its
	hazards are:
	Immediate (acute) health hazard
	Delayed (chronic) health hazard
	Reactive hazard
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261)
SARA Reporting Requirements:	SARA 304 (40 CFR Table 302.4)- Butyl Acetate, Ethyl Acetate
SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
TSCA Section 8(b) Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA pre-manufacture
	notification requirements.
CERCLA Reportable Quantity (RQ):	Butyl Acetate: 2270 kg; 5000 lbs.; Ethyl Acetate: 2270 kg; 5000 lbs.

#### State Regulations

Otate Regulations	
CA Right-to-Know Law:	Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4,
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4, Nitrocellulose CAS# 9004-70-0, Triphenyl Phosphate CAS# 115-86-6
NJ Right-to-Know Law:	Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4
PA Right-to-Know Law:	Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4, Triphenyl Phosphate CAS# 115-86-6
FL Right-to-Know Law:	Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4
MN Right-to-Know Law:	Titanium Oxide CAS # 13463-67-7, Ethyl Acetate CAS #141-78-6, Butyl Acetate CAS # 123-86-4, Triphenyl Phosphate CAS# 115-86-6

## International Regulations

CDSL: Canadian Inventory	Hydroxpropyl methacrylate CAS #27813-02-1 is on the DSL List. WHMIS = D2B
(on Canadian Transitional List)	Hyroxycyclohexyl phenyl ketone CAS# 947-19-3 is on the DSL list. WHMIS - n/da 2-Hydroxyethyl methacrylate CASE# 868-77-9 is on the DSL List. WHMIS - n/da
	Isobornyl Methacrylate CAS# 7534-94-3 is on the DSL list. WHMIS - n/da Titanium Dioxide CAS# 13463-67-7WHMIS- not controlled
	D&C Violet 2/Cl60725 CAS # 81-48 is not on the DSL List. WHMIS = N/DA
	Ethyl Acetate CAS# 141-78-6 is on the DSL list.WHMIS= B2,D2B
	Butyl Acetate CAS # 123-86-4 is on the list. WHMIS + B2, D1B, D2B
	Acrylates Copolymer CAS # 25035-69-2 is on the DSL list.MHMIS= N/DA
Labelina according to EC Directives 4000/4E/EC	

### Labeling according to EC Directives - 1999/45/EC

European Community:





# HNH Base Gel:

- HAZARD SYMBOLS: Xi irritant, F: Flammable, Xn: Harmful
- RISK PHRASES: R22: Harmful if swallowed, R36/38/37: Irritating to eyes, respiratory system, and skin, R43: May

cause sensitization by skin contact. R10 Flammable, R11 Highly Flammable, R20 Harmful by inhalation

R21 Harmful in contact with the skin, R41 Risk of serious damage to eyes, R50 Very toxic to aquatic organisms
R53 May cause long term adverse effect in the aquatic environment, R65 Harmful, may cause lung damage

R66 Repeated exposure may cause skin dryness or cracking, R67 Vapors may cause drowsiness and dizziness

• SAFETY PHRASES: **\$18**: Handle and open container with care, **\$24/25**: avoid contact with skin and eyes, **\$36/37**:

Wear suitable protective clothing and gloves, \$38: in case of insufficient ventilation, wear suitable respiratory

equipment. S16: Keep away from sources of ignition-No Smoking, S23: Do no breathe vapor,

\$29: Do not empty into drains, \$33: Take precautionary measures against.

## EU Classes and Risk / Safety Phrases :

## Hazard Symbols:

Xi - Irritants

F - Flammable substances or preparations

Xn: Harmful

RISK PHRASES: R22: Harmful if swallowed, R36/38/37: Irritating to eyes, respiratory system, and skin, R43: May
cause sensitization by skin contact. R10 Flammable, R11 Highly Flammable, R20 Harmful by inhalation

R21 Harmful in contact with the skin, R41 Risk of serious damage to eyes, R50 Very toxic to aquatic organisms

R53 May cause long term adverse effect in the aquatic environment, R65 Harmful, may cause lung damage

R66 Repeated exposure may cause skin dryness or cracking, R67 Vapors may cause drowsiness and dizziness

• SAFETY PHRASES: S18: Handle and open container with care, S24/25: avoid contact with skin and eyes, S36/37:

Wear suitable protective clothing and gloves, **\$38**: in case of insufficient ventilation, wear suitable respiratory equipment. **\$16**: Keep away from sources of ignition-No Smoking, **\$23**: Do no breathe vapor,

S2 Keep out of reach of children; S3/7 Keep container tightly closed in a cool place; S26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice; \$27 Take off immediately all contaminated clothing; \$28 After contact with skin, wash immediately with plenty of water; \$29 Do not empty into drains;


S30 Never add water to this product; S33 Take precautionary measures against static discharges; S35 This material and its container must be disposed of in a safe way;

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show the container or label

Page 4 of 5

ection	16:	Other	Information

HMIS:





This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If there are any problems or concerns understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).