

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 3.1

MSDS Revision Date: 06/01/2013

1. PRODUCT IDENTIFICATION

1.1	Product Name: NAIL ENVY NAIL STRENGTHENER – MATTE FORMULA
1.2	Chemical Name: SOLVENT MIXTURE
1.3	Synonyms: NA
1.4	Trade Names: NT82
1.5	Product Use: COSMETIC USE ONLY
1.6	Manufacturer's Name: OPI PRODUCTS, INC.
1.7	Manufacturer's Address: 13034 SATICOY STREET, NO. HOLLYWOOD, CA 91605 USA
1.8	Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300
1.9	Business Phone: +1 (818) 759-2400 / +1 (800)-341-9999

2. HAZARD IDENTIFICATION

2.1	Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE but not as DANGEROUS GOODS according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia). DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. Hazard Statements (H): H225 – Highly flammable liquid and vapor. H317 – May cause an allergic skin reaction. Precautionary Statements (P): P201 – Obtain special instructions before use. P202 – Do not handle until all safety precautions have been read and understood. P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P261 – Avoid breathing fumes/mists/vapours/spray. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/protective clothing/eye protection/face protection. P281 – Use personal protective equipment as required. P302+P352 – IF ON SKIN: Wash with soap and water. P308+P313 - IF exposed or concerned: Get medical advice/attention. P333+P313 – If skin irritation or a rash occurs: Get medical advice/attention. P321 – Specific treatment (see section 4.1 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P405 – Store locked up. P501 – Dispose of contents/container to licensed, authorized treatment, storage and disposal facility (see Section 13.1 of this Safety Data Sheet).			 	
2.2	Routes of Entry:	Inhalation: YES	Absorption: YES		
2.3	Effects of Exposure: INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression. SKIN & EYES: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact. INHALATION: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).				
2.4	Symptoms of Overexposure: Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering.				
2.5	Acute Health Effects: Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.				
2.6	Chronic Health Effects: None known.				
2.7	Target Organs: Eyes, skin and respiratory system.				

NA = Not Available; ND = Not Determined; NE = Not Established; NF = Not Found; C = Ceiling Limit. See Section 16 for Additional Definitions of Terms Used.
 NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2010 format.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 3.1

MSDS Revision Date: 06/01/2013

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)								OTHER
					ACGIH		NOHSC			OSHA			
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	TLV	STEL	IDLH	
ETHYL ACETATE	141-78-6	AH5425000	201-550-6	30-60	400	NE	720	1440	NF	400	NE	2000	
BUTYL ACETATE	123-86-4	AF7350000	204-658-1	30-60	150	200	730	950	NF	200	200	1700	
NITROCELLULOSE	9004-70-0	QW0970000	NA	10-30	(10)	NE	NF	NF	NF	(10)	NE	NE	
PROPYL ACETATE	109-60-4	AJ3675000	203-686-1	7-13	200	250	835	1040	NF	200	840	1700	
TOSYLAMIDE/FORMALDEHYDE RESIN	1338-51-8	NA	NA	7-13	NA	NA	NF	NF	NF	NA	NA	NA	
ISOPROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	1-5	400	500	983	1230	NF	400	500	2000	
TALC	14807-96-6	WW2710000	238-877-9	≤ 5.0	(0.1)	NA	(2.5)	NF	NF	(0.1)	NA	NA	
TRIPHENYL PHOSPHATE	115-86-6	TC8400000	NA	1-5	3	NA	3	NF	NF	3	NA	NA	
TRIMETHYL PENTANYL DIISOBUTYRATE	6846-50-0	SA142000	229-937-9	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
BUTYL ALCOHOL	71-36-3	NA	200-751-6	1-5	50	NA	50	NF	152	100	NA	NA	
ETHYL TOSYLAMIDE	1077-56-1	NA	214-073-3	1-5	NA	NA	NF	NF	NF	NA	NA	NA	
FORMALDEHYDE	50-00-0	LP8925000	200-001-8	1-5	0.3	NA	0.016	2.0	NF	0.75	2.0	20.0	NIOSH
STEARALKONIUM BENTONITE	71011-24-0	NA	NA	1-5	NA	NA	NF	NF	NF	NA	NA	15	DUST
CAMPHOR	76-22-2	EX1225000	200-945-0	0.1-1	(2)	NA	12	19	NF	(2)	NA	NA	
HYDRATED SILICA	1343-98-2	VV8853000	215-683-2	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
DIACETONE ALCOHOL	123-42-2	SA9100000	NA	0.1-1	50	240	238	NF	NF	20	240	1800	
BENZOPHENONE-1	131-56-6	DJ0700000	205-029-4	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
CITRIC ACID	77-92-9	GE7350000	201-069-1	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
HYDROLYZED WHOLE WHEAT PROTEIN	70084-87-6	NA	NA	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
DIMETHICONE	9006-65-9	NA	63148-62-9	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
CALCIUM PANTOTHENATE	137-08-6	RU4375000	205-278-9	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
CI 60725 (VIOLET #2)	81-48-1	CB7700000	201-353-5	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA	
OTHER COMPONENTS PRESENT IN LESS THAN 1% CONCENTRATION				BAL	THE REMAINING COMPONENTS DO NOT CONTRIBUTE ANY SIGNIFICANT ADDITIONAL HAZARDS								

4. FIRST AID MEASURES

4.1	First Aid:	<p>INGESTION: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p>EYES: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.</p> <p>SKIN: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the effected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.</p> <p>INHALATION: Remove victim to fresh air at once.</p>													
4.2	Medical Conditions Aggravated by Exposure:	None known.	<table border="1"> <tr> <td>HEALTH</td> <td>1</td> </tr> <tr> <td>FLAMMABILITY</td> <td>3</td> </tr> <tr> <td>REACTIVITY</td> <td>0</td> </tr> <tr> <td>PROTECTIVE EQUIPMENT</td> <td>B</td> </tr> <tr> <td>EYES</td> <td></td> </tr> <tr> <td>SKIN</td> <td></td> </tr> </table>	HEALTH	1	FLAMMABILITY	3	REACTIVITY	0	PROTECTIVE EQUIPMENT	B	EYES		SKIN	
HEALTH	1														
FLAMMABILITY	3														
REACTIVITY	0														
PROTECTIVE EQUIPMENT	B														
EYES															
SKIN															

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 3.1

MSDS Revision Date: 06/01/2013

5. FIREFIGHTING MEASURES

5.1	Flashpoint & Method: -4 °C (24 °F) estimated.
5.2	Autoignition Temperature: NA
5.3	Flammability Limits: Lower Explosive Limit (LEL): NE Upper Explosive Limit (UEL): NE
5.4	Fire & Explosion Hazards: WARNING: Flammable! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed.
5.5	Extinguishing Methods: CO₂, Halon, Dry Chemical, Foam HazChem Code: 3YE Hazard Identification Number: 33
5.6	Firefighting Procedures: This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.



6. ACCIDENTAL RELEASE MEASURES

6.1	Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.
-----	---

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.
7.2	Storage & Handling: Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).
7.3	Special Precautions: Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 3.1

MSDS Revision Date: 06/01/2013

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Ventilation & Engineering Controls: When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.
8.2	Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.
8.3	Eye Protection: Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166.
8.4	Hand Protection: If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.
8.5	Body Protection: No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Density:	0.9980 – 1.0008
9.2	Boiling Point:	171 - 640°F
9.3	Melting Point:	NE
9.4	Evaporation Rate:	NA
9.5	Vapor Pressure:	NA
9.6	Molecular Weight:	NE
9.7	Appearance & Color:	Viscous, translucent liquid with ester-like (fruity) odor
9.8	Odor Threshold:	ND
9.9	Solubility:	Insoluble
9.10	pH	NA
9.11	Viscosity:	1000 - 3000 cPs
9.12	Other Information:	NA

10. STABILITY & REACTIVITY

10.1	Stability: Stable under ambient conditions when stored properly (see Section 7, Storage and Handling).
10.2	Hazardous Decomposition Products: If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO₂).
10.3	Hazardous Polymerization: May occur, if exposed to extremely high temperatures.
10.4	Conditions to Avoid: This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide).
10.5	Incompatible Substances: None known.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 3.1

MSDS Revision Date: 06/01/2013

11. TOXICOLOGICAL INFORMATION

11.1	Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document.
11.2	Acute Toxicity: See Section 2.5
11.3	Chronic Toxicity: See Section 2.6
11.4	Suspected Carcinogen: This product contains Isopropyl Alcohol, which is not carcinogenic to humans but is listed as Group 3 carcinogens by the IARC. Formaldehyde is listed as a Group 2A Carcinogen by IARC.
11.5	Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans.
	Mutagenicity: This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity: This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity: This product is not reported to cause teratogenic effects in humans.
	Reproductive Toxicity: This product is not reported to cause reproductive effects in humans.
11.6	Irritancy of Product: See Section 2.3
11.7	Biological Exposure Indices: NE
11.8	Physician Recommendations: Treat symptomatically.

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate: K _{oc} = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: K _{oc} = 1.82. Water solubility: 120 parts H ₂ O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log K _{ow} = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate.
12.2	Effects on Plants & Animals: There are no specific data available for this product.
12.3	Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations.
13.2	Special Considerations: U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 3.1

MSDS Revision Date: 06/01/2013

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – UNTIL 12/31/20 UN1263, PAINT, 3, II (IP VOL > 1.0 L)	   
14.2	IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (IP VOL ≤ 0.5 L) UN1263, PAINT, 3, II (IP VOL > 0.5 L)	
14.3	IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) UN1263, PAINT, 3, II (IP VOL > 1.0 L)	
14.4	TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (IP VOL ≤ 1.0 L) UN1263, PAINT, 3, II (IP VOL > 1.0 L)	
14.5	ADR/RID (EU): UN1263, PAINT, 3, II, ADR, LTD QTY (IP VOL ≤ 1.0 L)	
14.6	MEXICO (SCT): UN1263, PINTURA, 3, II, CANTIDAD LIMITADA (IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L)	

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements: SARA 304 (40 CFR Table 302.4) – Butyl Acetate, Ethyl Acetate, Isopropyl alcohol. Formaldehyde is subject to SARA Title III reporting (304, 313).	
15.2	SARA Threshold Planning Quantity: Formaldehyde: 500 lbs TPQ	
15.3	TSCA Inventory Status: The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ): Butyl Acetate: 2270 kg (5000 lbs); Ethyl Acetate: 2260 kg (5000 lbs); Formaldehyde: 45.4 kg (100 lbs)	
15.5	Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).	
15.6	Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B1 Flammable Liquid.	 
15.7	State Regulatory Information: Ingredients in this mixture on found on the following state criteria lists: Formaldehyde is found on the following state criteria Lists: California OSHA Hazardous Substances List (CA), California Proposition 65 (CA65), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposure Limits (WA), Wisconsin Hazardous Substances List (WI). Butyl Acetate is found on the following state criteria lists: CA, Delaware Air Quality Management List (DE), MA, NJ, New York List of Hazardous Substances (NY), PA, WA, WI. Ethyl Acetate is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, WA. Isopropanol is found on the following state criteria lists: CA, MA, MN, NJ, PA, WA. Diacetone is found on the following state criteria lists: CA, Michigan Critical Substances List (MI), MN, NJ, WI. Nitrocellulose is found on the following state criteria lists: DE, MA, PA. Camphor is found on the following state criteria lists: MA, MN, PA. Talc is found on the following state criteria lists: MA, MN, PA, WA. Propyl Acetate is found on the following state criteria lists: CA, MI, MN, NJ, WI. Silica is found on the following state criteria lists: PA. Triphenyl Phosphate is found on the following state criteria lists: WA.	

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 3.1

MSDS Revision Date: 06/01/2013

15. REGULATORY INFORMATION - continued

15.8 67/548/EEC (European Union) Requirements:

The primary components of this product are listed in Annex I of EU Directive 67/548/EEC:

Butyl Acetate: Flammable (F). **Risk Phrases (R):** Flammable. **Safety Phrases (S):** 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Ethyl Acetate: Flammable (F). **Risk Phrases (R):** 11-36/37/38 - Highly flammable. Irritating to eyes, respiratory system and skin. **Safety Phrases (S):** 2-16-23-29-33 - Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.

DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION.

Hazard Statements (H): H225 - Highly flammable liquid and vapor. H317 - May cause an allergic skin reaction.

Precautionary Statements (P): P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat/sparks/open flame/hot surfaces - No Smoking. P233 - Keep container tightly closed. P261 - Avoid breathing fumes/mists/vapours/spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P281 - Use personal protective equipment as required. P302+P352 - IF ON SKIN: Wash with soap and water. P308+P313 - IF exposed or concerned: Get medical advice/attention. P333+P313 - If skin irritation or a rash occurs: Get medical advice/attention. P321 - Specific treatment (see section 4.1 of this Safety Data Sheet). P363 - Wash contaminated clothing before reuse. P405 - Store locked up. P501 - Dispose of contents/container to licensed, authorized treatment, storage and disposal facility (see Section 13.1 of this Safety Data Sheet).



16. OTHER INFORMATION

16.1 Other Information:

EXTREMELY FLAMMABLE! Keep away from heat or flame. Use only as directed. Avoid eye contact. If contact occurs, flush eye thoroughly with running water. Use only in a well-ventilated area. If redness or other signs of adverse reaction occur, discontinue use immediately. Keep container closed. Store in a cool place. **KEEP OUT OF REACH OF CHILDREN.**

16.2 Terms & Definitions:

Please see last page of this Safety Data Sheet.

16.3 Disclaimer:

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI Products' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4 Prepared for:

OPI Products, Inc.
13034 Saticoy Street
No. Hollywood, CA 91605 USA
Tel: +1 (818) 759-2400
Fax: +1 (818) 759-5770
<http://www.opi.com/>

O·P·I

16.5 Prepared by:

ShipMate, Inc.
PO Box 787
Sisters, OR 97759-0787 USA
Tel: +1 (310) 370-3600
Fax: +1 (310) 370-5700
e-mail: shipmate@shipmate.com



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 3.1

MSDS Revision Date: 06/01/2013

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	

G	
H	
I	
J	
K	
X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Eye Protection	Gloves
Boots	Synthetic Apron	Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product.

OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:	
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₀₁	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₀₁, LD₀₁, & LD₀₁ or TC, TC₀₁, LC₀₁, & LC₀₁	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

A	B	C	D1	D2	D3	E	F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment