

MATERIAL SAFETY DATA SHEET**SECTION 1 : CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Name: Danica I am Peace EDP.

Formula #: RR033109A

Product Description: Liquid

Manufacturer : Cosmetix West

143 Oregon Street

El Segundo, CA 90245

Phone : 310 726 3080

Fax : 310 726 3083

SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS

CONCENTRATION (%)

Proprietary Blend

SECTION 3 : HAZARDS IDENTIFICATION**Potential Health Effects****Eye**

May cause eye irritation. Symptoms include stinging, tearing and redness.

Skin

May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include : stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), involuntary eye movement, respiratory depression (slowing of the breathing rate), loss of coordination, confusion, irregular heartbeat, anesthesia, respiratory failure, coma, and death.

Target Organ Effects

This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of this findings to ethanol exposure in industrial environments is uncertain. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals : pancreatic damage, liver damage, brain damage, testis damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans : liver damage.

Cancer Information

This product contains ethanol. The International Agency for Research on Cancer (IARC) has determined that exposure to ethanol through chronic human consumption of alcoholic

beverages can cause cancer. The relevance of this finding to ethanol exposure in industrial environments is uncertain.

Other Health Effects

No data.

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

SECTION 4 : FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water.

Swallowing

Seek medical attention. Drink water or milk to dilute. If individual is drowsy or unconscious, do not give anything by mouth ; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention.

SECTION 5 : FIRE FIGHTING MEASURES

Flash Point 66 °F (ASTM 93 close up cup method)

Autoignition Temperature

No data

Hazardous Products of Combustion

May form : carbon dioxide, carbon monoxide and unidentified organic compounds

Fire and Explosion Hazards

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

Foam, water fog, carbon dioxide, dry chemical

Fire Fighting Instructions

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

Unusual Fire and Explosion Hazards

None, material is not pyrophoric. Does not react with water, not oxygen donor, material is shock stable

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Ventilate area. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify

authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

SECTION 7 : HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and solid), all hazard precautions given in the data sheet must be observed. All five-gallon pails and larger metal containers, including tank cars and tank trucks, should be grounded and/or bonded when material is transferred.

Storage

Store in tightly sealed containers in cool, dry and well-ventilated area. Do not exposure to temperatures above 95°F. Keep away from heat and flame.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised.

Skin Protection

Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions. Engineering or administrative controls should be implemented to reduce exposure.

Local Ventilation

Local exhaust recommended (Explosion Proof)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

Not Established

Melting Point

N/A

Vapor Pressure

N/A

Specific Vapor Density

N/A (Air = 1.0)

Specific Gravity

0.80-0.90 @ 25°C (H₂O = 1.0)

Refractive Index

1.382-1.385 @ 20°C

pH

N/A

Viscosity

N/A

Appearance

Clear

State

Liquid

Physical Form

Homogeneous liquid

Color

yellow

Odor

Floral-tuberose

Solubility in water

Miscible

VOC

75%

SECTION 10 : STABILITY AND REACTIVITY

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Hazardous Decomposition: May form: carbon dioxide and carbon monoxide

Chemical Stability: Stable under normal circumstances

Incompatibility: Avoid contact with acids, alkalis or oxidizing agents.

Conditions to avoid: Elevated temperature (>60°C)

SECTION 11 : TOXICOLOGICAL INFORMATION

No data

SECTION 12 : ECOLOGICAL INFORMATION

No Information is available

SECTION 13 : DISPOSAL CONSIDERATIONS

As local regulations may vary, all waste must be disposed/recycled/reclaimed in accordance with federal, state, and local environmental control regulations.

SECTION 14 : TRANSPORT INFORMATION

UN# 1266
UN Pack group II
UN Class: 3
Shipping Name : Perfumery products
IMDG Class: 3
ICAO/IATA : Class 9 ID8000 Consumer commodity

SECTION 15 : REGULATORY INFORMATION

Title III of the Superfund Amendments & Reauthorization Act (Sara) of 1986 Notification : This product is subject to the reporting requirements of section 313 of Title III of SARA, and Title 40 of the CFR, part 372.

Component	Reporting Threshold
tert-butyl Alcohol CAS#75-65-0	0.75%

California Proposition 65 :

This product contains the following chemicals subject to the reporting requirements of proposition 65.

None

SECTION 16 : OTHER INFORMATION

Hazard Rating

Health :1 Flammability :3 Reactivity :0

Note :

Least	Slight	Moderate	High	Extreme
0	1	2	3	4

The statements made here are based upon technical data that Cosmetix West believes to be reliable, are intended to describe the product with regard to necessary safety protections. They do not guarantee special characteristics. This information is furnished without warranty, expressed or implied, except that it is accurate to the best of our current knowledge.