

**MATERIAL SAFETY DATA SHEET**

**SECTION 1 : CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:** Danica I am Good EDP.

Formula #: RR033109I

Product Description: Liquid

**Manufacturer :** Cosmetix West

143 Oregon Street

El Segundo, CA 90245

Phone : 310 726 3080

Fax : 310 726 3083

**SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS**

INGREDIENTS

CONCENTRATION (%)

Proprietary Blend

**SECTION 3 : HAZARDS IDENTIFICATION**

**Potential Health Effects**

**Eye**

May cause eye irritation. Symptoms include stinging, tearing and redness.

**Skin**

May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**Swallowing**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

**Inhalation**

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See section 8).

**Symptoms of Exposure**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include : stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), cough, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), involuntary eye movement, respiratory depression (slowing of the breathing rate), loss of coordination, confusion, irregular heartbeat, anesthesia, respiratory failure, coma, and death.

**Target Organ Effects**

This product contains ethanol. Alcoholic beverage consumption has been associated with brain damage, heart damage, and pancreatitis in humans. The relevance of this findings to ethanol exposure in industrial environments is uncertain. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals : pancreatic damage, liver damage, brain damage, testis damage. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans : liver damage.

**Cancer Information**

This product contains ethanol. The International Agency for Research on Cancer (IARC) has determined that exposure to ethanol through chronic human consumption of alcoholic

beverages can cause cancer. The relevance of this finding to ethanol exposure in industrial environments is uncertain.

**Other Health Effects**

No data.

**Primary Route(s) of Entry**

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

---

**SECTION 4 : FIRST AID MEASURES**

---

**Eyes**

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

**Skin**

Remove contaminated clothing. Wash exposed area with soap and water.

**Swallowing**

Seek medical attention. Drink water or milk to dilute. If individual is drowsy or unconscious, do not give anything by mouth ; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

**Inhalation**

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention.

---

**SECTION 5 : FIRE FIGHTING MEASURES**

---

**Flash Point** 66 °F (ASTM 93 close up cup method)

**Autoignition Temperature**

No data

**Hazardous Products of Combustion**

May form : carbon dioxide, carbon monoxide and unidentified organic compounds

**Fire and Explosion Hazards**

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

**Extinguishing Media**

Foam, water fog, carbon dioxide, dry chemical

**Fire Fighting Instructions**

Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

**Unusual Fire and Explosion Hazards**

None, material is not pyrophoric. Does not react with water, not oxygen donor, material is shock stable

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

---

**Small Spill**

Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

**Large Spill**

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Ventilate area. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify

authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

**SECTION 7 : HANDLING AND STORAGE**

**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and solid), all hazard precautions given in the data sheet must be observed. All five-gallon pails and larger metal containers, including tank cars and tank trucks, should be grounded and/or bonded when material is transferred.

**Storage**

Store in tightly sealed containers in cool, dry and well-ventilated area. Do not exposure to temperatures above 95°F. Keep away from heat and flame.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eye Protection**

Chemical splash goggles in compliance with OSHA regulations are advised.

**Skin Protection**

Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**Respiratory Protections**

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions. Engineering or administrative controls should be implemented to reduce exposure.

**Local Ventilation**

Local exhaust recommended (Explosion Proof)

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**Boiling Point**

Not Established

**Melting Point**

N/A

**Vapor Pressure**

N/A

**Specific Vapor Density**

N/A (Air = 1.0)

**Specific Gravity**

0.80-0.90 @ 25°C (H<sub>2</sub>O = 1.0)

**Refractive Index**

1.381-1.384 @ 20°C

**pH**

N/A

**Viscosity**

N/A

**Appearance**

Clear

**State**

Liquid

**Physical Form**

Homogeneous liquid

**Color**

Pale yellow to yellow

**Odor**

Floral

**Solubility in water**

Miscible

**VOC**

75%

**SECTION 10 : STABILITY AND REACTIVITY**

**Hazardous Polymerization:** Product will not undergo hazardous polymerization.

**Hazardous Decomposition:** May form: carbon dioxide and carbon monoxide

**Chemical Stability:** Stable under normal circumstances

**Incompatibility:** Avoid contact with acids, alkalis or oxidizing agents.

**Conditions to avoid:** Elevated temperature (>60°C)

**SECTION 11 : TOXICOLOGICAL INFORMATION**

No data

**SECTION 12 : ECOLOGICAL INFORMATION**

No Information is available

**SECTION 13 : DISPOSAL CONSIDERATIONS**

As local regulations may vary, all waste must be disposed/recycled/reclaimed in accordance with federal, state, and local environmental control regulations.

**SECTION 14 : TRANSPORT INFORMATION**

**UN#** 1266  
**UN Pack group** II  
**UN Class:** 3  
**Shipping Name :** Perfumery products  
**IMDG Class:** 3  
**ICAO/IATA :** Class 9 ID8000 Consumer commodity

**SECTION 15 : REGULATORY INFORMATION**

Title III of the Superfund Amendments & Reauthorization Act (Sara) of 1986 Notification : This product is subject to the reporting requirements of section 313 of Title III of SARA, and Title 40 of the CFR, part 372.

Component	Reporting Threshold
tert-butyl Alcohol CAS#75-65-0	0.75%

California Proposition 65 :

This product contains the following chemicals subject to the reporting requirements of proposition 65.

None

**SECTION 16 : OTHER INFORMATION**

**Hazard Rating**

Health :1 Flammability :3 Reactivity :0

Least	Slight	Moderate	High	Extreme
0	1	2	3	4

**Note :**

The statements made here are based upon technical data that Cosmetix West believes to be reliable, are intended to describe the product with regard to necessary safety protections. They do not guarantee special characteristics. This information is furnished without warranty, expressed or implied, except that it is accurate to the best of our current knowledge.