

SAFETY DATA SHEET

Supersedes Date: N/A

Revision Date 16-Nov-2014

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name SpaRitual Gold Flexible Color Lacquer: Neon Crèmes

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Nail polish/lacquer

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Orly International, Inc.
Supplier Address 7710 Haskell Avenue
Van Nuys
CA
91406
US
Supplier Phone Number 818-994-1001
Supplier Email regulatory@orlybeauty.com
Emergency telephone number

2. HAZARDS IDENTIFICATION


Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 15 %

GHS Label elements, including precautionary statements

Signal word	Danger		
Hazard Statements			
Highly Flammable Liquid and vapor			
May cause an allergic reaction			
May cause drowsiness or dizziness			
Flammable liquid and vapor			
			
Appearance	Semi-viscous	Physical State	Liquid
		Odor	Solvent

Precautionary Statements – General

Read label before use. Keep out of reach of children

If medical advice is needed, have product container or label at hand.

Precautionary Statements –Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None known

Unknown Toxicity

15 % Percentage of the mixture consisting of ingredient(s) of unknown toxicity

Other information

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Butyl acetate	123-86-4	20-50	*
Ethyl acetate	141-78-6	10 - 40	*
Nitrocellulose	9004-70-0	10-15	*
Isopropyl alcohol	67-63-0	2-8	*
May Contain Ingredient(s)**			
Titanium dioxide	13463-67-7	0 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

** The SDS is used for a group of substantially similar mixtures whereas the "May Contain" chemicals may vary in %. There are no additional ingredient present, which within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available are listed in section 8

4. FIRST AID MEASURES**First aid measures****General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Call Physician if irritation persists. Check for and remove any contact lenses.

Skin Contact

In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water while removing All contaminated clothes and shoes.

Inhalation

Remove to fresh air. If not breathing, Seek Medical advice.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent Spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Burning sensation.

Causes serious eye irritation

Inhalation

Can cause central nervous system (CNS) depression). May cause drowsiness and dizziness. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin Contact

No known significant effects or critical hazards

Ingestion

Can cause central nervous system (CNS) depression). Irritating to mouth, throat and stomach.

Over exposure signs/symptoms**Eye Contact**

Adverse symptoms may include the following: Pain or irritation, Watering, Redness

Inhalation

Adverse symptom may include the following: Nausea or vomiting, Headache, Drowsiness/fatigue, Dizziness/vertigo, unconsciousness

Skin Contact

No specific data

Ingestion

No specific data

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours

Specific Treatments

No specific treatments

Protection of first aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth to mouth resuscitation.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO₂, water spray or regular foam.

Unsuitable Extinguishing Media

Do not use water jet.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and container may burst, with the risk of a subsequent explosion. Run off to sewer may create fire or explosion hazard.

Uniform Fire Code

Sensitizer: Liquid
Flammable Liquid: I-C

Hazardous Combustion Products

Oxides of Nitrogen, Oxides of Carbon, Carbon aldehyde, Methane

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Special protective actions for fire fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire if this can be done without risk. Use water spray to keep fire exposed containers cool.

Protective equipment and precautions for firefighters

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**For non-emergency personnel**

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off ignition sources. No flares, smoking or flame in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in section 8 on suitable and unsuitable materials. See also information in "For non-emergency personnel".

when handling the product must be grounded. Stop leak if you can do it without risk.

Other Information

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil and air)

Methods and material for containment and cleaning up**Small Spill**

Stop leak if without risk

A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Large Spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Note: see Section 1 for emergency contact information and Section 13 for waste disposal

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling**Handling**

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition.

Conditions for safe storage, including any incompatibilities**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of

ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers.

Incompatible Products

Strong oxidizing agents. Acids. Bases. Chlorinated compounds.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m ³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection

None required for consumer use. If splashes are likely to occur: Tight sealing safety goggles.

Skin and Body Protection

Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Take off contaminated clothing and wash before reuse.

Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. EPHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear viscous liquid
Color	: Various
Odor	: Solvent
<u>Property</u>	
pH	: Not available
Melting Point	: Not available
Boiling Point	: 77.2-338 °C (171-640.4 °F)
Flash Point	: -4 °C (24 °F)
Lower and Upper explosive (Flammable) Limits	: Not available
Vapor Pressure	: Not available
Vapor Density	: Not available
Relative Density	: 0.999
Solubility	: insoluble in water
Solubility in Water	: Not available
Partition Coefficient n-Octane/water	: Not Available
Auto-ignition temperature	: Not available
Viscosity	: Not Available
Oxidizing Properties	: Not Available
Auto ignition temperature	: Not Available
Decomposition temperature	: Not Available
<u>Other information</u>	
Softening Point	: Not Available
VOC Content (%)	: Not Available
Particle Size	: Not Available
Particle size distribution	: No data
Particle Size	: No data

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Acids. Bases. Chlorinated compounds.

Hazardous Decomposition Products

Oxides of Nitrogen, Oxides of Carbon, Carbon aldehyde, Methane

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Not available

Product Information

Product does not present an acute toxicity hazard based on known or supplied information.

Inhalation

Specific test data for the substance or mixture is not available. Can cause central nervous system (CNS) depression.
May cause drowsiness and dizziness. Exposure to
Decomposition products may cause a health hazard. Serious effects may be delayed following exposure

Eye Contact

Causes serious eye irritation

Skin Contact

Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes.
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

This product has NOT been tested on animals for the purpose of obtaining toxicology data. There exists toxicology data for the components of the product which can be found in scientific literature. These data have not been included in this document.

Symptoms

May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

May cause sensitization of susceptible persons. May cause sensitization by skin contact.

Mutagenic Effects

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen or probable carcinogen or possible carcinogen or not classifiable as to carcinogenicity in humans.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropyl alcohol 67-63-0		Group 3		
Titanium dioxide*** 13463-67-7		Group 2B		

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X – Found to be a potential carcinogen by OSHA

***denotes a "May-Contain" ingredient.

Specific Target organ toxicity (single exposure)

Ingredient Name	Category	Route of Exposure	Target Organs
Ethyl acetate	Category 3	Not applicable	Narcotic effects
Butyl Acetate	Category 3	Not applicable	Narcotic effects

Isopropyl alcohol	Category 3	Not applicable	Narcotic effects
-------------------	------------	----------------	------------------

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure

No information available.
 No information available.
 No information available.

Chronic Toxicity

No known effect based on information supplied. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. This product may contain titanium dioxide. If it does, it is in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product.

Target Organ Effects

Eyes. Respiratory system. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Peripheral Nervous System (PNS). Kidney. Liver. Spleen. Systemic Toxicity. Lungs.

Aspiration Hazard
Numerical measures of toxicity Product Information

No information available.
 No information available.

12. ECOLOGICAL INFORMATION

Eco toxicity

There is no specific data available for this product. However, very large releases of this product may be toxic to aquatic life.

Persistence and Degradability

No information available.

Bioaccumulation

No specific information available for this product.

Other adverse effects

No information available.

Ingredient Name	Result	Species	Exposure
Ethyl acetate	Acute LC50 18000 µg/l Fresh water	Fish-Pimephales promelas	96 hours
	Acute EC50 2500000 µg/l Fresh water	Algae- Selenastrum sp	96 hours
	Acute LC50 750000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 154000 µg/l Fresh water	Daphnia- Daphnia cucullata	48 hours
	Acute LC50 212500 µg/l Fresh water	Fish - Heteropneustes fossilis	96 hours
	Chronic NOEC 2400 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 75.6 mg/l Fresh water -	Fish - Pimephales promelas-embryos	32 days
Isopropyl alcohol	Acute LC50 1400000 µg/l Marine	Crustaceans - Crangon crangon	48 hours
	water Acute LC 50 1400000 ug/l	Fish- Gambusia affinis	96 hours

Bioaccumulation Potential

Ingredient Name	Log P _{ow}	BCF	Potential
-----------------	---------------------	-----	-----------

Mobility in Soil

Soil/water partition Coefficient (K_{oc})

Not available

Other adverse effects

No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number

D001 U112 U031







Chemical Name	RCRA	RCRA - Basis for	RCRA - D Series	RCRA - U Series
Ethyl acetate 141-78-6		Included in waste stream: F039		U112

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical	California Hazardous Waste
Ethyl acetate 141-78-6	Toxic Ignitable
Butyl acetate 123-86-4	Toxic
Isopropyl alcohol 67-63-0	Toxic Ignitable

14. TRANSPORT INFORMATION

	<u>DOT</u> <u>Classification</u>	<u>TDG</u> <u>Classification</u>	<u>Mexico</u> <u>Classification</u>	<u>ADR/RID</u> <u>Classification</u>	<u>IMDG</u> <u>Classification</u>	<u>IATA</u> <u>Classification</u>
UN Number	1263	1263	1263	1263	1263	1263
UN Shipping Name	PAINT	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class	3 	3 	3 	3 	3 	3 
Packing group	II	II	II	II	II	II
Environmental Hazard	No	No	No	No	No	No
Additional information	Reportable quantity 12973.5 lbs / 5890 kg(1557.5 gal/5895.9 L) Package sizes shipped in quantities less than the product	-	-	Special Provisions: 640 (C) Tunnel Code (D/E)	-	-

	reportable quantity are not subject to the RQ (reportable quantity) transportation requirements					
--	--	--	--	--	--	--

Special precautions for use:

Transport within Users premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or leakage.

**Transport in Bulk according to
Annex II or MARPOL 73/78
and IBC Cod**

Not available

15. REGULATORY INFORMATION

International Inventories**TSCA**

Complies

DSL

All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold
Isopropyl alcohol - 67-63-0	67-63-0	5-10	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous
Butyl acetate 123-86-4	5000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances	RQ
Ethyl acetate 141-78-6	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product "May contain" the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7*	Carcinogen
CI 77266 - 1333-86-4*	Carcinogen

*Denotes that under Proposition 65, the material must be airborne, unbound, particles of respirable size. If one or both of these chemicals are contained in the product, they are in a non-respirable form. Inhalation of titanium dioxide and/or CI 77266 is unlikely to occur from exposure to this product.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Ethyl acetate 141-78-6	X	X	X	X	
Butyl acetate 123-86-4	X	X	X	X	
Nitrocellulose 9004-70-0	X	X	X		X
Isopropyl alcohol 67-63-0	X	X	X	X	

International Regulations**Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Ethyl acetate 141-78-6 (10 - 30)		Mexico: TWA= 400 ppm Mexico: TWA= 1400 mg/m ³
Butyl acetate 123-86-4 (10 - 30)		Mexico: TWA 150 ppm Mexico: TWA 710 mg/m ³ Mexico: STEL 200 ppm Mexico: STEL 950 mg/m ³
Isopropyl alcohol 67-63-0 (1 - 5)		Mexico: TWA 400 ppm Mexico: TWA 980 mg/m ³ Mexico: STEL 500 ppm Mexico: STEL 1225 mg/m ³
Titanium dioxide 13463-67-7 (0.1 - 1)		Mexico: TWA= 10 mg/m ³ Mexico: STEL= 20 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada**WHMIS Hazard Class**

B2 - Flammable liquid

D2B - Toxic materials



16. OTHER INFORMATION

NFPA	Health Hazards 2	Flammability 3	Instability 1	Physical and Chemical Hazards - Personal Protection
HMIS	Health Hazards 2	Flammability	Physical Hazard 1	X
Comments	New Document			
Revision Date	11-16-2014			
Revision #	1			

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet