

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards



SDS Revision: 1.4

SDS Revision Date: 4/15/2015

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	OPI NAIL ENVY – PINK TO ENVY
1.2	Chemical Name:	Solvent Mixture
1.3	Synonyms:	P/N NT223
1.4	Trade Names:	OPI Nail Envy – Pink To Envy
1.5	Product Use:	Cosmetic Use Only
1.6	Distributor's Name:	OPI Products, Inc.
1.7	Distributor's Address:	13034 Satcoy Street, No. Hollywood, CA 91605 USA
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 16377)
1.9	Business Phone / Fax:	+1 (818) 759-2400 / +1 (818) 759-5776

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC and ADG Code (Australia).</p> <p>WARNING! FLAMMABLE LIQUID AND VAPOUR. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.</p> <p><u>Hazard Statements (H):</u> H226 – Flammable liquid and vapor. H302 – May be harmful if swallowed. H317 – May cause an allergic skin reaction. H319 – Causes serious eye irritation. H402 – Harmful to aquatic life.</p> <p><u>Precautionary Statements (P):</u> P210 – Keep away from heat/sparks/open flames/hot surfaces. – No smoking. P233 - Keep container tightly closed. P243 - Take precautionary measures against static discharge. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs - Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).</p>	 
-----	------------------------	--	---

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
BUTYL ACETATE	123-86-4	AF73500000	204-658-1	15-40	150	200	150	200	NF	200	200	1700	150 TWA	
Flam. Liq. 3; Acute Tox. 5; Skin Irrit. 2; Eye Irrit. 2A, STOT-SE 3; Acute Aq. 3; Chron. Aq. 3; H226, H315, H319, H333, H336, H412														
ETHYL ACETATE	141-78-6	AH5425000	205-500-4	15-40	400	400	200	400	NF	NA	NA	2000	400 TWA	
Flam. Liq. 2; Eye Irrit. 2; STOT SE 3; H225, H319, H336														
ETHANOL (SD ALCOHOL 40B)	64-17-5	KQ6300000	200-578-6	10-30	1000	1900	1880	NF	NF	1000	1900	3300		
Flam. Liq. 2; H225														
NITROCELLULOSE	9004-70-0	AH5425000	NA	7-13	400	400	400	200	NF	NA	NA	2000		
Flam. Liq. 2; H225														
ADIPIC ACID / NEOPENTYL/ GLYCOL / TRIMELLITIC ANHYDRIDE COPOLYMER	28407-73-0	NA	NA	7-13	NA	NA	NF	NF	NF	NA	NA	NA		
Skin Sens. 1; H317														
ISOPROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	3-7	400	500	400	500	NF	400	500	2000	400 TWA	
Flam. Liq. 2; Skin Irrit. 3; Eye Irrit. 2A; STOT SE 3; H225, H316, H319														
TRIBENZOIN	614-33-5	NA	210-379-6	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
TRIMETHYL PENTANYL DIISOBUTYRATE	6846-50-0	SA142000	229-937-9	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
SILICA	7631-86-9	VV7565000	231-545-4	1-5	(10)	NA	NF	NF	NF	(6)	NA	NA		
Eye Irrit. 2A; STOT SE 3; H319, H335														
TRIPHENYL PHOSPHATE	115-86-6	TC840000	204-112-2	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
Aquatic Acute 1; Aquatic Chronic 1; H400, H410														
SUCROSE ACETATE ISOBUTYRATE	126-13-6	WN6550000	204-771-6	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
ETOCRYLENE	5232-99-5	AT6200000	226-029-0	1-5	NA	NA	NF	NF	NF	NA	NA	NA		
BENZOPHENONE-1	131-56-6	DJ0700000	205-029-4	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA		
Sin Irrit. 2; Eye Irrit. 2; STOT SE 3; H315, H319, H335														
HYDROLYZED WHEAT PROTEIN	70084-87-6	NA	NA	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA		


3. COMPOSITION & INGREDIENT INFORMATION – cont'd

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
DIMETHICONE	9006-65-9	NA	NA	< 0.1	NA	NA	NF	NF	NF	NA	NA	NA		
CALCIUM PANTOTHENATE	137-08-6	RU4375000	205-278-9	< 0.1	NA	NA	NF	NF	NF	NA	NA	NA		
CI 15850 (RED 6)	5858-81-1	QJ1975000	227-497-9	< 0.1	NA	NA	NF	NF	NF	NA	NA	NA		

4. FIRST AID MEASURES

4.1	First Aid:	<p>Ingestion: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p>Eyes: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.</p> <p>Skin: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.</p> <p>Inhalation: Remove victim to fresh air at once.</p>											
4.2	Effects of Exposure:	<p>Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.</p> <p>Eyes: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p>Skin: May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact.</p> <p>Inhalation: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).</p>											
4.3	Symptoms of Overexposure:	Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. Irritation of the nose and throat, skin irritation, signs of nervous system depression (e.g., drowsiness, dizziness, loss of coordination and/or fatigue)											
4.4	Acute Health Effects:	Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.											
4.5	Chronic Health Effects:	None known.											
4.6	Target Organs:	Eyes, skin and respiratory system.											
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system).	<table border="1"> <tr> <td>HEALTH</td> <td>1</td> </tr> <tr> <td>FLAMMABILITY</td> <td>3</td> </tr> <tr> <td>PHYSICAL HAZARDS</td> <td>0</td> </tr> <tr> <td>PROTECTIVE EQUIPMENT</td> <td>B</td> </tr> <tr> <td>EYES</td> <td>SKIN</td> </tr> </table>	HEALTH	1	FLAMMABILITY	3	PHYSICAL HAZARDS	0	PROTECTIVE EQUIPMENT	B	EYES	SKIN
HEALTH	1												
FLAMMABILITY	3												
PHYSICAL HAZARDS	0												
PROTECTIVE EQUIPMENT	B												
EYES	SKIN												

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	WARNING! FLAMMABLE LIQUID AND VAPOR! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. Fine mist or sprays may be flammable at temperatures below the flashpoint. If involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO ₂ , NO _x).	
5.2	Extinguishing Methods:	Water Fog, CO ₂ , Halon (if permitted), Dry Chemical, Foam HazChem Code: 3[Y] E Hazard Identification Number: 33	
5.3	Firefighting Procedures:	This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.	

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.4

SDS Revision Date: 4/15/2015

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <u>small spills</u> (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.</p>
-----	---------	--

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.
7.2	Storage & Handling:	Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10).
7.3	Special Precautions:	Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)		ACGIH		NOHSC			OSHA			OTHER
		CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ETHYL ACETATE	400	400	400	200	NF	NA	NA	2000	400 TWA
		BUTYL ACETATE	150	200	150	200	NF	200	200	1700	150 TWA
		ETHANOL (SD ALCOHOL 40B)	1000	1900	1880	NF	NF	1000	1900	3300	
		NITROCELLULOSE	400	400	400	200	NF	NA	NA	2000	
		ISOPROPYL ALCOHOL	400	500	400	500	NF	400	500	2000	400 TWA
		SILICA	(10)	NA	NF	NF	NF	(6)	NA	NA	
8.2	Ventilation & Engineering Controls:	When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.									
8.4	Eye Protection:	Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166.									
8.5	Hand Protection:	If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.									
8.6	Body Protection:	No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.									

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Viscous Liquid
9.2	Odor:	Ester (Fruity) Odor
9.3	Odor Threshold:	NA
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	77 – 130 °C (171 - 266 °F)
9.7	Flashpoint:	-4 °C (24 °F), TCC
9.8	Upper/Lower Flammability Limits:	LEL: 1.0%; UEL: 13.0%
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	NA

9. PHYSICAL & CHEMICAL PROPERTIES – cont'd

9.11	Relative Density:	0.9998-1.0008
9.12	Solubility:	Insoluble
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	1000-3000 cPs
9.17	Other Information:	NA

10. STABILITY & REACTIVITY

10.1	Stability:	Stable under ambient conditions when stored properly (See Section 7, Storage and Handling)
10.2	Hazardous Decomposition Products:	If exposed to extremely high temperatures, the products of thermal decomposition may include irritation vapors and carbon oxide gases (e.g. CO, CO ₂).
10.3	Hazardous Polymerization:	May occur if exposed to extremely high temperatures.
10.4	Conditions to Avoid:	High temperatures and incompatible substances.
10.5	Incompatible Substances:	Strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide).

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has not been tested on animals to obtain toxicology data. There is toxicology data for some components of the product, which are found in scientific literature. This data is presented below: <u>Ethyl Acetate</u> : LD ₅₀ (oral, rat) = 11,300 mg/kg; <u>Butyl Acetate</u> : LD ₅₀ (oral, rat) = 11,400 mg/kg; <u>Isopropyl Alcohol</u> : LD ₅₀ (oral, rat) = 5,840 mg/kg;		
11.3	Acute Toxicity:	See Section 4.4		
11.4	Chronic Toxicity:	See Section 4.5		
11.5	Suspected Carcinogen:	This product contains Isopropyl Alcohol, which is not carcinogenic to humans, but is listed as Group 3 carcinogen by IARC.		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to cause mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to cause embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See section 2.3		
11.8	Biological Exposure Indices:	NA		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: <u>Ethyl Acetate</u> : K _{OC} = 0.73. Water solubility: 64,000 mg/L. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. <u>Butyl Acetate</u> : K _{OC} = 1.82. Water solubility: 120 parts H ₂ O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. <u>Isopropyl Alcohol</u> : Log K _{OW} = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate.
12.2	Effects on Plants & Animals:	There are no specific data for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Waste disposal must be in accordance with appropriate Federal, state, and local regulations.
13.2	Special Considerations:	U.S. EPA Waste Number: D001 (characteristic - ignitable)


Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.4

SDS Revision Date: 4/15/2015



14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.



14.1	49 CFR (GND):	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020 UN1263, PAINT, 3, II	
14.2	IATA (AIR):	CONSUMER COMMODITY, 9, ID8000 (IP VOL ≤ 0.5 L) UN1263, PAINT, 3, II	
14.3	IMDG (OCN):	UN1263, PAINT, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) UN1263, PAINT, 3, II	
14.4	TDGR (Canadian GND):	UN1263, PAINT, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) UN1263, PAINT, 3, II	
14.5	ADR/RID (EU):	UN1263, PAINT, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) UN1263, PAINT, 3, II	
14.6	SCT (MEXICO):	UN1263, PINTURA, 3, II, (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L) UN1263, PINTURA, 3, II	
14.7	ADGR (AUS):	UN1263, PAINT, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) UN1263, PAINT, 3, II	

* This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package)

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	SARA 304 (40 CFR Table 302.4) – <u>Butyl Acetate</u> , <u>Ethyl Acetate</u> . This product contains <u>Isopropyl Alcohol</u> , a substance subject to SARA Title III (313) reporting and 40 CFR part 373.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	<u>Butyl Acetate</u> : 2,270 kg (5,000 lbs); <u>Ethyl Acetate</u> : 2,270 kg (5,000 lbs)	
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B2 Flammable Liquid.	
15.7	State Regulatory Information:	<p><u>Butyl Acetate</u> is found on the following state criteria lists: California Hazardous Substances List (CA), Delaware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List (WA).</p> <p><u>Ethyl Acetate</u> is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, WA, and Wisconsin Hazardous Substances List (WI).</p> <p><u>Nitrocellulose</u> is found on the following state criteria lists: FL, MA, and PA.</p> <p><u>Isopropyl Alcohol</u> is found on the following state criteria lists: FL, MA, MN, NJ, PA, and WA.</p> <p>No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p>	
15.8	Other Requirements:	<p>The primary components of this product are listed in Annex I of EU Directive 67/548/EEC:</p> <p><u>Isopropyl Alcohol</u>: Flammable, Irritant (F, Xi); <u>Butyl Acetate</u>: Flammable. (F); <u>Ethyl Acetate</u>: Flammable, Irritant (F, Xi). <u>Risk Phrases</u> (R) – R11-36-66-67 – Highly flammable. Harmful if swallowed. Irritating to eyes. Vapors may cause drowsiness and dizziness. Repeated exposure may cause skin dryness and cracking. <u>Safety Phrases</u> (S): S1/2-7/9-16-20/21-24/25-26-28-33-46 - Keep locked up and out of the reach of children. Keep container tightly closed and in a well-ventilated place. Keep away from sources of ignition. When using do not eat, drink or smoke. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash with plenty of soap and warm water. Take precautionary measures against static discharges. If swallowed, seek medical advice immediately and show this container or label.</p>	

16. OTHER INFORMATION

16.1	Other Information:	WARNING! FLAMMABLE LIQUID AND VAPOUR. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. For specific first aid treatment (see section 4 of this Safety Data Sheet). Store in a well-ventilated place. Keep cool. KEEP OUT OF REACH OF CHILDREN.	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 http://www.opi.com	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	

G	
H	
I	
J	
K	
X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD ₀₁	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD ₀₁ , LD ₀₁ , & LD ₀₁ or TC, TC ₀₁ , LC ₀₁ , & LC ₀₁	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment