

**Issuing Date** No data available

**Revision Date** 16-Jul-2018

**Revision Number** 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

<b>Product Name</b>	<b>CND Vinylux Glitter Top Coat</b>
<b>Bulk Number</b>	4705405000
<b>Brand</b>	CND
<b>Category</b>	Nail

### Other means of identification

<b>Physical state</b>	Liquid
-----------------------	--------

<b>UPC Code(s)</b>	xxxx
<b>Synonyms</b>	None

### Recommended use of the chemical and restrictions on use

<b>Recommended Use</b>	No information available
------------------------	--------------------------

<b>Restrictions on use</b>	This industrial Safety Data Sheet is not intended for consumers and does not address consumer use of the product. Please read the labeling on the consumer package for proper use of this material. For external use only. Use only as directed.
----------------------------	--

<b>Uses advised against</b>	No information available
-----------------------------	--------------------------

### Details of the supplier of the safety data sheet

<b>Supplier Name</b>	Revlon
----------------------	--------

<b>Supplier Address</b>	2121 Route 27, Edison, NJ 08818
-------------------------	---------------------------------

<b>Supplier Phone Number</b>	(732) 287-1400
------------------------------	----------------

<b>Supplier Information</b>	Revlon Research Center 2121 Route 27 Edison, NJ 08818 Telephone #: (732) 287-1400
-----------------------------	---

### Emergency telephone number

<b>Chemical Emergency Phone Number</b>	703-527-3887
<b>Company Emergency Phone Number</b>	Chemtrec 1-800-424-9300
<b>Emergency Telephone Number</b>	Medical Emergencies: 303-739-1110

<b>Emergency Telephone Number</b>	Medical Emergencies: 303-739-1110 CHEMTREC: 1-800-424-9300 or 703-527-3887 (spill related emergencies)
-----------------------------------	--

## 2. HAZARDS IDENTIFICATION


### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Acute toxicity - Inhalation (Vapors)	Category 3
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

### GHS Label elements, including precautionary statements

#### Emergency Overview

<b>Signal word</b>	<b>Danger</b>		
<b>Hazard statements</b> Toxic if inhaled Causes serious eye irritation Highly flammable liquid and vapor			
<b>Appearance</b> No information available	<b>Physical state</b> Liquid	<b>Odor</b> Characteristic	

#### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves/protective clothing/eye protection/face protection  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Wash face, hands and any exposed skin thoroughly after handling  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ ventilating/ lighting/ equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

#### Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
Specific treatment (see supplemental first aid instructions on this label)

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Call a POISON CENTER or doctor

#### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish

#### Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

#### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other information

Harmful to aquatic life with long lasting effects  
Harmful to aquatic life

#### Interactions with Other Chemicals

No information available.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No	Percent	Trade Secret
Butyl acetate	123-86-4	<50	-
Ethyl acetate	141-78-6	<25	-
Nitrocellulose	9004-70-0	<10	-
Isopropyl alcohol	67-63-0	<5	-

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

#### First aid measures

Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact	Wash skin with soap and water.
Inhalation	Remove to fresh air.
Ingestion	Rinse mouth immediately and drink plenty of water.

#### Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects	No information available.
-------------------------------------	---------------------------

#### Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### **Unsuitable extinguishing media**

CAUTION: Use of water spray when fighting fire may be inefficient.

### **Specific hazards arising from the chemical**

No information available.

### **Explosion Data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

### **Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### **Personal precautions, protective equipment and emergency procedures**

#### **Personal precautions**

Use personal protective equipment as required. Ensure adequate ventilation. Take precautionary measures against static discharges. See section 8 for more information. Avoid breathing vapors or mists. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes or clothing. Remove all sources of ignition. Do not breathe vapor or mist.

#### **Environmental precautions**

#### **Environmental precautions**

Local authorities should be advised if significant spillages cannot be contained. Do not flush into surface water or sanitary sewer system.

### **Methods and material for containment and cleaning up**

#### **Methods for containment**

Prevent further leakage or spillage if safe to do so.

#### **Methods for cleaning up**

Prevent product from entering drains. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal. Take up with sand, earth or other non-combustible absorbent material. Use personal protective equipment as required.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapor or mist. Ensure adequate ventilation. Remove all sources of ignition. Avoid contact with eyes. Refer to Section 8.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers.

**Incompatible Products** Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure Guidelines** This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butyl acetate 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
Ethyl acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>

### Appropriate engineering controls

**Engineering Measures** Ventilation systems Ensure that eyewash stations and safety showers are close to the workstation location

### Individual protection measures, such as personal protective equipment

**Eye/face protection** No special protective equipment required.

**Skin and body protection** None under normal use conditions. None required for consumer use.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. Ensure adequate ventilation.

**Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical and Chemical Properties**

<b>Physical state</b>	Liquid	<b>Odor</b>	No information available
<b>Appearance</b>	Holographic silver glitter	<b>Odor Threshold</b>	No information available
<b>Color</b>	Holographic silver glitter		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	77 °C / 171 °F	None known	
Flash Point	-5 C / 23 F	CC (closed cup)	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	0.99-1.01		
Water Solubility	Insoluble in water		
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	

**Other Information**

VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

None known based on information supplied.

**Incompatible materials**

Strong oxidizing agents.

**Hazardous Decomposition Products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Product Information</b>	Specific test data for the substance or mixture is not available.
<b>Inhalation</b>	Specific test data for the substance or mixture is not available.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available.

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Butyl acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Ethyl acetate 141-78-6	= 5620 mg/kg ( Rat )	> 18000 mg/kg ( Rabbit ) > 20 mL/kg ( Rabbit )	= 4000 ppm ( Rat ) 4 h
Nitrocellulose 9004-70-0	> 5 g/kg ( Rat )	-	-
Isopropyl alcohol 67-63-0	= 1870 mg/kg ( Rat )	= 4059 mg/kg ( Rabbit )	= 72600 mg/m <sup>3</sup> ( Rat ) 4 h

#### Information on toxicological effects

**Symptoms** No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.

**Mutagenic Effects** No information available.

**Carcinogenicity** Contains no ingredient listed as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Nitrocellulose 9004-70-0		Group 2A		X
Isopropyl alcohol 67-63-0		Group 3		X

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Target organ effects** Respiratory system. Eyes. Skin. Central nervous system (CNS). lungs.

**Aspiration Hazard** No information available.

#### Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)**  
7,884.00 mg/kg  
**ATEmix (dermal)**

20,103.00 mg/kg  
**ATEmix (inhalation-dust/mist)**  
1,719.00 mg/l  
**ATEmix (inhalation-vapor)**  
3.60 ATEmix

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Butyl acetate 123-86-4	72h EC50: = 674.7 mg/L (Desmodesmus subspicatus)	96h LC50: 17 - 19 mg/L (Pimephales promelas) 96h LC50: = 100 mg/L (Lepomis macrochirus) 96h LC50: = 62 mg/L (Leuciscus idus)		24h EC50: = 72.8 mg/L
Ethyl acetate 141-78-6	48h EC50: = 3300 mg/L (Desmodesmus subspicatus)	96h LC50: 220 - 250 mg/L (Pimephales promelas) 96h LC50: = 484 mg/L (Oncorhynchus mykiss) 96h LC50: 352 - 500 mg/L (Oncorhynchus mykiss)		48h EC50: = 560 mg/L
Isopropyl alcohol 67-63-0	72h EC50: > 1000 mg/L (Desmodesmus subspicatus) 96h EC50: > 1000 mg/L (Desmodesmus subspicatus)	96h LC50: = 9640 mg/L (Pimephales promelas) 96h LC50: > 1400000 µg/L (Lepomis macrochirus) 96h LC50: = 11130 mg/L (Pimephales promelas)		48h EC50: = 13299 mg/L

### Persistence and Degradability

No information available.

### Bioaccumulation

No information available

Chemical name	Log Pow
Butyl acetate 123-86-4	1.81
Ethyl acetate 141-78-6	0.6
Isopropyl alcohol 67-63-0	0.05

### Other adverse effects

No information available.

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Disposal methods** Dispose of contents/containers in accordance with local regulations.

**Contaminated Packaging** Do not reuse empty containers.

**US EPA Waste Number** D001 U112

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Butyl acetate 123-86-4	Toxic
Ethyl acetate 141-78-6	Toxic Ignitable
Nitrocellulose 9004-70-0	Ignitable in ether and alcohol Reactive in ether and alcohol
Isopropyl alcohol 67-63-0	Toxic Ignitable

### 14. TRANSPORT INFORMATION

#### DOT

**Proper Shipping Name** Consumer Commodity ORM-D

#### IATA

**Proper Shipping Name** Consumer Commodity ID8000

#### IMDG/IMO

**Proper Shipping Name** UN1263 Paint, Class 3, Packing Group II, Limited Quantity

-

**Bulk Description** UN1263, Paint, Class 3, PG II

### 15. REGULATORY INFORMATION

#### International Inventories

TSCA Complies  
DSL All components are listed either on the DSL or NDSL.

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

#### US Federal Regulations

##### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS-No	Percent	SARA 313 - Threshold Values %
Isopropyl alcohol - 67-63-0	67-63-0	<5	1.0

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl acetate 123-86-4	5000 lb			X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethyl acetate 141-78-6	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Silica - 7631-86-9	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Butyl acetate 123-86-4	X	X	X	X	
Ethyl acetate 141-78-6	X	X	X	X	
Nitrocellulose 9004-70-0	X	X	X		X
Isopropyl alcohol 67-63-0	X	X	X	X	

**International Regulations**

Component	Carcinogen Status	Exposure Limits
Butyl acetate 123-86-4 ( <50 )		Mexico: TWA 150 ppm Mexico: TWA 710 mg/m <sup>3</sup> Mexico: STEL 200 ppm Mexico: STEL 950 mg/m <sup>3</sup>
Ethyl acetate 141-78-6 ( <25 )		Mexico: TWA 400 ppm Mexico: TWA 1400 mg/m <sup>3</sup>
Isopropyl alcohol 67-63-0 ( <5 )		Mexico: TWA 400 ppm Mexico: TWA 980 mg/m <sup>3</sup> Mexico: STEL 500 ppm

		Mexico: STEL 1225 mg/m <sup>3</sup>
--	--	-------------------------------------

Canada  
WHMIS Hazard Class  
Not determined

## 16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 3	Instability 0	Physical and Chemical Hazards -
HMIS	Health hazards 2 *	Flammability 3	Physical Hazard 0	Personal Protection X

Chronic Hazard Star Legend \* = Chronic Health Hazard

Prepared By	Revlon Research Center, Edison, NJ
Revision Date	16-Jul-2018
Revision Note	No information available

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Cosmetic products are exempted from Safety Data Sheets by article 2.6 (b) of regulation (EC)n 1907/2006 concerning the Registration, Evaluation, Authorization and Restriction of chemicals (REACH) in Europe. Cosmetic products are partially exempt from Canada's Workplace Hazardous Materials Information System (WHMIS) by section C of the regulation. Cosmetic product for consumer use are exempted from labeling requirements under the United States Occupational Safety and Health Administration's Hazard Communication Standard 29 CFR 1910.1200 under section 29 CFR 1910.1200(b)(5)(iii). Cosmetics are covered by the Food and Drug Administration's Food, Drug and Cosmetic Act and Consumer Product Safety Act.

**End of Safety Data Sheet**