

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Identification

Reviewed on 01/10/2019


 Product Identifier · Trade Name: NeoStrata Oily Skin Solution NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution **Exvuiance Professional Clarifying Solution RoC Oil Control Glycolic 8.0** · Product Number: FLA#: 022-097 · Relevant identified uses of the substance or mixture and uses advised against: · Product Description: Cosmetics, personal care products · Details of the Supplier of the Safety Data Sheet:

Manufacturer/Supplier: NeoStrata Company Inc. 307 College Road East Princeton, NJ 08540 Phone: +1-609-520-0715 Fax: +1-609-986-1928 www.neostrata.com

Responsible Person: NeoStrata UG, DE-41470 Neuss Emergency telephone number: Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887


Hazard(s) Identification

· Classification of the substance or mixture:



H226 Flammable liquid and vapor.

Corrosion





STOT SE 3 H335 May cause respiratory irritation.

Aquatic Acute 3 H402 Harmful to aquatic life.

· Label elements:

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



· Signal word: Danger



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Exuv Exvu	Strata Professional Pore Clearing Solution viance Clarifying Solution viance Professional Clarifying Solution Oil Control Glycolic 8.0
	ining components of labeling:
Glycolic acid Denatured Etha	nol
Ammonium Hyd	
Hazard statem	
	le liquid and vapor.
	erious eye damage.
	e respiratory irritation.
H402 Harmful to	
Precautionary	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P210 P240	Ground/bond container and receiving equipment.
P240 P241	
P241 P242	Use explosion-proof electrical/ventilating/lighting/equipment.
P242 P243	Use only non-sparking tools. Take precautionary measures against static discharge.
P261	
P264	Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.
P270	
P270 P271	Do not eat, drink or smoke when using this product.
P301+P310	Use only outdoors or in a well-ventilated area.
P321	If swallowed: Immediately call a poison center/doctor.
P321 P330	Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). Rinse mouth.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
F3007F3017F3	38 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,
P312	present and easy to do. Continue rinsing.
P332+P313	Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.
Unknown acut	

3 Composition/Information on Ingredients

· Chemica	l charac	terization:	Mixtures
-----------	----------	-------------	----------

· Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:

2 angoi e ao e e inpeni		
CAS: 64-17-5	Ethanol	15-35%
RTECS: KQ 6300000	♦ Flam. Liq. 2, H225; ♦ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: NeoStrata Oily Skin Solution NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution Exvuiance Professional Clarifying Solution RoC Oil Control Glycolic 8.0

CAS: 79-14-1 RTECS: MC 5250000	Glycolic acid ♦ Skin Corr. 1A, H314; Eye Dam. 1, H318; ♦ Acute Tox. 4, H302	5-10%
CAS: 57-55-6 RTECS: TY 2000000	Propylene Glycol Eye Irrit. 2B, H320	2-12%
CAS: 1336-21-6	Ammonium Hydroxide vPvB ♦ Acute Tox. 3, H331; ♦ Skin Corr. 1B, H314; Eye Dam. 1, H318; ♦ Aquatic Acute 1, H400; ♦ Acute Tox. 4, H302	≤2.5%
CAS: 18472-51-0	D-gluconic acid, compound with N,N"-bis(4-chlorophenyl)-3,12-diimino- 2,4,11,13-tetraazatetradecanediamidine (2:1) Aquatic Chronic 1, H410	≤2.5%

4 First-Aid Measures

· Description of first aid measures

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Generally the product does not irritate the skin.

If skin irritation occurs, consult a doctor.

- After eye contact:
- If easy to do so, remove contact lenses if worn.

Hold eyelids apart and flush eyes with plenty of water for at least 20 minutes.

Have eyes examined and tested by medical personnel.

Get immediate medical attention.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:
- No further relevant information available.

5 Fire-Fighting Measures

- Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters
- Special protective equipment for firefighters: No special measures required.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: NeoStrata Oily Skin Solution

NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution Exvuiance Professional Clarifying Solution RoC Oil Control Glycolic 8.0

· Reference to other sections:

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

Protective Action Criteria for Chemicals

Ethanol	1,800 ppm
Glycolic acid	25 mg/m³
Propylene Glycol	30 mg/m³
Ammonium Hydroxide	61 ppm
Tetrasodium ethylenediaminetetraacetate	75 mg/m³
Ethanol	3300* ppm
Glycolic acid	280 mg/m ³
Propylene Glycol	1,300 mg/m³
Ammonium Hydroxide	330 ppm
Tetrasodium ethylenediaminetetraacetate	830 mg/m³
Ethanol	15000* ppm
Glycolic acid	390 mg/m³
Propylene Glycol	7,900 mg/m³
Ammonium Hydroxide	2,300 ppm
Tetrasodium ethylenediaminetetraacetate	5,000 mg/m³
	Ethanol Glycolic acid Propylene Glycol Ammonium Hydroxide Tetrasodium ethylenediaminetetraacetate Ethanol Glycolic acid Propylene Glycol Ammonium Hydroxide Tetrasodium ethylenediaminetetraacetate Ethanol Glycolic acid Propylene Glycol Ammonium Hydroxide Tetrasodium ethylenediaminetetraacetate

7 Handling and Storage

· Handling

- **Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect from heat.
 Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Protect from heat and direct sunlight.
- Specific end use(s): No further relevant information available.





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: NeoStrata Oily Skin Solution NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution Exvuiance Professional Clarifying Solution

RoC Oil Control Glycolic 8.0

8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:

64-17-5 Ethanol

- PEL Long-term value: 1900 mg/m³, 1000 ppm
- REL Long-term value: 1900 mg/m³, 1000 ppm
- TLV Short-term value: 1880 mg/m³, 1000 ppm

57-55-6 Propylene Glycol

WEEL Long-term value: 10 mg/m³

• Additional information: The lists that were valid during the creation of this SDS were used as basis.

- · Exposure controls:
- Personal protective equipment
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

- · Protection of hands: Not required.
- · Material of gloves: Not applicable.
- · Penetration time of glove material: Not applicable.
- · Eye protection:



Tightly sealed goggles required in a manufacturing setting only.

· Limitation and supervision of exposure into the environment: None

9 Physical and Chemical Properties

· Information on basic physical and chemical properties

· General Information	u chemical properties
· Appearance:	
Form:	Liquid
Color:	Clear
· Odour:	Characteristic
· Odor threshold:	Not determined.
[.] pH-value @ 20 °C (68 °F):	3.6-4.2
 Change in condition Melting point/Melting range: 	Not determined.





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: NeoStrata Oily Skin Solution NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution Exvuiance Professional Clarifying Solution RoC Oil Control Glycolic 8.0

Boiling point/Boiling range:	Undetermined.
· Flash point:	35 °C (95 °F) (closed cup)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	425 °C (797 °F)
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	0.0 Vol % 15.0 Vol %
· Vapor pressure @ 20 °C (68 °F):	59 hPa (44.3 mm Hg)
 Density @ 25 °C (77 °F): Relative density: Vapor density: Evaporation rate: 	0.97 g/cm³ (8.0947 lbs/gal) Not determined. Not determined. Not determined.
 Solubility in / Miscibility with: Water: 	Miscible
· Partition coefficient (n-octanol/water,): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
 Solvent content: Organic solvents: VOC content: Other information: 	25.0 % 35.0 % No further relevant information available.
10 Stability and Reactivity	

· Reactivity:

No further relevant information available. The product is stable under normal conditions

No further relevant information available.

- · Chemical stability:
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Heat, flame and ignition sources.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: NeoStrata Oily Skin Solution

NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution Exvuiance Professional Clarifying Solution RoC Oil Control Glycolic 8.0

1 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:
- 79-14-1 Glycolic acid
- Oral LD50 1950 mg/kg (Rat)
- Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Irritating effect.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Irritant
- · Carcinogenic categories:
- · IARC (International Agency for Research on Cancer):
- Group 1 Carcinogenic to humans
- Group 2A Probably carcinogenic to humans
- Group 2B Possibly carcinogenic to humans
- Group 3 Not classifiable as to its carcinogenicity to humans
- Group 4 Probably not carcinogenic to humans

The IARC (the International Agency for Research on Cancer) concluded that ethanol found alcoholic beverages to be Group 1 - Carcinogenic to humans. All other instances it is not consider carcinogenic.

64-17-5 Ethanol

• NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

2 Ecological Information

- · Toxicity:
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes: Not known to be hazardous to water.
- Results of PBT and vPvB assessment:
- **PBT:** Not applicable.

· vPvB:

1336-21-6 Ammonium Hydroxide

• Other adverse effects: No further relevant information available.

1



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: NeoStrata Oily Skin Solution NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution Exvuiance Professional Clarifying Solution RoC Oil Control Glycolic 8.0


13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging
- · Recommendation: Disposal must be made according to official regulations.

4 Transport Information





Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: NeoStrata Oily Skin Solution NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution Exvuiance Professional Clarifying Solution **RoC Oil Control Glycolic 8.0** · Label: 3 ·IMDG Limited Quantity · Class: 3 Flammable liquids · Label: 3+ID8000

·IATA





♥	
· Class:	3 Flammable liquids
· Label:	3+ID8000
· Packing group:	
· DOT, ADR/ADN, IMDG, IATA	III
 Environmental hazards: 	Not applicable.
 Special precautions for user: 	Warning: Flammable liquids
Danger code (Kemler):	30
· EMS Number:	F-E, <u>S-E</u>
 Transport in bulk according to Annex II of 	of
MARPOL73/78 and the IBC Code:	Not applicable.
• Transport/Additional information:	
·DOT	
· Quantity limitations:	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
· Remarks:	Special marking with the symbol (fish and tree).
· ADR/ADN	
• Excepted quantities (EQ):	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDO	
	51
 Limited quantities (LQ): 	5L



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: NeoStrata Oily Skin Solution NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution Exvuiance Professional Clarifying Solution **RoC Oil Control Glycolic 8.0**

 Excepted quantities (EQ): 	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
• UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL
-	ALCOHOL), GLYCOLIC ACID), 3, III

15 Regulatory Information

Section 35	55 (extremely hazardous substances):	
None of the	e ingredients are listed.	
Section 31	13 (Specific toxic chemical listings):	
1336-21-6	Ammonium Hydroxide	
TSCA (To	xic Substances Control Act):	
All ingredie	ents are listed or exempt from listing.	
	Proposition 65:	
	s known to cause cancer:	
None of the	e ingredients are listed.	
	s known to cause reproductive toxicity for females:	
None of the	e ingredients are listed.	
Chemicals	s known to cause reproductive toxicity for males:	
None of the	e ingredients are listed.	
Chemicals	s known to cause developmental toxicity:	
64-17-5 Et	thanol	
New Jerse	ey Right-to-Know List:	
64-17-5		
57-55-6	Propylene Glycol	
1336-21-6	Ammonium Hydroxide	
New Jerse	ey Special Hazardous Substance List:	
64-17-5	Ethanol	CA, MU, TE, F
1336-21-6	Ammonium Hydroxide	СО
Pennsylva	ania Right-to-Know List:	
64-17-5	Ethanol	
	Propylene Glycol	
1336-21-6	Ammonium Hydroxide	
Pennsylva	ania Special Hazardous Substance List:	
1336-21-6	Ammonium Hydroxide	

A3



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: NeoStrata Oily Skin Solution

NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution Exvuiance Professional Clarifying Solution RoC Oil Control Glycolic 8.0

• TLV (Threshold Limit Value established by ACGIH):

64-17-5 Ethanol

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



· Signal word: Danger

• *Hazard-determining components of labeling:* Glycolic acid

Denatured Ethanol

Ammonium Hydroxide

· Hazard statements:

H226 Flammable liquid and vapor.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H402 Harmful to aquatic life.

· Precautionary statements:

i i ccuulionui y Sic	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P321	Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
P330	Rinse mouth.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P312	Call a poison center/doctor if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
D402 D22E	Store in a well ventilated place. Keep gool

P403+P235 Store in a well-ventilated place. Keep cool.





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: NeoStrata Oily Skin Solution

NeoStrata Professional Pore Clearing Solution Exuviance Clarifying Solution Exvuiance Professional Clarifying Solution RoC Oil Control Glycolic 8.0

P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

• Date of preparation / last revision: 01/10/2019 / 15

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Identifica	ion	
Product Ide	ntifier	
	: Exuviance Purifying Clay Masque Exuviance Professional Purifying Clay Masque WORKS BEAUTY Clay Mask mber: FLA#: 268-183	
	entified uses of the substance or mixture and uses advised against: scription: Cosmetics, personal care products	
Details of th Manufactur NeoStrata C 307 College Princeton, N Phone: +1-6 Fax: +1-609 www.neostra	ompany Inc. Road East J 08540 09-520-0715 986-1928	
	Person: NeoStrata UG, DE-41470 Neuss <i>telephone number:</i> Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887	
Hazard(s)	Identification	
Hazard pict Signal word Hazard stat H320 Cause Precautiona P264 P305+P351- P337+P313 Unknown a This value re 29.9 % of the Hazard(s) n	 Imments is classified and labeled according to the Globally Harmonized System (GHS). ograms: Non-Regulated Material ? Warning ements: s eye irritation. rry statements: Wash thoroughly after handling. P338 If in eyes: Rinse cautiously with water for several minutes. Remove conta present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. cute toxicity: fers to knowledge of known, established toxicological or ecotoxicological values. e mixture consists of component(s) of unknown toxicity. ot otherwise classified (HNOC): None known 	ct le
Composit	ion/Information on Ingredients	
Description	naracterization: Mixtures : Mixture of substances listed below with non-hazardous additions.	
1332-58-7	Components:	1
	Talc (Mg3H2(SiO3)4) () Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
90-80-2	δ-Gluconolactone () STOT SE 3, H335	



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/23/2019

Reviewed on 01/23/2019

Trade Name: Exuviance Purifying Clay Masque Exuviance Professional Purifying Clay Masque WORKS BEAUTY Clay Mask

	Polyethylene glycol stearate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	≤2.5%
	Titanium Dioxide	≤2.5%
	🚸 Carc. 2, H351	
59259-38-0	I-Menthyl lactate	≤2.5%
	Aquatic Acute 3, H402; Aquatic Chronic 3, H412	
1310-73-2	Sodium Hydroxide	≤2.5%
	🚸 Skin Corr. 1A, H314	

• Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

Description of first aid measures

· General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: If skin irritation occurs, consult a doctor.
- After eye contact:

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

Rinse opened eye for several minutes under running water.

• After swallowing: If swallowed and symptoms occur, consult a doctor.

- · Information for doctor
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

- Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- For safety reasons unsuitable extinguishing agents: No further relevant information.
- Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures: Not required.
- *Environmental precautions:* Do not allow to enter sewers/surface or ground water.

• **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

Dispose of the collected material according to regulations.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/23/2019

Trade Name: Exuviance Purifying Clay Masque Exuviance Professional Purifying Clay Masque WORKS BEAUTY Clay Mask

· Reference to other sections:

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

Protective Action Criteria for Chemicals

107-88-0	1,3-Butanediol	120 mg/m³
13463-67-7	Titanium Dioxide	30 mg/m³
122-99-6	2-Phenoxyethanol	1.5 ppm
36653-82-4	1-Hexadecanol	1.6 mg/m³
1310-73-2	Sodium Hydroxide	0.5 mg/m³
9005-00-9	Polyoxyethylene(20) stearyl ether	5.7 mg/m³
PAC-2:		
107-88-0	1,3-Butanediol	1,300 mg/m³
13463-67-7	Titanium Dioxide	330 mg/m³
122-99-6	2-Phenoxyethanol	16 ppm
36653-82-4	1-Hexadecanol	18 mg/m³
1310-73-2	Sodium Hydroxide	5 mg/m³
9005-00-9	Polyoxyethylene(20) stearyl ether	63 mg/m³
PAC-3:		
107-88-0	1,3-Butanediol	4,500 mg/m³
13463-67-7	Titanium Dioxide	2,000 mg/m³
122-99-6	2-Phenoxyethanol	97 ppm
36653-82-4	1-Hexadecanol	110 mg/m³
1310-73-2	Sodium Hydroxide	50 mg/m³
9005-00-9	Polyoxyethylene(20) stearyl ether	380 mg/m³

7 Handling and Storage

· Handling

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s): No further relevant information available.
- 8 Exposure Controls/Personal Protection

• Additional information about design of technical systems: No further data; see section 7.

Reviewed on 01/23/2019

(Contd. on page 4)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/23/2019

Reviewed on 01/23/2019

Trade Name: Exuviance Purifying Clay Masque Exuviance Professional Purifying Clay Masque WORKS BEAUTY Clay Mask

· Control parameters:

Components with occupational exposure limits:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

1332-58-7 Kaolin

- PEL Long-term value: 15* 5** mg/m³ *total dust **respirable fraction REL Long-term value: 10* 5** mg/m³
- *total dust **respirable fraction TLV Long-term value: 2* mg/m³
- E; as respirable fraction

9004-99-3 Polyethylene glycol stearate

TWA Long-term value: 10 mg/m³

1310-73-2 Sodium Hydroxide

- PEL Long-term value: 2 mg/m³
- REL Ceiling limit value: 2 mg/m³
- TLV Ceiling limit value: 2 mg/m³

• Additional information: The lists that were valid during the creation of this SDS were used as basis.

- Exposure controls:
- · Personal protective equipment
- General protective and hygienic measures:
- The usual precautionary measures for handling chemicals should be followed.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing and wash before reuse.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Breathing equipment: Not required.
- Protection of hands: Not required.
- Material of gloves: Not applicable.
- · Penetration time of glove material: Not applicable.
- Eye protection:



Tightly sealed goggles recommended in a manufacturing setting only.

· Limitation and supervision of exposure into the environment: None

9 Physical and Chemical Properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:
 - Form:
 - Color:
- · Odour:
- · Odor threshold:

Cream Light green Characteristic Not determined.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/23/2019

ing Clay Masque

Reviewed on 01/23/2019

Trade Name: Exuviance Purifying Clay Masque Exuviance Professional Purifying Clay Masque WORKS BEAUTY Clay Mask

· pH-value:	Not applicable.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not determined. ≥100 °C (≥212 °F)
· Flash point:	None
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	Not applicable
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
• Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure @ 20 °C (68 °F):	≤23 hPa (≤17.3 mm Hg)
 Density: Relative density: Vapor density: Evaporation rate: 	Not determined. Not determined. Not determined.
 Solubility in / Miscibility with: Water: 	Soluble.
· Partition coefficient (n-octanol/water)	: Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
 Solvent content: Organic solvents: Water: VOC content: 	0.8 % 48.8 % 0.77 %
Solids content: • Other information:	45.3 % No further relevant information available.
10 Stability and Reactivity	

· Reactivity:

No further relevant information available.

The product is stable under normal conditions

No further relevant information available.

· Chemical stability: Stable under normal conditions.

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.

· Incompatible materials: No further relevant information available.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/23/2019

Trade Name: Exuviance Purifying Clay Masque Exuviance Professional Purifying Clay Masque WORKS BEAUTY Clay Mask

· Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological Information

· Information on	toxicological	effects:
------------------	---------------	----------

• Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:				
13463-67	13463-67-7 Titanium Dioxide				
Oral	LD50	>10,000 mg/kg (Rat)			
Dermal	LD50	>10,000 mg/kg (Rabbit)			
Inhalative	e LC50/4 h	>6.82 mg/l (Rat)			
1310-73-	2 Sodium I	Hydroxide			
Oral	LD50	2,000 mg/kg (Rat)			
D.1.	indiana for a ff				

• Primary irritant effect:

- · On the skin: No irritating effect.
- On the eye: Irritating effect.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic categories:

· IARC (International Agency for Research on Cancer):

(a) Although IARC has classified titanium dioxide as possible carcinogenic to human (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is bound to other materials, such as in cosmetics or in paints."

(b) OSHA does not regulate Titanium Dioxide as a carcinogen. However, under 29 CFR 1910.1200 the SDS must convey the fact that Titanium Dioxide is a potential carcinogen to rats.

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

14807-96-6 Talc (Mg3H2(SiO3)4)

13463-67-7 Titanium Dioxide

• NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

2 Ecological Information

• Toxicity:

• Aquatic toxicity:

13463-67-7 Titanium Dioxide

EC50 >1,000 mg/l (Water flea)

1310-73-2 Sodium Hydroxide

EC50 40 mg/l (Daphnia)

Reviewed on 01/23/2019

3 2B



Reviewed on 01/23/2019



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/23/2019

Trade Name: Exuviance Purifying Clay Masque Exuviance Professional Purifying Clay Masque WORKS BEAUTY Clay Mask

- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · *Bioaccumulative potential:* No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment:
- · PBT: Not applicable.
- vPvB: Not applicable.

· Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packaging
- Recommendation: Disposal must be made according to official regulations.

14 Transport Information

 UN-Number: DOT, ADR/ADN, ADN, IMDG, IATA UN proper shipping name: DOT, ADR/ADN, ADN, IMDG, IATA Transport hazard class(es): 	Non-Regulated Material Non-Regulated Material
· DOT, ADR/ADN, ADN, IMDG, IATA · Class: · Packing group:	Non-Regulated Material
· DOT, ADR/ADN, IMDG, IATA	Non-Regulated Material
 Environmental hazards: 	Not applicable.
 Special precautions for user: 	Not applicable.
Transport in bulk according to Annex	ll of
MARPOL73/78 and the IBC Code:	Not applicable.
· UN "Model Regulation":	Non-Regulated Material

5 Regulatory Information

• Safety, health and environmental regulations/legislation specific for the substance or mixture: • SARA (Superfund Amendments and Reauthorization):

· Section 35	5 (extremely hazardous substances):		
	None of the ingredients are listed.		
· Section 31	3 (Specific toxic chemical listings):		
122-99-6 2	Phenoxyethanol		
TSCA (Tox	ic Substances Control Act):		
1332-58-7	Kaolin		
1302-78-9	Bentonite		
	(Contd. on page 8)		



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/23/2019

Reviewed on 01/23/2019

Trade Name: Exuviance Purifying Clay Masque Exuviance Professional Purifying Clay Masque WORKS BEAUTY Clay Mask

14807-96-6	Talc (Mg3H2(SiO3)4)
90-80-2	δ-Gluconolactone
11099-07-3	Glyceryl Stearate
9004-99-3	Polyethylene glycol stearate
68411-27-8	C12-15 Alkyl Benzoate
12199-37-0	Magnesium aluminum silicate
107-88-0	1,3-Butanediol
13463-67-7	Titanium Dioxide
7200-25-1	DL-arginine
	Alcohols, C16-18
	2-Phenoxyethanol
36653-82-4	1-Hexadecanol
	DL-α-Tocopherol acetate
	Sodium Hydroxide
	Polyvinyl Alcohol (PVA, PVOH, PVAL)
	Xanthan Gum
	Caprylyl Glycol
	Retinyl palmitate
	Polyethylene glycol hexadecyl ether
	Polyoxyethylene(20) stearyl ether
7732-18-5	Water, distilled water, deionized water
· TSCA new	(21st Century Act): (Substances not listed)
59259-38-0	I-Menthyl lactate
	Proposition 65:
· Chemicals	known to cause cancer:
13463-67-7	Titanium Dioxide
· Chemicals	known to cause reproductive toxicity for females:
None of the	ingredients are listed.
· Chemicals	known to cause reproductive toxicity for males:
None of the	ingredients are listed.
	known to cause developmental toxicity:
None of the	ingredients are listed.
· New Jersey	/ Right-to-Know List:
1332-58-7	Kaolin
14807-96-6	Talc (Mg3H2(SiO3)4)
13463-67-7	Titanium Dioxide
1310-73-2	Sodium Hydroxide
· New Jersey	/ Special Hazardous Substance List:
14807-96-6	Talc (Mg3H2(SiO3)4) CA
1310-73-2	Sodium Hydroxide CO, R1
	(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/23/2019

Trade Name: Exuviance Purifying Clay Masque Exuviance Professional Purifying Clay Masque WORKS BEAUTY Clay Mask

1332-58-7	Kaolin	
14807-96-6	Talc (Mg3H2(SiO3)4)	
	Titanium Dioxide	
1310-73-2	Sodium Hydroxide	
Pennsylvar	ia Special Hazardous Substance List:	
1310-73-2	Sodium Hydroxide	E
· Carcinoger	ic categories:	
· EPA (Envir	onmental Protection Agency):	
None of the	ingredients are listed.	
· TLV (Thres	hold Limit Value established by ACGIH):	
1332-58-7	Kaolin	2 mg/m
14807-96-6	Talc (Mg3H2(SiO3)4)	A4
13463-67-7	Titanium Dioxide	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health):	
13463-67-7	Titanium Dioxide	
	is classified and labeled according to the Globally Harmonized System (GHS). ograms: Non-Regulated Material I: Warning ements: s eye irritation.	
H320 Cause Precautiona P264	Wash thoroughly after handling. P338 If in eyes: Rinse cautiously with water for several minutes. Remov present and easy to do. Continue rinsing.	e contact lenses,
H320 Cause Precaution P264 P305+P351	Wash thoroughly after handling. P338 If in eyes: Rinse cautiously with water for several minutes. Remov present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	ve contact lenses,

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 01/23/2019 / 1

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Reviewed on 01/23/2019



Reviewed on 01/23/2019



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/23/2019

Trade Name: Exuviance Purifying Clay Masque Exuviance Professional Purifying Clay Masque WORKS BEAUTY Clay Mask

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 * * Data compared to the previous version altered. SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/21/2018

Reviewed on 09/21/2018

1 Identification

- · Product Identifier
- Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40
- · Product Number: FLA#: 345-188
- · Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description: Cosmetics, personal care products
- Details of the Supplier of the Safety Data Sheet:
 Manufacturer/Supplier: NeoStrata Company Inc. 307 College Road East Princeton, NJ 08540 Phone: +1-609-520-0715 Fax: +1-609-986-1928

Responsible Person: NeoStrata UG, DE-41470 Neuss • Emergency telephone number: Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887

2 Hazard(s) Identification

www.neostrata.com

· Classification of the substance or mixture:

Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Eye Irrit. 2B	H320	Causes eye irritation.
Aquatic Acute 2	H401	Toxic to aquatic life.

- · Label elements:
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms:



- · Signal word: Warning
- Hazard statements:
- H320 Causes eye irritation.
- H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements:

- P264 Wash thoroughly after handling.
- P273 Avoid release to the environment.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/21/2018

Page 2/11

Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40

P391 Collect spillage.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

19.7 % of the mixture consists of component(s) of unknown toxicity.

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:

· Dangerous Compon	ents:	
CAS: 5466-77-3	Octyl methoxycinnamate	5-10%
	Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
CAS: 190085-41-7	2-hydroxybenzoic acid 2-butyloctyl ester	2-12%
	Aquatic Chronic 4, H413	
CAS: 541-02-6	Decamethylcyclopentasiloxane	2-12%
	Flam. Liq. 4, H227; Eye Irrit. 2B, H320; Aquatic Chronic 4, H413	
CAS: 141-62-8	Decamethyltetrasiloxane	2-12%
	Flam. Liq. 4, H227	
CAS: 56-81-5	Glycerol	2-12%
RTECS: MA 8050000		
CAS: 70356-09-1	Butyl Methoxydibenzoylmethane	2-12%
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 9004-99-3	Polyethylene glycol stearate	≤2.5%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
CAS: 36653-82-4	1-Hexadecanol	≤2.5%
RTECS: MM 0225000) 🚸 Skin Irrit. 2, H315; Eye Irrit. 2B, H320	

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

· Description of first aid measures

General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Generally the product does not irritate the skin.

If skin irritation occurs, consult a doctor.

• After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor. If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/21/2018

Reviewed on 09/21/2018

Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:
- No further relevant information available.

5 Fire-Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: No further relevant information.
- · Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

• *Personal precautions, protective equipment and emergency procedures:* Not required. • *Environmental precautions:*

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/surface or ground water.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information. • Protective Action Criteria for Chemicals

PAC-1:		
56-81-5	Glycerol	45 mg/m ³
107-88-0	1,3-Butanediol	120 mg/m
36653-82-4	1-Hexadecanol	1.6 mg/m ³
57-55-6	Propylene Glycol	30 mg/m ³
122-99-6	2-Phenoxyethanol	1.5 ppm
139-33-3	Edetate Disodium - EDTA	11 mg/m ³
9005-00-9	Polyoxyethylene(20) stearyl ether	5.7 mg/m ³
7631-90-5	sodium hydrogensulphite	15 mg/m³
PAC-2:		
56-81-5	Glycerol	180 mg/m³
107-88-0	1,3-Butanediol	1,300 mg/m
36653-82-4	1-Hexadecanol	18 mg/m³
57-55-6	Propylene Glycol	1,300 mg/m
	1	(Contd. on page



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/21/2018

Reviewed on 09/21/2018

Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40

122-99-6	2-Phenoxyethanol 16 pp	
139-33-3	Edetate Disodium - EDTA	120 mg/m ³
9005-00-9	Polyoxyethylene(20) stearyl ether	63 mg/m³
7631-90-5	sodium hydrogensulphite	66 mg/m³
· PAC-3:		
56-81-5	Glycerol	1,100 mg/m ³
107-88-0	1,3-Butanediol	4,500 mg/m ³
36653-82-4	1-Hexadecanol	110 mg/m ³
57-55-6	Propylene Glycol	7,900 mg/m ³
122-99-6	2-Phenoxyethanol	97 ppm
139-33-3	Edetate Disodium - EDTA	730 mg/m ³
9005-00-9	Polyoxyethylene(20) stearyl ether	380 mg/m ³
7631-90-5	sodium hydrogensulphite	400 mg/m ³

7 Handling and Storage

· Handling

· Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

• Additional information about design of technical systems: No further data; see section 7.

- · Control parameters:
- Components with occupational exposure limits:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

56-81-5 Glycerol

- PEL |Long-term value: 15* 5** mg/m³
- mist; *total dust **respirable fraction

TLV TLV withdrawn-insufficient data human occup. exp.

9004-99-3 Polyethylene glycol stearate

TWA Long-term value: 10 mg/m³

• Additional information: The lists that were valid during the creation of this SDS were used as basis.

Page 4/11

(Contd. on page 5)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/21/2018

Reviewed on 09/21/2018

Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40

- · Exposure controls:
- · Personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

- Avoid contact with the eyes.
- · Breathing equipment: Not required.
- · Protection of hands: Not required.
- Material of gloves: Not applicable.
- · Penetration time of glove material: Not applicable.
- Eye protection:



Tightly sealed goggles recommended in a manufacturing setting only.

• *Limitation and supervision of exposure into the environment:* Keep away from drains, surface and ground waters. Avoid release into the environment.

9 Physical and Chemical Properties

 Information on basic physical and cl General Information 	nemical properties
 Appearance: Form: Color: Odour: Odor threshold: 	Lotion White to off white Characteristic Not determined.
· pH-value @ 20 °C (68 °F):	4-6
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not determined. ≥100 ℃ (≥212 ℉)
· Flash point:	≥113 ℃ (≥235.4 ℉)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	Not applicable
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure @ 20 °C (68 °F):	≤23 hPa (≤17.3 mm Hg)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/21/2018

Reviewed on 09/21/2018

Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40

· Density @ 20 °C (68 °F): · Relative density: · Vapor density: · Evaporation rate:	0.96-1.04 g/cm ³ (8.0112-8.6788 lbs/gal) Not determined. Not determined. Not determined.	
 Solubility in / Miscibility with: Water: 	Miscible	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity: Dynamic @ 20 ℃ (68 ℉): Kinematic:	8,000-30,000 mPas Not determined.	
 Solvent content: Organic solvents: Water: VOC content: 	3.7 % 44.2 % 0.48 %	
Solids content: • Other information:	8.9 % No further relevant information available.	

10 Stability and Reactivity

• *Reactivity:* No further relevant information available.

- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
541-02-6 I	541-02-6 Decamethylcyclopentasiloxane		
Oral	LD50	>5,000 mg/kg (Rat)	
Dermal	LD50	>2,000 mg/kg (Rabbit)	
Inhalative	LC50/4 h	8.67 mg/l (Rat)	
56-81-5 G	56-81-5 Glycerol		
Oral	LD50	12,600 mg/kg (Rat)	
Dermal	LD50	>10,000 mg/kg (Rabbit)	
Inhalative	LC50/96 hours	>50,000 mg/l (Trout)	
36653-82-4 1-Hexadecanol			
Oral	LD50	5,000 mg/kg (Rat)	
· Primary irritant effect:			

· On the skin: No irritating effect.

• On the eye: Irritating effect.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/21/2018

Reviewed on 09/21/2018

Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Irritant
- · Carcinogenic categories:
- · IARC (International Agency for Research on Cancer):
- Group 1 Carcinogenic to humans
- Group 2A Probably carcinogenic to humans
- Group 2B Possibly carcinogenic to humans
- Group 3 Not classifiable as to its carcinogenicity to humans
- Group 4 Probably not carcinogenic to humans

9003-01-4 Carbomer

7631-90-5 sodium hydrogensulphite

• NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

12 Ecological Information

· Toxicity:

· Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

- Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- *Mobility in soil:* No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

Poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · Results of PBT and vPvB assessment:
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

(Contd. on page 8)

3

3



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Page 8/11

Issue date 09/21/2018

Reviewed on 09/21/2018

Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40

- · Uncleaned packaging
- *Recommendation:* Disposal must be made according to official regulations.

14 Transport Information

- · UN-Number: · DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material · UN proper shipping name: · DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material • Transport hazard class(es): · DOT. ADR/ADN Limited Quantity · Class: Non-Regulated Material · ADN/R Class: Non-Regulated Material · IMDG, IATA Limited Quantity · Class: Non-Regulated Material · Label: 9+ID8000 · Packing group: · DOT, ADR/ADN, IMDG, IATA Non-Regulated Material · Environmental hazards: Not applicable. · Special precautions for user: Not applicable. · Stowage Category Α · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable. Non-Regulated Material · UN "Model Regulation": 5 Regulatory Information
- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- · SARA (Superfund Amendments and Reauthorization):
- Section 355 (extremely hazardous substances):
 None of the ingredients are listed.

 Section 313 (Specific toxic chemical listings):
 122-99-6 2-Phenoxyethanol

 TSCA (Toxic Substances Control Act):
 5466-77-3 Octyl methoxycinnamate
 118-60-5 Ethyl hexyl salicylate
 541-02-6 Decamethylcyclopentasiloxane
 141-62-8 Decamethyltetrasiloxane
 (Contd. on page 9)



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/21/2018

Page 9/11

Reviewed on 09/21/2018

Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40

68411-27-8	C12-15 Alkyl Benzoate
	Glycerol
	Butyl Methoxydibenzoylmethane
	Glyceryl Monostearate
	1,3-Butanediol
9004-99-3	Polyethylene glycol stearate
36653-82-4	1-Hexadecanol
57-55-6	Propylene Glycol
58-95-7	α-tocopheryl acetate
122-99-6	2-Phenoxyethanol
11138-66-2	Xanthan Gum
139-33-3	Edetate Disodium - EDTA
9004-95-9	Polyethylene glycol hexadecyl ether
9005-00-9	Polyoxyethylene(20) stearyl ether
	octane-1,2-diol
	Carbomer
	sodium hydrogensulphite
7732-18-5	Water, distilled water, deionized water
· TSCA new	(21st Century Act) (Substances not listed)
190085-41-	7 2-hydroxybenzoic acid 2-butyloctyl ester
70356-09-	1 Butyl Methoxydibenzoylmethane
	Proposition 65:
· Chemicals	known to cause cancer:
None of the	ingredients are listed.
	known to cause reproductive toxicity for females:
None of the	ingredients are listed.
· Chemicals	known to cause reproductive toxicity for males:
None of the	ingredients are listed.
· Chemicals	known to cause developmental toxicity:
None of the	ingredients are listed.
· New Jersey	/ Right-to-Know List:
56-81-5	Glycerol
57-55-6	Propylene Glycol
7631-90-5	sodium hydrogensulphite
· New Jersey	/ Special Hazardous Substance List:
7631-90-5	sodium hydrogensulphite CO
· Pennsylvar	nia Right-to-Know List:
56-81-5	Glycerol
57-55-6	Propylene Glycol
	sodium hydrogensulphite
L	(Contd. on page 10



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

lssue date 09/21/2018

Reviewed on 09/21/2018

Page 10/11

Е

A4

Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40

- · Pennsylvania Special Hazardous Substance List:
- 7631-90-5 sodium hydrogensulphite
- · Carcinogenic categories:
- · EPA (Environmental Protection Agency):
- None of the ingredients are listed.
- TLV (Threshold Limit Value established by ACGIH):
- 7631-90-5 sodium hydrogensulphite
- NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

• Hazard pictograms:



- · Signal word: Warning
- · Hazard statements:
- H320 Causes eye irritation.
- H401 Toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements:
- P264 Wash thoroughly after handling.
- P273 Avoid release to the environment.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P391 Collect spillage.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

• Date of preparation / last revision: 09/21/2018 / 2

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/21/2018

Reviewed on 09/21/2018

Trade Name: Exuviance Professional Sheer Refining Fluid with Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration Sunscreen Broad Spectrum SPF 40 NeoStrata Sheer Hydration with Sunscreen Broad Spectrum SPF 40 NeoStrata ProSystem Sheer Hydration with Sunscreen Broad Spectrum SPF 40

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** Flam. Liq. 4: Flammable liquids - Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4 * Data compared to the previous version altered. SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106 Page 11/11



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

1 Identification

- · Product Identifier
- Trade Name: Exuviance Revitalizing-Plus Peel Exuviance Professional Revitalizing-Plus Peel

FOR SALON USE ONLY

- · Product Number: FLA#: 268-049
- Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description: Cosmetics, personal care products
- Details of the Supplier of the Safety Data Sheet:
 Manufacturer/Supplier: NeoStrata Company Inc. 307 College Road East Princeton, NJ 08540 Phone: +1-609-520-0715 Fax: +1-609-986-1928 www.neostrata.com

Responsible Person: NeoStrata UG, DE-41470 Neuss *Emergency telephone number:* Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887

2 Hazard(s) Identification

Classification of the substance or mixture:

Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

Corrosion

Skin Corr. 1A	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
Aquatic Acute 2	H401 Toxic to aquatic life.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

· Label elements:

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



· Signal word: Danger

• *Hazard-determining components of labeling:* Glycolic acid Ammonium Hydroxide



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Exuviance Revitalizing-Plus Peel Exuviance Professional Revitalizing-Plus Peel FOR SALON USE ONLY

· Hazard statements:

- H226 Flammable liquid and vapor.
- H314 Causes severe skin burns and eye damage.
- H401 Toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dusts or mists.
- P264 Wash thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- P310 Immediately call a poison center/doctor.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Unknown acute toxicity:

3 % of the mixture consists of component(s) of unknown toxicity.

Hazard(s) not otherwise classified (HNOC): None known

Composition/Information on Ingredients

· Chemica	characterization:	Mixtures
-----------	-------------------	----------

· Description: Mixture of substances listed below with non-hazardous additions.

 Dangerous Compone 	ents:	
CAS: 79-14-1	Glycolic acid	25-50%
RTECS: MC 5250000	🤣 Skin Corr. 1A, H314; Eye Dam. 1, H318; 🚸 Acute Tox. 4, H302	
CAS: 64-17-5	Ethanol	5-10%
RTECS: KQ 6300000	♦ Flam. Liq. 2, H225; ♦ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
CAS: 57-55-6	Propylene Glycol	2-12%
RTECS: TY 2000000	Eye Irrit. 2B, H320	
CAS: 1336-21-6	Ammonium Hydroxide	2-12%
	vPvB	
	 Acute Tox. 3, H331; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302 	
	(O	

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Exuviance Revitalizing-Plus Peel Exuviance Professional Revitalizing-Plus Peel FOR SALON USE ONLY

CAS: 9002-93-1	Polyethylene glycol octylphenol ether	$\leq 2.5\%$
	 Acute Tox. 3, H331; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Eye Irrit. 2A, H319 	

4 First-Aid Measures

[.] Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or a rash occurs, consult a doctor.

• After eye contact:

If easy to do so, remove contact lenses if worn.

Have eyes examined and tested by medical personnel.

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

After swallowing:

Never give anything by mouth to an unconscious person.

Rinse mouth with water.

Call a doctor immediately.

Do not induce vomiting without medical advice.

- Information for doctor
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:
- No further relevant information available.

5 Fire-Fighting Measures

- Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face piece operated in positive pressure mode.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures:
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/surface or ground water.

(Contd. on page 4)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Exuviance Revitalizing-Plus Peel Exuviance Professional Revitalizing-Plus Peel FOR SALON USE ONLY

 Methods and material for containment and cleaning up: Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent. Dispose contaminated material as waste according to section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
 Reference to other sections: See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and Storage

· Handling

- **Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect from heat.
 Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities · Storage
- · Requirements to be met by storerooms and receptacles: Store in the original container.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
 Protect from heat and direct sunlight.
 Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

• Control parameters:

· Components with occupational exposure limits:

64-17-5 Ethanol

- PEL Long-term value: 1900 mg/m³, 1000 ppm
- REL Long-term value: 1900 mg/m³, 1000 ppm
- TLV Short-term value: 1880 mg/m³, 1000 ppm

57-55-6 Propylene Glycol

WEEL Long-term value: 10 mg/m³

• Additional information: The lists that were valid during the creation of this SDS were used as basis.

• Exposure controls:

- Personal protective equipment
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Page 5/11

Trade Name: Exuviance Revitalizing-Plus Peel Exuviance Professional Revitalizing-Plus Peel FOR SALON USE ONLY

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air. **Protection of hands:**

Ind Can

Protective gloves

• Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

...

Eye protection:

...



Tightly sealed goggles required in a manufacturing setting only.

9 Physical and Chemical Properties

 Information on basic physical and General Information 	I chemical properties
· Appearance:	
Form:	Solution
Color:	Clear
Odour:	Characteristic
· Odor threshold:	Not determined.
[.] pH-value @ 20 °C (68 °F):	3-3.8
· Change in condition	
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	78 °C (172.4 °F)
· Flash point:	43 °C (109.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	317 °C (602.6 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
• Explosion limits:	
Lower:	0.0 Vol %
Upper:	15.0 Vol %
	(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Trade Name: Exuviance Revitalizing-Plus Peel Exuviance Professional Revitalizing-Plus Peel FOR SALON USE ONLY

· Vapor pressure @ 20 °C (68 °F):	59 hPa (44.3 mm Hg)
 Density @ 25 °C (77 °F): Relative density: Vapor density: Evaporation rate: 	1.05-1.15 g/cm³ (8.7623-9.5968 lbs/gal) Not determined. Not determined. Not determined.
 Solubility in / Miscibility with: Water: 	Miscible
· Partition coefficient (n-octanol/water)	: Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
 Solvent content: Organic solvents: Water: VOC content: 	15.0 % 48.5 % 18.5 %
Solids content: • Other information:	33.0 % No further relevant information available.

0 Stability and Reactivity

• *Reactivity:* No further relevant information available.

· Chemical stability: Stable under normal conditions.

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Heat, flame and ignition sources.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

79-14-1 G	lycolic aci	id
Oral	LD50	1950 mg/kg (Rat)
9002-93-1	Polyethy	lene glycol octylphenol ether
Oral	LD50	1800 mg/kg (Rat)
Dermal	LD50	8000 mg/kg (Rat)
Inhalative	LC50/4 h	8.9 mg/l (Pimephales)
· Primary in	Primary irritant effect:	

• On the skin: Strong caustic effect on skin and mucous membranes.

• On the eye: Corrosive effect.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Reviewed on 01/10/2019



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Page 7/11

1

Trade Name: Exuviance Revitalizing-Plus Peel Exuviance Professional Revitalizing-Plus Peel FOR SALON USE ONLY

Corrosive

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories:

· IARC (International Agency for Research on Cancer):

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

The IARC (the International Agency for Research on Cancer) concluded that ethanol found alcoholic beverages to be Group 1 - Carcinogenic to humans. All other instances it is not consider carcinogenic.

64-17-5 Ethanol

• NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

2 Ecological Information

· Toxicity:

· Aquatic toxicity:

9002-93-1 Polyethylene glycol octylphenol ether

EC50 26 mg/kg (Daphnia)

- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · *Bioaccumulative potential:* No further relevant information available.
- Mobility in soil: No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- Harmful to aquatic organisms
- Results of PBT and vPvB assessment:
- · PBT: Not applicable.

· vPvB:

1336-21-6 Ammonium Hydroxide

• Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Trade Name: Exuviance Revitalizing-Plus Peel **Exuviance Professional Revitalizing-Plus Peel** FOR SALON USE ONLY


- · Uncleaned packaging
- · Recommendation: Disposal must be made according to official regulations.

4 Transport Information

· UN-Number:	None
· DOT, ADR/ADN, IMDG, IATA	UN2924
 UN proper shipping name: 	Limited Quantity, Consumer Commodity
·DOT	Flammable liquids, corrosive, n.o.s. (Glycolic acid, Ethanol)
· ADR/ADN	UN2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Glycolic
	acid, ETHANOL (ETHYL ALCOHOL))
·IMDG	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Glycolic acid,
	ETHANOL (ETHYL ALCOHOL))
	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Glycolic acid,
	ETHANOL)
 Transport hazard class(es): 	

· DOT, IMDG





- · Class:
- · Label:
- · ADR/ADN

3 Flammable liquids LimitedQuant





Limited Quantity

· Class:

· Label:

3 Flammable liquids Ltd Qty

(Contd. on page 9)

Reviewed on 01/10/2019




OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Page 9/11

Trade Name: Exuviance Revitalizing-Plus Peel Exuviance Professional Revitalizing-Plus Peel FOR SALON USE ONLY



• Safety, health and environmental regulations/legislation specific for the substance or mixture: • SARA (Superfund Amendments and Reauthorization):

or not (oup on and month and mouth on Earlon).
· Section 355 (extremely hazardous substances):
None of the ingredients are listed.
· Section 313 (Specific toxic chemical listings):
1336-21-6 Ammonium Hydroxide
· TSCA (Toxic Substances Control Act):
All ingredients are listed or exempt from listing.
· California Proposition 65:
· Chemicals known to cause cancer:
None of the ingredients are listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients are listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

64-17-5 Ethanol

· Carcinogenic categories:

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

• TLV (Threshold Limit Value established by ACGIH):

64-17-5 Ethanol

(Contd. on page 10)

A3



Reviewed on 01/10/2019



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Trade Name: Exuviance Revitalizing-Plus Peel **Exuviance Professional Revitalizing-Plus Peel** FOR SALON USE ONLY

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms:





- · Signal word: Danger
- · Hazard-determining components of labeling:
- Glycolic acid
- Ammonium Hydroxide

· Hazard statements:

- H226 Flammable liquid and vapor.
- H314 Causes severe skin burns and eye damage.
- H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements:
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment. P241
- P242 Use only non-sparking tools.
- Take precautionary measures against static discharge. P243
- P260 Do not breathe dusts or mists.
- P264 Wash thoroughly after handling.
- Avoid release to the environment. P273
- Wear protective gloves/protective clothing/eye protection/face protection. P280
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a poison center/doctor.
- Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). P321
- Wash contaminated clothing before reuse. P363
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Page 11/11

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Exuviance Revitalizing-Plus Peel Exuviance Professional Revitalizing-Plus Peel FOR SALON USE ONLY

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

• Date of preparation / last revision: 01/10/2019 / 5

Abbreviations and acronyms: ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

1 Identification

- · Product Identifier
- Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)
- · Product Number: FLA#: 268-050
- · Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description: Cosmetics, personal care products
- Details of the Supplier of the Safety Data Sheet:
 Manufacturer/Supplier: NeoStrata Company Inc. 307 College Road East Princeton, NJ 08540 Phone: +1-609-520-0715 Fax: +1-609-986-1928 www.neostrata.com

Responsible Person: NeoStrata UG, DE-41470 Neuss *Emergency telephone number:* Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887

2 Hazard(s) Identification

• Classification of the substance or mixture:

Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

Corrosion

Skin Corr. 1A	H314 Causes severe skin burns and eye damage.
---------------	---

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements:

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



· Signal word: Danger

• *Hazard-determining components of labeling:* Glycolic acid

Ammonium Hydroxide

Hazard statements:

H226 Flammable liquid and vapor. H314 Causes severe skin burns and eye damage.





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

• Precautionary statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dusts or mists.
- P264 Wash thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- P310 Immediately call a poison center/doctor.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

3 % of the mixture consists of component(s) of unknown toxicity.

· Hazard(s) not otherwise classified (HNOC): None known

Composition/Information on Ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:	
Glycolic acid	15-35%
📀 Skin Corr. 1A, H314; Eye Dam. 1, H318; 🚸 Acute Tox. 4, H302	
Ethanol	5-10%
♦ Flam. Liq. 2, H225; ♦ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
Ammonium Hydroxide vPvB	≤2.5%
Acute Tox. 3, H331; 😵 Skin Corr. 1B, H314; Eye Dam. 1, H318; 🚯 Aquatic Acute 1, H400; 🕐 Acute Tox. 4, H302	
Polyethylene glycol octylphenol ether	≤2.5%
Acute Tox. 3, H331; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Eye Irrit. 2A, H319	
	Glycolic acid ♦ Skin Corr. 1A, H314; Eye Dam. 1, H318; ♦ Acute Tox. 4, H302 Ethanol ♦ Flam. Liq. 2, H225; ♦ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320 Ammonium Hydroxide vPvB ♦ Acute Tox. 3, H331; ♦ Skin Corr. 1B, H314; Eye Dam. 1, H318; ♦ Aquatic Acute 1, H400; ♦ Acute Tox. 4, H302

(Contd. on page 3)



Page 3/13

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

• Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

· Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

• After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed:* No further relevant information available.

5 Fire-Fighting Measures

- Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture:

Combustible liquid. Vapors can travel to a source of ignition and flash back.

Explosive mixtures may occur at temperatures at or above flashpoint.

- Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

Reference to other sections:

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. • **Protective Action Criteria for Chemicals**

· PAC-1:

79-14-1 Glycolic acid	25 mg/m³
64-17-5 Ethanol	1,800 ppm
1336-21-6 Ammonium Hydroxide	61 ppm
PAC-2:	
79-14-1 Glycolic acid	280 mg/m³
64-17-5 Ethanol	3300* ppm
1336-21-6 Ammonium Hydroxide	330 ppm
· PAC-3:	
79-14-1 Glycolic acid	390 mg/m³
64-17-5 Ethanol	15000* ppm
1336-21-6 Ammonium Hydroxide	2,300 ppm

7 Handling and Storage

· Handling

- **Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect from heat.
 Protect against electrostatic charges.

• Conditions for safe storage, including any incompatibilities

- · Storage
- Requirements to be met by storerooms and receptacles: Store in the original container.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Protect from heat and direct sunlight.
- Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters:

Components with occupational exposure limits:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

64-17-5 Ethanol

- PEL Long-term value: 1900 mg/m³, 1000 ppm
- REL Long-term value: 1900 mg/m³, 1000 ppm



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

TLV Short-term value: 1880 mg/m³, 1000 ppm

• Additional information: The lists that were valid during the creation of this SDS were used as basis.

• Exposure controls:

Personal protective equipment

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

• Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

• Eye protection:



Tightly sealed goggles

• *Limitation and supervision of exposure into the environment:* Keep away from drains, surface and ground waters. Avoid release into the environment.

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:	
Form:	Solution
Color:	Clear
· Odour:	Characteristic
· Odor threshold:	Not determined.
· pH-value @ 20 °C (68 °F):	3.3
 Change in condition Melting point/Melting range: 	Not determined.
Boiling point/Boiling range:	≥78 °C (≥172.4 °F)

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

Flash point: 45 °C (113 °F) Flammability (solid, gaseous): Not applicable. Ignition temperature: ≥425 °C (≥797 °F) Decomposition temperature: Not determined. Auto igniting: Product is not self-igniting. Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Explosion limits: Upper: Lower: 0 Vol % Upper: 15 Vol % Vapor pressure @ 20 °C (68 °F): 559 hPa (≤44.3 mm Hg) Density @ 20 °C (68 °F): 1.007 g/cm³ (8.4034 lbs/gal) Relative density: Not determined. Vapor density: Not determined. Vapor density: Not determined. Vapor density: Not determined. Vater: Soluble. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Solvent content: 0.0 % Organic solvents: 10.0 % Water: 59.6 % VOC content: 10.00 % Solids content: 23.0 % Other information: No further re		
Ignition temperature: >425 °C (≥797 °F) Decomposition temperature: Not determined. Auto igniting: Product is not self-igniting. Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Explosion limits: Upper: Lower: 0 Vol % Upper: 15 Vol % Vapor pressure @ 20 °C (68 °F): ≤59 hPa (≤44.3 mm Hg) Density @ 20 °C (68 °F): 1.007 g/cm³ (8.4034 lbs/gal) Relative density: Not determined. Vapor density: Not determined. Viscosity: Solubile. Partition coefficient (n-octanol/water): Not determined. Viscosity: Not determined. Organic solvents: 10.0 % Water: \$9.6 % VOC content: 59.6 % VOC content: 10.00 % Solids content: 23.0 % Other information: <th>· Flash point:</th> <th>45 °C (113 °F)</th>	· Flash point:	45 °C (113 °F)
Decomposition temperature: Not determined. Auto igniting: Product is not self-igniting. Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Explosion limits: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Explosion limits: 0 Vol % Lower: 0 Vol % Upper: 15 Vol % Vapor pressure @ 20 °C (68 °F): s59 hPa (≤44.3 mm Hg) Density @ 20 °C (68 °F): 1.007 g/cm³ (8.4034 lbs/gal) Relative density: Not determined. Vapor density: Not determined. Vapor density: Not determined. Vapor density: Not determined. Vater: Soluble. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Organic solvents: 10.0 % Yea 6 % VOC content: 59.6 % You 0 % Solids content: 23.0 % Not further relevant information available.	· Flammability (solid, gaseous):	Not applicable.
Auto igniting: Product is not self-igniting. Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Explosion limits: 0 Vol % Lower: 0 Vol % Upper: 15 Vol % Vapor pressure @ 20 °C (68 °F): ≤59 hPa (≤44.3 mm Hg) Density @ 20 °C (68 °F): 1.007 g/cm³ (8.4034 lbs/gal) Relative density: Not determined. Vapor density: Not determined. Vapor density: Not determined. Vapor after: Soluble. Partition coefficient (n-octanol/water): Not determined. Viscosity: Not determined. Mot determined. Not determined. Viscosity: Not determined. Organic solvents: 10.0 % Water: 59.6 % VOC content: 10.00 % Solids content: 23.0 % Other information: No further relevant information available.	· Ignition temperature:	≥425 °C (≥797 °F)
Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Explosion limits: 0 Vol % Lower: 0 Vol % Upper: 15 Vol % Vapor pressure @ 20 °C (68 °F): ≤59 hPa (≤44.3 mm Hg) Density @ 20 °C (68 °F): 1.007 g/cm³ (8.4034 lbs/gal) Relative density: Not determined. Vapor coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Dynamic: Not determined. Viscosity: Not determined. Organic solvents: 10.0 % VOC content: 59.6 % VOC content: 10.00 % Solids content: 23.0 % Other information: No further relevant information available.	• Decomposition temperature:	Not determined.
mixtures are possible. Explosion limits: Lower: 0 Vol % Upper: 15 Vol % Vapor pressure @ 20 °C (68 °F): ≤59 hPa (≤44.3 mm Hg) Density @ 20 °C (68 °F): 1.007 g/cm³ (8.4034 lbs/gal) Relative density: Not determined. Vapor density: Not determined. Vapor density: Not determined. Solubility in / Miscibility with: Water: Water: Soluble. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Dynamic: Not determined. Kinematic: Not determined. Organic solvents: 10.0 % Water: 59.6 % VOC content: 10.00 % Solids content: 23.0 % Other information: Not further relevant information available.	· Auto igniting:	Product is not self-igniting.
Lower: $0 \ Vol \%$ Upper: $15 \ Vol \%$ Vapor pressure @ 20 °C (68 °F): $559 \ hPa (\le 44.3 \ mm \ Hg)$ Density @ 20 °C (68 °F): $1.007 \ g/cm^3 (8.4034 \ lbs/gal)$ Relative density:Not determined.Vapor density:Not determined.Vapor density:Not determined.Vapor density:Not determined.Vapor density:Not determined.Solubility in / Miscibility with: Water:Soluble.Partition coefficient (n-octanol/water): Not determined.Viscosity: Dynamic: Kinematic:Not determined.Solvent content: Organic solvents: 10.0% Water:Solids content: VOC content: 10.0% Solids content:Solids content: 23.0% Other information:No further relevant information available.	· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Density @ 20 °C (68 °F): 1.007 g/cm³ (8.4034 lbs/gal) Relative density: Not determined. Vapor density: Not determined. 'Vapor ation rate: Not determined. 'Evaporation rate: Not determined. 'Solubility in / Miscibility with: Water: 'Water: Soluble. 'Partition coefficient (n-octanol/water): Not determined. 'Viscosity: Dynamic: Dynamic: Not determined. Kinematic: Not determined. 'Solvent content: Organic solvents: Organic solvents: 10.0 % Water: 59.6 % 'VOC content: 10.00 % Solids content: 23.0 % 'Other information: No further relevant information available.	Lower:	
Relative density: Not determined. Vapor density: Not determined. Evaporation rate: Not determined. Solubility in / Miscibility with: Water: Water: Soluble. Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Dynamic: Not determined. Kinematic: Not determined. Solvent content: Not determined. Organic solvents: 10.0 % Water: 59.6 % VOC content: 10.00 % Solids content: 23.0 % Other information: No further relevant information available.	· Vapor pressure @ 20 °C (68 °F):	≤59 hPa (≤44.3 mm Hg)
Water:Soluble.Partition coefficient (n-octanol/water): Not determined.Viscosity:Dynamic:Not determined.Kinematic:Not determined.Solvent content:Organic solvents:10.0 %Water:59.6 %VOC content:10.00 %Solids content:23.0 %Other information:No further relevant information available.	· Relative density: · Vapor density:	Not determined. Not determined.
· Viscosity: Dynamic: Not determined. Dynamic: Not determined. Kinematic: Not determined. · Solvent content: 10.0 % Organic solvents: 10.0 % VOC content: 59.6 % VOC content: 10.00 % Solids content: 23.0 % · Other information: No further relevant information available.		Soluble.
Dynamic: Kinematic:Not determined.Solvent content: Organic solvents:10.0 %Water: VOC content:59.6 %VOC content:10.00 %Solids content:23.0 %Other information:No further relevant information available.	· Partition coefficient (n-octanol/water	r): Not determined.
Organic solvents:10.0 %Water:59.6 %VOC content:10.00 %Solids content:23.0 %Other information:No further relevant information available.	Dynamic:	
• Other information: No further relevant information available.	Organic solvents: Water:	59.6 %
10 Stability and Reactivity		
	10 Stability and Reactivity	

· Reactivity:

1

No further relevant information available.

The product is stable under normal conditions

- No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Heat, flame and ignition sources.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

Acute tox	•	
		relevant for classification:
	lycolic acid	
Oral	LD50	1,950 mg/kg (Rat)
64-17-5 E	thanol	
Oral	LD50	7,060 mg/kg (Rat) Remarks: Lungs, Thorax, or Respiration: Other changes. Carcinogenicity - Mouse - Oral Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumori Blood: Lymphomas including Hodgkin's disease. Central nervous system depression, narcosis, Damage to the heart., To the be of our knowledge, the chemical, physical, and toxicological properties have no been thoroughly investigated. Heart - Irregularities - Based on Human Evidence Central nervous system - Breathing difficulties - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence
Inhalative	LC50/4 h	20,000 mg/l (Rat)
	LC50/96 hours	12,900-15,300 mg/l (Trout)
1336-21-6	Ammonium Hy	/droxide
Oral	LD50	350 mg/kg (RAT) Remarks: Gastrointestinal: Other changes. Liver: Other changes. Kidney, Urete Bladder: Other changes.
Inhalative	LC50/96 hours	8.2 mg/l (Pimephales)
9002-93-1	Polyethylene g	glycol octylphenol ether
Oral	LD50	1,800 mg/kg (Rat)
Dermal	LD50	8,000 mg/kg (Rat)
Inhalative	LC50/4 h	8.9 mg/l (Pimephales)

· On the eye:

Strong irritant with the danger of severe eye injury.

Corrosive effect.

Causes serious eye irritation.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories:

· IARC (International Agency for Research on Cancer):

The IARC (the International Agency for Research on Cancer) concluded that ethanol found alcoholic beverages to be Group 1 - Carcinogenic to humans. All other instances it is not consider carcinogenic. Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans



1



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

- Group 2B Possibly carcinogenic to humans
- Group 3 Not classifiable as to its carcinogenicity to humans
- Group 4 Probably not carcinogenic to humans

64-17-5 Ethanol

• NTP (National Toxicology Program):

None of the ingredients are listed.

• OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

2 Ecological Information

· Toxicity:

• Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

64-17-5 Ethanol

EC50 34,900 mg/l (Daphnia)

1336-21-6 Ammonium Hydroxide

EC50 0.66 mg/l (Daphnia)

0.66 mg/l (Water flea)

9002-93-1 Polyethylene glycol octylphenol ether

EC50 26 mg/l (Daphnia)

· Persistence and degradability: No further relevant information available.

· Behavior in environmental systems:

- · **Bioaccumulative potential:** No further relevant information available.
- Mobility in soil: No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Harmful to aquatic organisms

• Results of PBT and vPvB assessment:

· **PBT:** Not applicable.

· vPvB:

1336-21-6 Ammonium Hydroxide

• Other adverse effects: No further relevant information available.

3 Disposal Considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

· Uncleaned packaging

• *Recommendation:* Disposal must be made according to official regulations.




OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)



3 Flammable liquids



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

· Label:	3/8+ID8000
 Limited Quantity Class: Label: Packing group: DOT, ADR/ADN, IMDG, IATA Environmental hazards: Special precautions for user: Danger code (Kemler): EMS Number: Segregation groups: Stowage Category Stowage Code Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: 	3 Flammable liquids 3 (8)+ID8000 Non-Regulated Material III Not applicable. Warning: Flammable liquids 38 F-E,S-C Acids, ammonium compounds, alkalis A SW2 Clear of living quarters. of Not applicable.
• Transport/Additional information:	
DOT Quantity limitations:	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR/ADN · Excepted quantities (EQ):	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 IMDG Limited quantities (LQ): Excepted quantities (EQ): UN "Model Regulation": 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ETHANOL (ETHYL ALCOHOL), GLYCOLIC ACID), 3 (8), III
15 Regulatory Information	

• Safety, health and environmental regulations/legislation specific for the substance or mixture: • SARA (Superfund Amendments and Reauthorization):

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

• Section 313 (Specific toxic chemical listings):

1336-21-6 Ammonium Hydroxide

(Contd. on page 11)



Reviewed on 01/10/2019



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

•	kic Substances Control Act):	
All ingredie	nts are listed or exempt from listing.	
	Proposition 65:	
· Chemicals	known to cause cancer:	
None of the	e ingredients are listed.	
· Chemicals	s known to cause reproductive toxicity for females:	
None of the	e ingredients are listed.	
· Chemicals	s known to cause reproductive toxicity for males:	
None of the	e ingredients are listed.	
· Chemicals	known to cause developmental toxicity:	
64-17-5 E	hanol	
New Jerse	y Right-to-Know List:	
64-17-5	Ethanol	
1336-21-6	Ammonium Hydroxide	
· New Jerse	y Special Hazardous Substance List:	
64-17-5	Ethanol	CA, MU, TE, F3
1336-21-6	Ammonium Hydroxide	CO
	nia Right-to-Know List:	
64-17-5	Ethanol	
1336-21-6	Ammonium Hydroxide	
· Pennsylva	nia Special Hazardous Substance List:	
1336-21-6	Ammonium Hydroxide	E
· Carcinoge	nic categories:	
· EPA (Envi	ronmental Protection Agency):	
None of the	e ingredients are listed.	
•	shold Limit Value established by ACGIH):	
64-17-5 E	hanol	A3
· NIOSH-Ca	(National Institute for Occupational Safety and Health):	
None of the	e ingredients are listed.	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms:



· Signal word: Danger

- · Hazard-determining components of labeling: Glycolic acid Ammonium Hydroxide
- · Hazard statements:

H226 Flammable liquid and vapor.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

H314 Causes severe skir	burns and eye damage.
-------------------------	-----------------------

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements:
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dusts or mists.
- P264 Wash thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a poison center/doctor.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

• Date of preparation / last revision: 01/10/2019 / 5

Abbreviations and acronyms:

- ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 01/10/2019

Reviewed on 01/10/2019

Trade Name: Evuviance Revitalizing Peel 20% Glycolic Acid Evuviance Professional Revitalizing Peel (20% Glycolic Acid)

OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 • * Data compared to the previous version altered. SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/27/2018

Reviewed on 09/27/2018

1 Identification

- · Product Identifier
- Trade Name: Exuviance Clarifying Peel/Booster Exuviance Professional Clarifying Peel/Booster
- · Product Number: FLA#: 357-077B
- · Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description: Cosmetics, personal care products
- Details of the Supplier of the Safety Data Sheet:
 Manufacturer/Supplier: NeoStrata Company Inc. 307 College Road East Princeton, NJ 08540 Phone: +1-609-520-0715 Fax: +1-609-986-1928 www.neostrata.com

Responsible Person: NeoStrata UG, DE-41470 Neuss • *Emergency telephone number:* Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887

2 Hazard(s) Identification

· Classification of the substance or mixture:



Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Acute 3 H402 Harmful to aquatic life.

- · Label elements:
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms:



- · Signal word: Danger
- Hazard-determining components of labeling: mandelic acid
 Glycolic acid
 Ammonium Hydroxide
 Hazard statements:
- H318 Causes serious eye damage. H402 Harmful to aquatic life.
- Precautionary statements:
- P273 Avoid release to the environment.
- P280 Wear eye protection / face protection.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a poison center/doctor.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/27/2018

Reviewed on 09/27/2018

Trade Name: Exuviance Clarifying Peel/Booster Exuviance Professional Clarifying Peel/Booster

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

- 7 % of the mixture consists of component(s) of unknown toxicity.
- · Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.
- · Dangerous Components:

Dangerous components.		
CAS: 90-64-2	mandelic acid	15-35%
	🗇 Eye Dam. 1, H318; 🚸 Skin Irrit. 2, H315	
CAS: 79-14-1	Glycolic acid	2-12%
RTECS: MC 5250000	📀 Skin Corr. 1A, H314; Eye Dam. 1, H318; 🚸 Acute Tox. 4, H302	
CAS: 90-80-2	δ-Gluconolactone	2-12%
	🚸 STOT SE 3, H335	
CAS: 1336-21-6	Ammonium Hydroxide	≤2.5%
	vPvB	
	Acute Tox. 3, H331; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302	

• Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

· Description of first aid measures

General information:

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Generally the product does not irritate the skin.

If skin irritation occurs, consult a doctor.

• After eye contact:

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Have eyes examined and tested by medical personnel.

If easy to do so, remove contact lenses if worn.

Get immediate medical attention.

· After swallowing: If swallowed and symptoms occur, consult a doctor.

· Information for doctor

- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/27/2018

Reviewed on 09/27/2018

Trade Name: Exuviance Clarifying Peel/Booster Exuviance Professional Clarifying Peel/Booster

5 Fire-Fighting Measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: No further relevant information.
- · Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures: Not required.
 Environmental precautions:
- Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation. Dispose of the collected material according to regulations.

· Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

· PAC-2:		
7631-90-5	sodium hydrogensulphite	15 mg/m³
122-99-6	2-Phenoxyethanol	1.5 ppm
1336-21-6	Ammonium Hydroxide	61 ppm
79-14-1	Glycolic acid	25 mg/m ³
90-64-2	mandelic acid	25 mg/m ³
140 11		

90-64-2	mandelic acid	270 mg/m ³
79-14-1	Glycolic acid	280 mg/m ³
1336-21-6	Ammonium Hydroxide	330 ppm
122-99-6	2-Phenoxyethanol	16 ppm
7631-90-5	sodium hydrogensulphite	66 mg/m ³

· PAC-3:

90-64-2	mandelic acid	1,600 mg/m ³
79-14-1	Glycolic acid	390 mg/m ³
1336-21-6	Ammonium Hydroxide	2,300 ppm
122-99-6	2-Phenoxyethanol	97 ppm
7631-90-5	sodium hydrogensulphite	400 mg/m ³
		(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/27/2018

Reviewed on 09/27/2018

Page 4/10

Trade Name: Exuviance Clarifying Peel/Booster Exuviance Professional Clarifying Peel/Booster

7 Handling and Storage

- · Handling
- · Precautions for safe handling:
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- Exposure controls:
- · Personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

- · Breathing equipment: Not required.
- · Protection of hands: Not required.
- · Material of gloves: Not applicable.
- · Penetration time of glove material: Not applicable.
- · Eye protection:



Tightly sealed googles required in a manufacturing setting only.

• *Limitation and supervision of exposure into the environment:* Keep away from drains, surface and ground waters. Avoid release into the environment.

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- General Information
- · Appearance:

Form:	
Color:	

Solution Light brown



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/27/2018

Reviewed on 09/27/2018

Trade Name: Exuviance Clarifying Peel/Booster Exuviance Professional Clarifying Peel/Booster

· Odour: · Odor threshold:	Characteristic Not determined.
· pH-value @ 20 °C (68 °F):	3.3-3.8
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not determined. ≥100 ℃ (≥212 ℉)
· Flash point:	None
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	Not applicable
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
• Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure @ 20 °C (68 °F):	≤23 hPa (≤17.3 mm Hg)
 Density: Relative density: Vapor density: Evaporation rate: 	Not determined. Not determined. Not determined.
 Solubility in / Miscibility with: Water: 	Miscible
· Partition coefficient (n-octanol/water): Not determined.
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.
 Solvent content: Organic solvents: Water: VOC content: 	0.6 % 70.4 % 0.64 %
Solids content: • Other information:	27.3 % No further relevant information available.

10 Stability and Reactivity

· *Reactivity:* No further relevant information available.

- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/27/2018

Reviewed on 09/27/2018

Trade Name: Exuviance Clarifying Peel/Booster Exuviance Professional Clarifying Peel/Booster

• LD/LC50 values that are relevant for classification: 90-64-2 mandelic acid Oral LD50 4,100 mg/kg (Rat) 79-14-1 Glycolic acid	Acute tox	on on toxicolog icity:	gicai enecis:
Oral LD50 4,100 mg/kg (Rat) 79-14-1 Glycolic acid ID50 1,950 mg/kg (Rat) 1336-21-6 Ammonium Hydroxide ID50 350 mg/kg (RAT) Remarks: Gastrointestinal: Other changes. Liver: Other changes. Kidney, Urete Bladder: Other changes. Inhalative LC50/96 hours 8.2 mg/l (Pimephales) Primary irritant effect: On the skin: Strong caustic effect on skin and mucous membranes. On the eye: Strong irritant with the danger of severe eye injury. Corrosive effect. Causes serious eye irritation. Additional toxicological information: The product shows the following dangers according to internally approved calculation methods preparations: Irritant Carcinogenic categories: IAC (International Agency for Research on Cancer): Group 1 - Carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 4 - Probably not carcinogenic to humans Group 4 - Probably not carcinogenic to humans Toxicology Program): None of the ingredients are listed. OSH-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. CSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. Ecological Information 2Ecological Information <th></th> <th>•</th> <th>relevant for classification:</th>		•	relevant for classification:
79-14-1 Glycolic acid Image: Sector of the sector of t	90-64-2 m	andelic acid	
Oral LD50 1,950 mg/kg (Rat) 1336-21-6 Ammonium Hydroxide Oral LD50 350 mg/kg (RAT) Remarks: Gastrointestinal: Other changes. Liver: Other changes. Kidney, Urete Bladder: Other changes. Inhalative LC50/96 hours 8.2 mg/l (Pimephales) Primary irritant effect: 0n the skin: Strong caustic effect on skin and mucous membranes. On the skin: Strong caustic effect on skin and mucous membranes. On the eye: Strong irritant with the danger of severe eye injury. Corrosive effect. Coursoive effect. Causes serious eye irritation. Additional toxicological information: The product shows the following dangers according to internally approved calculation methods preparations: Irritant Carcinogenic categories: IARC (International Agency for Research on Cancer): Group 1 - Carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 2 A - Probably carcinogenic to humans Group 4 - Probably not carcinogenic to humans 7631-90-5 sodium hydrogensulphite NTP (National Toxicology Program): None of the ingredients are listed. OSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. OSHA-Ca (Information Zecological Information Youry 4 - Pro	Oral	LD50	4,100 mg/kg (Rat)
1336-21-6 Ammonium Hydroxide Oral LD50 350 mg/kg (RAT) Remarks: Gastrointestinal: Other changes. Liver: Other changes. Kidney, Urete Bladder: Other changes. Inhalative LC50/96 hours 8.2 mg/l (Pimephales) Primary irritant effect: On the skin: Strong caustic effect on skin and mucous membranes. On the eye: Strong irritant with the danger of severe eye injury. Corrosive effect. Causes serious eye irritation. Additional toxicological information: Additional toxicological information: The product shows the following dangers according to internally approved calculation methods preparations: Irritant Irritant Carcinogenic categories: IARC (International Agency for Research on Cancer): Group 1 - Carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 2 - Probably not carcinogenic to humans Group 3 - Not classifiable as to its carcinogenicity to humans 7631-90-5 sodium hydrogensulphite INTP (National Toxicology Program): None of the ingredients are listed. OSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. Ecological Information Ecological Information Toxicity: Aquatic toxicity: Aquatic toxicity:	79-14-1 G	lycolic acid	
Oral LD50 350 mg/kg (RAT) Remarks: Gastrointestinal: Other changes. Liver: Other changes. Kidney, Urete Bladder: Other changes. Inhalative LC50/96 hours 8.2 mg/l (Pimephales) Primary irritant effect: On the skin: Strong caustic effect on skin and mucous membranes. On the skin: Strong caustic effect on skin and mucous membranes. On the eye: Strong irritant with the danger of severe eye injury. Corrosive effect. Causes serious eye irritation. Additional toxicological information: The product shows the following dangers according to internally approved calculation methods preparations: Irritant Carcinogenic categories: IARC (International Agency for Research on Cancer): Group 1 - Carcinogenic to humans Group 2 - Probably carcinogenic to humans Group 3 - Not classifiable as to its carcinogenicity to humans Group 3 - Not classifiable as to its carcinogenicity to humans Group 3 - Not classifiable as to its carcinogenicity to humans Group 4 - Probably not carcinogenic to humans Group 5 sodium hydrogensulphite NTP (National Toxicology Program): None of the ingredients are listed. OSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. E	Oral	LD50	1,950 mg/kg (Rat)
Remarks: Gastrointestinal: Other changes. Liver: Other changes. Kidney, Ureter Bladder: Other changes. Inhalative LC50/96 hours 8.2 mg/l (Pimephales) Primary irritant effect: On the skin: Strong caustic effect on skin and mucous membranes. On the skin: Strong caustic effect on skin and mucous membranes. Corrosive effect. Causes serious eye irritation. Additional toxicological information: The product shows the following dangers according to internally approved calculation methods preparations: Irritant Carcinogenic categories: IARC (International Agency for Research on Cancer): Group 1 - Carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 4 - Probably not carcinogenic to humans Group 4 - Probably not carcinogenic to humans Group 4 - Probably not carcinogenic to humans Group 5 sodium hydrogensulphite NTP (National Toxicology Program): None of the ingredients are listed. OSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. Ecological Information Toxicity: Aquatic toxicity:	1336-21-6	Ammonium Hy	ydroxide
 Primary irritant effect: On the skin: Strong caustic effect on skin and mucous membranes. On the eye: Strong irritant with the danger of severe eye injury. Corrosive effect. Causes serious eye irritation. Additional toxicological information: The product shows the following dangers according to internally approved calculation methods preparations: Irritant Carcinogenic categories: IARC (International Agency for Research on Cancer): Group 1 - Carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 3 - Not classifiable as to its carcinogenicity to humans Group 4 - Probably not carcinogenic to humans 7631-90-5 sodium hydrogensulphite NTP (National Toxicology Program): None of the ingredients are listed. Cecological Information: Toxicity: Aquatic toxicity: 	Oral	LD50	Remarks: Gastrointestinal: Other changes. Liver: Other changes. Kidney, Urete
 On the skin: Strong caustic effect on skin and mucous membranes. On the eye: Strong irritant with the danger of severe eye injury. Corrosive effect. Causes serious eye irritation. Additional toxicological information: The product shows the following dangers according to internally approved calculation methods preparations: Irritant Carcinogenic categories: IARC (International Agency for Research on Cancer): Group 1 - Carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 2B - Possibly carcinogenic to humans Group 3 - Not classifiable as to its carcinogenicity to humans Group 4 - Probably not carcinogenic to humans Totational Toxicology Program): None of the ingredients are listed. OSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. Ecological Information 	Inhalative	LC50/96 hours	8.2 mg/l (Pimephales)
Group 3 - Not classifiable as to its carcinogenicity to humans Group 4 - Probably not carcinogenic to humans 7631-90-5 sodium hydrogensulphite • <i>NTP (National Toxicology Program):</i> None of the ingredients are listed. • <i>OSHA-Ca (Occupational Safety & Health Administration):</i> None of the ingredients are listed. • <i>Cological Information</i> • <i>Toxicity:</i> • <i>Aquatic toxicity:</i>	preparatio Irritant <i>Carcinoge</i> <i>IARC (Inte</i> Group 1 - Group 2A	ns: enic categories ernational Ager Carcinogenic to - Probably carcin	s: ncy for Research on Cancer): humans nogenic to humans
 7631-90-5 sodium hydrogensulphite <i>NTP (National Toxicology Program):</i> None of the ingredients are listed. <i>OSHA-Ca (Occupational Safety & Health Administration):</i> None of the ingredients are listed. <i>Ecological Information</i> <i>Toxicity:</i> <i>Aquatic toxicity:</i> 	Group 3 -	Not classifiable	as to its carcinogenicity to humans
 NTP (National Toxicology Program): None of the ingredients are listed. OSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. Ecological Information Toxicity: Aquatic toxicity: 	•		•
None of the ingredients are listed. OSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. Ecological Information Toxicity: Aquatic toxicity:	7631-90-5	sodium hydrog	jensulphite
OSHA-Ca (Occupational Safety & Health Administration): None of the ingredients are listed. Ecological Information Toxicity: Aquatic toxicity:	•	-	
None of the ingredients are listed. Ecological Information Toxicity: Aquatic toxicity:	None of th	e ingredients ar	e listed.
 Ecological Information Toxicity: Aquatic toxicity: 	OSHA-Ca	(Occupational	Safety & Health Administration):
· Toxicity: · Aquatic toxicity:	None of th	e ingredients ar	e listed.
Aquatic toxicity:	e Ecologi	cal Informati	ion
Avoid release into the environment. Aution from the control of dilution water may cause pollution.	Aquatic to		ironment. Runoff from fire control or dilution water may cause pollution.
	1336-21-6	Ammonium Hy	ydroxide
EC50 0.66 mg/l (Daphnia)		-	

0.66 mg/l (Water flea)

· Persistence and degradability: No further relevant information available.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/27/2018

Trade Name: Exuviance Clarifying Peel/Booster Exuviance Professional Clarifying Peel/Booster

- · Behavior in environmental systems:
- · *Bioaccumulative potential:* No further relevant information available.
- · *Mobility in soil:* No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.

· vPvB:

1336-21-6 Ammonium Hydroxide

· Other adverse effects: No further relevant information available.

3 Disposal Considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

· Uncleaned packaging

· Recommendation: Disposal must be made according to official regulations.

4 Transport Information

 UN-Number: DOT, ADR/ADN, ADN, IMDG, IATA UN proper shipping name: DOT, ADR/ADN, ADN, IMDG, IATA Transport hazard class(es): 	Non-Regulated Material Non-Regulated Material
 DOT, ADR/ADN, ADN, IMDG, IATA Class: Packing group: DOT, ADR/ADN, IMDG, IATA 	Non-Regulated Material Non-Regulated Material
 Environmental hazards: Special precautions for user: Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: UN "Model Regulation": 	Not applicable. Not applicable. of Not applicable. Non-Regulated Material

15 Regulatory Information

· Safety, health and environmental regulations/legislation specific for the substance or mixture:

- SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

1336-21-6 Ammonium Hydroxide

Reviewed on 09/27/2018

(Contd. on page 8)



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/27/2018

Reviewed on 09/27/2018

Trade Name: Exuviance Clarifying Peel/Booster Exuviance Professional Clarifying Peel/Booster

122-99-6 2-Phenoxyethanol	
TSCA (Toxic Substances Control Act):	
90-64-2 mandelic acid	
79-14-1 Glycolic acid	
90-80-2 δ-Gluconolactone	
7200-25-1 DL-arginine	
1336-21-6 Ammonium Hydroxide	
122-99-6 2-Phenoxyethanol	
1117-86-8 Caprylyl Glycol	
7631-90-5 sodium hydrogensulphite	
7732-18-5 Water, distilled water, deionized water	
• TSCA new (21st Century Act) (Substances not listed)	
90-64-2 mandelic acid	
· California Proposition 65:	
· Chemicals known to cause cancer:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
· New Jersey Right-to-Know List:	
1336-21-6 Ammonium Hydroxide	
7631-90-5 sodium hydrogensulphite	
New Jersey Special Hazardous Substance List:	
1336-21-6 Ammonium Hydroxide	C
7631-90-5 sodium hydrogensulphite	C
Pennsylvania Right-to-Know List:	
1336-21-6 Ammonium Hydroxide	
7631-90-5 sodium hydrogensulphite	
Pennsylvania Special Hazardous Substance List:	
1336-21-6 Ammonium Hydroxide	
7631-90-5 sodium hydrogensulphite	
Carcinogenic categories:	
· EPA (Environmental Protection Agency):	
None of the ingredients are listed.	
• TLV (Threshold Limit Value established by ACGIH):	
7631-90-5 sodium hydrogensulphite	A
• NIOSH-Ca (National Institute for Occupational Safety and Health):	
None of the ingredients are listed.	
	(Contd. on nord



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/27/2018

Reviewed on 09/27/2018

Trade Name: Exuviance Clarifying Peel/Booster Exuviance Professional Clarifying Peel/Booster

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



- · Signal word: Danger
- Hazard-determining components of labeling: mandelic acid Glycolic acid Ammonium Hydroxide · Hazard statements: H318 Causes serious eye damage. H402 Harmful to aquatic life. · Precautionary statements: P273 Avoid release to the environment. Wear eye protection / face protection. P280 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a poison center/doctor.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

Date of preparation / last revision: 09/27/2018 / 1

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit



Reviewed on 09/27/2018



Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 09/27/2018

Trade Name: Exuviance Clarifying Peel/Booster Exuviance Professional Clarifying Peel/Booster

REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3 • * **Data compared to the previous version altered.** SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/13/2018

Reviewed on 11/13/2018

1 Identification

- · Product Identifier
- Trade Name: NeoStrata ProSystem Foaming Peel Neutralizer NeoStrata ProSystem Foaming Peel Neutralizer-Refill NeoStrata Perfecting Peel Neutralizer Pad Exuviance Neutralizing Solution Exuviance Neutralizing Solution-Refill Exuviance Professional Neutralizing Solution
- · Product Number: FLA#: 007-076
- Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description: Cosmetics, personal care products
- · Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier: NeoStrata Company Inc. 307 College Road East Princeton, NJ 08540 Phone: +1-609-520-0715 Fax: +1-609-986-1928 www.neostrata.com

Responsible Person: NeoStrata UG, DE-41470 Neuss

Emergency telephone number: Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887

2 Hazard(s) Identification

• Classification of the substance or mixture: The product does not need classification according to OSHA HazCom Standard 29 CFR paragraph (d) of §1910.1200(g) and GHS Rev 03.

- · Label elements:
- · GHS label elements Non-Regulated Material
- · Hazard pictograms: Non-Regulated Material
- · Signal word: Non-Regulated Material
- · Hazard statements: Non-Regulated Material
- · Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

- 0 % of the mixture consists of component(s) of unknown toxicity.
- · Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous Compone	· Dangerous Components:		
CAS: 57-55-6 RTECS: TY 2000000	Propylene Glycol	2-12%	
CAS: 56-81-5 RTECS: MA 8050000	Glycerol	2-12%	

• Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

(Contd. on page 2)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/13/2018

Reviewed on 11/13/2018

Trade Name: NeoStrata ProSystem Foaming Peel Neutralizer NeoStrata ProSystem Foaming Peel Neutralizer-Refill NeoStrata Perfecting Peel Neutralizer Pad Exuviance Neutralizing Solution Exuviance Neutralizing Solution-Refill Exuviance Professional Neutralizing Solution

4 First-Aid Measures

- · Description of first aid measures
- · General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: If skin irritation occurs, consult a doctor.
- · After eye contact:

If eye irritation occurs, consult a doctor.

Rinse opened eye for several minutes under running water.

- After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

- Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · For safety reasons unsuitable extinguishing agents: No further relevant information.
- Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters
- · Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures: Not required.
- · Environmental precautions: Do not allow to enter sewers/surface or ground water.

• **Methods and material for containment and cleaning up:** Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Dispose of the collected material according to regulations.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

- See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:		
57-55-6	Propylene Glycol	30 mg/m³
56-81-5	Glycerol	45 mg/m³
144-55-8	Sodium Hydrogencarbonate	13 mg/m³
· PAC-2:		
57-55-6	Propylene Glycol	1,300 mg/m³
56-81-5	Glycerol	180 mg/m³
144-55-8	Sodium Hydrogencarbonate	140 mg/m³
		(Contd. on page 3)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/13/2018

Reviewed on 11/13/2018

Trade Name: NeoStrata ProSystem Foaming Peel Neutralizer NeoStrata ProSystem Foaming Peel Neutralizer-Refill NeoStrata Perfecting Peel Neutralizer Pad Exuviance Neutralizing Solution Exuviance Neutralizing Solution-Refill Exuviance Professional Neutralizing Solution

· PAC-3:

57-55-6	Propylene Glycol	7,900 mg/m³
56-81-5	Glycerol	1,100 mg/m³
144-55-8	Sodium Hydrogencarbonate	840 mg/m³

7 Handling and Storage

- · Handling
- · Precautions for safe handling: No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

- · Control parameters:
- · Components with occupational exposure limits:

57-55-6 Propylene Glycol

WEEL Long-term value: 10 mg/m³

56-81-5 Glycerol

PEL Long-term value: 15* 5** mg/m³

mist; *total dust **respirable fraction

TLV TLV withdrawn-insufficient data human occup. exp.

• Additional information: The lists that were valid during the creation of this SDS were used as basis.

• Exposure controls:

- Personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

- Breathing equipment: Not required.
- Protection of hands: Not required.
- *Material of gloves:* Not applicable.
- Penetration time of glove material: Not applicable.

· Eye protection:



Goggles recommended during refilling.

· Limitation and supervision of exposure into the environment: None





ĺ

Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/13/2018

Solids content:

Trade Name: NeoStrata ProSystem Foaming Peel Neutralizer

Reviewed on 11/13/2018

Trade Name: NeoStrata ProSystem Foal	ming Peel Neutralizer ming Peel Neutralizer-Refill
NeoStrata Perfecting Peel	Neutralizer Pad
Exuviance Neutralizing So Exuviance Neutralizing So	
Exuviance Professional No	eutralizing Solution
9 Physical and Chemical Prope	rties
· Information on basic physical and c	hemical properties
General Information	
· Appearance: Form:	Liquid
Color:	Clear
· Odour: · Odor threshold:	Characteristic Not determined.
· pH-value @ 20 °C (68 °F):	7.5-9.5
· Change in condition	1.5-8.5
Melting point/Melting range: Boiling point/Boiling range:	Not determined. ≥100 °C (≥212 °F)
· Flash point:	≥100 °C (≥217.4 °F)
· Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	≥371 °C (≥699.8 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
• Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower: Upper:	Not determined. Not determined.
· Vapor pressure @ 20 °C (68 °F):	≤23 hPa (≤17.3 mm Hg)
Density @ 20 °C (68 °F):	1.0388 g/cm³ (8.6688 lbs/gal)
 Relative density: Vapor density: 	Not determined. Not determined.
· Evaporation rate:	Not determined.
 Solubility in / Miscibility with: Water: 	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity:	
Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content:	Not determined.
Organic solvents:	5.0 %
Water:	87.5 %
VOC content:	0.00 %

2.5 %

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/13/2018

Reviewed on 11/13/2018

Trade Name: NeoStrata ProSystem Foaming Peel Neutralizer

NeoStrata ProSystem Foaming Peel Neutralizer-Refill NeoStrata Perfecting Peel Neutralizer Pad Exuviance Neutralizing Solution Exuviance Neutralizing Solution-Refill Exuviance Professional Neutralizing Solution

• Other information:

No further relevant information available.

10 Stability and Reactivity

· Reactivity:

No further relevant information available.

The product is stable under normal conditions

No further relevant information available.

- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Toxicological Information

· Information on toxicological effects:

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

57-55-6 P	ropylene Glyco	l
Oral	LD50	20,000 mg/kg (Rat)
Dermal	LD50	20,800 mg/kg (Rabbit)
Inhalative	LC50/96 hours	52,930 mg/l (Pimephales)
	Intravenous	6,630 mg/kg (Mouse)
		6,423 mg/kg (Rat)
		6,500 mg/kg (Rabbit)
56-81-5 G	lycerol	
Oral	LD50	12,600 mg/kg (Rat)
Dermal	LD50	>10,000 mg/kg (Rabbit)
Inhalative	LC50/96 hours	>50,000 mg/l (Trout)

Primary irritant effect:

• On the skin: No irritating effect.

• On the eye: No irritating effect.

Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations.

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

Carcinogenic categories:

· Carcinogenic categories:
· IARC (International Agency for Research on Cancer):
None of the ingredients are listed.

• NTP (National Toxicology Program):

None of the ingredients are listed.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/13/2018

Reviewed on 11/13/2018

Trade Name: NeoStrata ProSystem Foaming Peel Neutralizer NeoStrata ProSystem Foaming Peel Neutralizer-Refill NeoStrata Perfecting Peel Neutralizer Pad Exuviance Neutralizing Solution Exuviance Neutralizing Solution-Refill Exuviance Professional Neutralizing Solution

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

2 Ecological Information

· Toxicity:

· Aquatic toxicity:

57-55-6 Propylene Glycol

EC50 >10,000 mg/l (Daphnia)

- · Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
- · *Bioaccumulative potential:* No further relevant information available.
- · Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

3 Disposal Considerations

· Waste treatment methods

· Recommendation:

Smaller quantities can be disposed of with household waste.

Observe all federal, state and local environmental regulations when disposing of this material.

· Uncleaned packaging

• **Recommendation:** Disposal must be made according to official regulations.

4 Transport Information

 · UN-Number: · DOT, ADR/ADN, ADN, IMDG, IATA · UN proper shipping name: · DOT, ADR/ADN, ADN, IMDG, IATA · Transport hazard class(es): 	Non-Regulated Material Non-Regulated Material
· DOT, ADR/ADN, ADN, IMDG, IATA · Class: · Packing group:	Non-Regulated Material
· DOT, ADR/ADN, IMDG, IATA	Non-Regulated Material
 Environmental hazards: 	Not applicable.
 Special precautions for user: 	Not applicable.
Transport in bulk according to Annex II o	f
MARPOL73/78 and the IBC Code:	Not applicable.





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/13/2018

Reviewed on 11/13/2018

Trade Name: NeoStrata ProSystem Foaming Peel Neutralizer NeoStrata ProSystem Foaming Peel Neutralizer-Refill NeoStrata Perfecting Peel Neutralizer Pad Exuviance Neutralizing Solution Exuviance Neutralizing Solution-Refill Exuviance Professional Neutralizing Solution

· UN "Model Regulation":

Non-Regulated Material

5 Regulatory Information

- Safety, health and environmental regulations/legislation specific for the substance or mixture:
- SARA (Superfund Amendments and Reauthorization):

· Section 355 (extremely hazardous substances):
None of the ingredients are listed.
· Section 313 (Specific toxic chemical listings):
None of the ingredients are listed.
· TSCA (Toxic Substances Control Act):
All ingredients are listed or exempt from listing.
· California Proposition 65:
· Chemicals known to cause cancer:
None of the ingredients are listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients are listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients are listed.
· Chemicals known to cause developmental toxicity:
· · · · · · · · · · · · · · · · · · ·
None of the ingredients are listed.
None of the ingredients are listed. • New Jersey Right-to-Know List:
None of the ingredients are listed. • New Jersey Right-to-Know List: 57-55-6 Propylene Glycol
None of the ingredients are listed. • New Jersey Right-to-Know List:
None of the ingredients are listed. · New Jersey Right-to-Know List: 57-55-6 Propylene Glycol 56-81-5 Glycerol · New Jersey Special Hazardous Substance List:
None of the ingredients are listed. • New Jersey Right-to-Know List: 57-55-6 Propylene Glycol 56-81-5 Glycerol
None of the ingredients are listed. · New Jersey Right-to-Know List: 57-55-6 Propylene Glycol 56-81-5 Glycerol · New Jersey Special Hazardous Substance List: None of the ingredients are listed. · Pennsylvania Right-to-Know List:
None of the ingredients are listed. New Jersey Right-to-Know List: 57-55-6 Propylene Glycol 56-81-5 Glycerol New Jersey Special Hazardous Substance List: None of the ingredients are listed. Pennsylvania Right-to-Know List: 57-55-6 Propylene Glycol
None of the ingredients are listed. · New Jersey Right-to-Know List: 57-55-6 Propylene Glycol 56-81-5 Glycerol · New Jersey Special Hazardous Substance List: None of the ingredients are listed. · Pennsylvania Right-to-Know List:
None of the ingredients are listed. New Jersey Right-to-Know List: 57-55-6 Propylene Glycol 56-81-5 Glycerol New Jersey Special Hazardous Substance List: None of the ingredients are listed. Pennsylvania Right-to-Know List: 57-55-6 Propylene Glycol 56-81-5 Glycerol Pennsylvania Right-to-Know List: 57-55-6 Propylene Glycol 56-81-5 Glycerol Pennsylvania Special Hazardous Substance List:
None of the ingredients are listed. · New Jersey Right-to-Know List: 57-55-6 Propylene Glycol 56-81-5 Glycerol · New Jersey Special Hazardous Substance List: None of the ingredients are listed. · Pennsylvania Right-to-Know List: 57-55-6 Propylene Glycol 56-81-5 Glycerol

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

• TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

• NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements Non-Regulated Material

· Hazard pictograms: Non-Regulated Material





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/13/2018

Reviewed on 11/13/2018

Trade Name: NeoStrata ProSystem Foaming Peel Neutralizer NeoStrata ProSystem Foaming Peel Neutralizer-Refill NeoStrata Perfecting Peel Neutralizer Pad Exuviance Neutralizing Solution Exuviance Neutralizing Solution-Refill Exuviance Professional Neutralizing Solution

· Signal word: Non-Regulated Material

· Hazard statements: Non-Regulated Material

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 11/13/2018 / 1

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL: Recommended Exposure Limit** * Data compared to the previous version altered. SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106