

Printed: 23/04/2015 Revised: V1-R-1-CLP du 23/04/2015

# **VITALITE - PARFUM**

### SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

#### 1.1. Product identifier

Name of the substance/mixture : VITALITE - PARFUM

N° CAS TSCA :N° CE :
N° index REACH An VI :
N° REACH (partially) :

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Parfum

### 1.3. Details of the supplier of the safety data sheet

#### SAS PARFUM COSMETIC WORLD

Parc de l'Argile - 213 Voie E 06370 Mouans-Sartoux - FRANCE Tel : +33 (0)4 92 28 23 30

Fax: +33 (0)4 92 28 23 39 Web: www.pcwfrance.com Email: info@pcwfrance.com

Technical responsible : regulatory@pcwfrance.com

## 1.4. Emergency telephone number

Emergency information service of the company

+33(6) 07 85 74 60 (24h/24h)

National emergency information service

INERIS: +33(8) 20 20 18 16

Anti poison Centers in France

ORFILA: +33(1) 45 42 59 59

## 2. SECTION 2 - HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

According to Regulation (EC) 1272/2008

(Legislation CLP)

EHC2 Hazardous to the aquatic environment, long-trem hazard 2

FL2 Flammable Liquids 2 SS1B Sensitisation, skin 1B

H225 - Highly flammable liquid and vapour



Printed: 23/04/2015 VITALITE - PARFUM Revised: V1-R-1-CLP du 23/04/2015

H411 - Toxic to aquatic life with long lasting effects.

EUH208 - May produce an allergic reaction. Contain: Geraniol,

6,7-Dihydro-1,1,2,3,3-pentamethyl-4(5H)-indanone, Tetramethyl acetyloctahydronaphthalenes (OTNE),

Limonene 1

#### 2.2. Label elements

According to Regulation (EC) 1272/2008 (Legislation CLP)







Warning mention: Danger

EHC2 Hazardous to the aquatic environment, long-trem hazard 2

FL2 Flammable Liquids 2 SS1B Sensitisation, skin 1B

H225 - Highly flammable liquid and vapour

H411 - Toxic to aquatic life with long lasting effects.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240+P241 - Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/.../equipment.

P243 - Take precautionary measures against static discharge

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272+P363 - Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container according to the local/regional / national / international Regulation.

EUH208 - May produce an allergic reaction. Contain : Geraniol, 6,7-Dihydro-1,1,2,3,3-pentamethyl-4(5H)-indanone, Tetramethyl acetyloctahydronaphthalenes (OTNE), Limonene  $^{\perp}$ 

#### 2.3. Other hazards

Sensitizing substances: See Tab. 3.1: Phrases H317 and/or EUH208

COV Swiss - Annex 2: 100%

## SECTION 3 - COMPOSITION INFORMATION ON INGREDIENTS

# 3.1. Substances

## 3.2. Mixtures

Material	C.A.S	EINECS	Classification	Percent %
----------	-------	--------	----------------	-----------



Printed: 23/04/2015 VITALITE - PARFUM Revised: V1-R-1-CLP du 23/04/2015

64-17-5	200-578-6	FL2 - H225	> à 50 %
105-95-3	203-347-8	EHC2 - H411	[ 1-5 ]
5989-27-5	227-813-5	AH1, EHA1, EHC1, FL3, SCI2, SS1B - H226, H304, H315, H317, H410	[ 1-5 ]
111879-80-2	422-320-3	EHA1, EHC1 - H400, H410	[ 1-5 ]
54464-57-2	259-174-3	EHA1, EHC1, SCI2, SS1B - H315, H317, H400, H410	[ 1-5 ]
68039-49-6	268-264-1	EDI2, EHC3, SCI2, SS1B - H315, H317, H319, H412	[ 0-1 ]
33704-61-9	251-649-3	EDI2, EHC2, SCI2, SS1A - H315, H317, H319, H411	[ 0-1 ]
5392-40-5	226-394-6	EDI2, SCI2, SS1B - H315, H317, H319	[ 0-1 ]
106-22-9	203-375-0	EDI2, SCI2, SS1B - H315	[ 0-1 ]
68737-61-1		EDI2, EHC3, SCI2, SS1 - H315, H317, H319, H412	[ 0-1 ]
141-78-6	205-500-4	EDI2, EUH066, FL2, STO-SE3-NE - H225, H319, H336	[ 0-1 ]
106-24-1	203-377-1	EDI1, SCI2, SS1A - H315	[ 0-1 ]
105-87-3	203-341-5	EHC2 - H411	[ 0-1 ]
8008-56-8	84929-31- 7	AH1, EHA1, EHC1, FL3, SCI2, SS1 - H226, H304, H315, H317, H400, H410	[ 0-1 ]
78-70-6	201-134-4	EDI2, SCI2 - H315, H319	[ 0-1 ]
115-95-7	204-116-4	EDI2, SCI2 - H315, H319	[ 0-1 ]
7212-44-4	230-597-5	EDI2, EHA1, EHC1 - H319, H410	[ 0-1 ]
8014-17-3	84929-38- 4	AH1, EHC2, SCI2, SS1 - H304, H315, H317, H411	[ 0-1 ]
469-61-4	207-418-4	AH1, EHA1, EHC1 - H304, H400, H410	[ 0-1 ]
14901-07-6	238-969-9	EHC2 - H411	[ 0-1 ]
127-91-3	204-872-5	AH1, FL3, SCI2, SS1B - H226, H304, H315, H317	[ 0-1 ]
99-87-6	202-796-7	AH1, EHC2, FL3 - H226, H304, H411	[ 0-1 ]
75-65-0	200-889-7	ATI4, EDI2, FL2, STO-SE3-RI - H225, H319, H332, H335	[ 0-1 ]
	105-95-3 5989-27-5 111879-80-2 54464-57-2 68039-49-6 33704-61-9 5392-40-5 106-22-9 68737-61-1 141-78-6 106-24-1 105-87-3 8008-56-8 78-70-6 115-95-7 7212-44-4 8014-17-3 469-61-4 14901-07-6 127-91-3 99-87-6	105-95-3 203-347-8 5989-27-5 227-813-5 111879-80-2 422-320-3 54464-57-2 259-174-3 68039-49-6 268-264-1 33704-61-9 251-649-3 5392-40-5 226-394-6 106-22-9 203-375-0 68737-61-1 141-78-6 205-500-4 106-24-1 203-377-1 105-87-3 203-341-5 8008-56-8 84929-31- 78-70-6 201-134-4 115-95-7 204-116-4 7212-44-4 230-597-5 8014-17-3 84929-38- 469-61-4 207-418-4 14901-07-6 238-969-9 127-91-3 204-872-5 99-87-6 202-796-7	105-95-3 203-347-8 EHC2 - H411  5989-27-5 227-813-5 AH1, EHA1, EHC1, FL3, SCI2, SS1B - H226, H304, H315, H317, H410  111879-80-2 422-320-3 EHA1, EHC1 - H400, H410  54464-57-2 259-174-3 EHA1, EHC1, SCI2, SS1B - H315, H317, H400, H410  68039-49-6 268-264-1 EDI2, EHC3, SCI2, SS1B - H315, H317, H319, H412  33704-61-9 251-649-3 EDI2, EHC2, SCI2, SS1A - H315, H317, H319, H411  5392-40-5 226-394-6 EDI2, SCI2, SS1B - H315, H317, H319, H411  106-22-9 203-375-0 EDI2, SCI2, SS1B - H315, H317, H319, H412  141-78-6 205-500-4 EDI2, EUH066, FL2, STO-SE3-NE - H225, H319, H336  106-24-1 203-377-1 EDI1, SCI2, SS1A - H315  105-87-3 203-341-5 EHC2 - H411  8008-56-8 84929-31- AH1, EHC1, FL3, SCI2, SS1 - H226, H304, H315, H317, H400, H410  78-70-6 201-134-4 EDI2, SCI2 - H315, H319  115-95-7 204-116-4 EDI2, SCI2 - H315, H319  7212-44-4 230-597-5 EDI2, EHA1, EHC1 - H319, H410  8014-17-3 84929-38- AH1, EHC2, SCI2, SS1 - H304, H315, H317, H411  469-61-4 207-418-4 AH1, EHC1 - H304, H400, H410  14901-07-6 238-969-9 EHC2 - H411  127-91-3 204-872-5 AH1, EHC2, FL3 - H226, H304, H315, H317  99-87-6 202-796-7 AH1, EHC2, FL3 - H226, H304, H411  75-65-0 200-889-7 AT14, EDI2, FL2, STO-SE3-RI - H225,

Description : Parfum

Solvent : Ethyl alcohol denat. / Aqua

Colorant(s):

## 4. SECTION 4 - FIRST AID MEASURES

## 4.1. Description of first aid measures



Printed: 23/04/2015 VITALITE - PARFUM Revised: V1-R-1-CLP du 23/04/2015

**General notes :** Please refer to the risk and safety statements (section 2)

**Following inhalation :** If inhaled : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Remove collar, belt, tie... Give artificial respiration if not breathing.

**Following ingestion :** If swallowed: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting.

Following skin contact: If on skin (or hair) or clothing rinse immediately contaminated clothing and skin with plenty of water

before removing clothes. If the symptom persists, consult a doctor.

**Following eye contact:** Rinse cautiously with water for several minutes (15 minutes open eyelids). Remove contact lenses, if present and easy to do. Continue rinsing. In case of disorder, consult an ophtalmologist.

Self-protection of the first aider: In lack of appropriate formation, none initiative should imply an individual risk.

#### 4.2. Most important symptoms and effects, both acute and delayed

See section 2

### 4.3. Indication of any immediate medical attention and special treatment needed

See section 2

## 5. SECTION 5 - FIREFIGHTING MEASURES

### 5.1. Extinguishing media

**Suitable extinguishing media:** Use an extinguishing agent suitable for the surrounding fire. CO2, powder, foam, specific liquid.

Unsuitable extinguishing media: Never use a direct stream of water.

#### 5.2. Special hazards arising from the substance or mixture

Flammability: The product is not flammable.

Prevention: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Particular risks linked to exposure: see section 2

#### Hazardous combustion products:

Release of poison gases : Monoxide de carbone (CO), Dioxyde de carbon (CO2), Oxyde d'azotes (NOx), Dioxyde de soufre (SO2), Cyanures (CN) ....

### 5.3. Advice for firefighters

**Fire-fighting equipment:** use an appropriate personal protective equipment with an approved positive-pressure self-contained breathing apparatus.

## 6. SECTION 6 - ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Call immediately the emergency personnel.



Printed: 23/04/2015 VITALITE - PARFUM Revised: V1-R-1-CLP du 23/04/2015

Promote adequate ventilation in the area.

### For non-emergency personnel

Keep them away from the area. Avoid all sources of ignition (spark of flame).

Avoid skin/eye contact. Do not inhal vapours.

#### For emergency responders

Use personal protective equipment. In case of accidental spills, wear protective gloves during the handling.

### 6.2. Environmental precautions

Avoid the dispersion and flow of the product. Keep away from drains, surface and ground water. Inform the competent authorities if the product enters in ground or surface waters.

### 6.3. Methods and material for containment and cleaning up

#### For containment

The spillage is contained with sand or inert powder. The chemical waste is placed in sealed containers.

#### For cleaning up

The soiled elements (rags, absorbent papiers, filters) are immediately soaked into water. The chemical waste are rapidly treated according to the local reglementation

### Other informations

Only qualified personnel is allowed to clean up.

## 6.4. Reference to other sections

See section 8 for personal protective equipment and section 13 for waste treatment.

## 7. SECTION 7 - HANDLING AND STORAGE

## 7.1. Precautions for safe handling

## Protective measures:

See section 2.2











## Measures to prevent fire:

Do not smoke. Do not expose to excessive heat or ignition sources (spark or flame).

### Measures to prevent aerosol and dust generation:

Maintain adequate ventilation in the area.

#### Measures to protect the environment:

Avoid spreading product and keep it from spilling. Precautions or coming in contact with the ground, waterways, drains and vents.

### Advice on general occupational hygiene:

Follow the general hygiene rules.

#### 7.2. Conditions for safe storage, including any incompatibilities



Printed: 23/04/2015 VITALITE - PARFUM Revised: V1-R-1-CLP du 23/04/2015

Storage conditions: Store in its original packaging in a cool dry place, away from light.

<u>Technical measures:</u> Close the container after use. In case of transferring, reproduce the labelling.

Packaging materials: Preserve only in the container of origin.

Respect the general rules of incompatibility.

Storage: Industrial: Keep under Nitrogen, in ambiant temperature. Avoid prolonged exposure to light, humidity and air.

### 7.3. Specific end use(s)

Wash the hands and any other zone exposed with soap and water before eating, drinking, to smoke and before leaving work.

### 8. SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1. Control parameters

**Measures of technical order:** Avoid contact with eyes, skin and closes. Do not ingest. Do not inhal vapors. Use proper personal protective equipment.

**Monitoring procedures**: If the product contains ingredients presenting exposure limits, he can turn out necessary to make an examination followed by the persons, by the atmosphere in the workplace either bodies living to end the efficiency of the ventilation or the other control measures or estimate the need to use of the material of protection of respiratory tracts. It is important to put back you in the European standard EN 689 concerning the methods to estimate the exhibition by inhalation to the chemical agents and to the national general documents of politics relative to the methods to determine dangerous substances.

### 8.2. Exposure controls

#### Appropriate technical controls:

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure.

#### Personal protection measures:

#### Personal protection:

- -Protection des mains : Protection non requise.-Protection des yeux : Protection non requise.
- -Protection respiratoire : En cas de ventilation insuffisante, porter un appareil respiratoire approprié.

**Respiratory protection**: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates that is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter apparatus (dust masks or half masks)

Type of filters

Type AX (Brown): Organic compounds boiling point < 65°C Type A (Brown): Organic compounds boiling point > 65°C

Type B (Grey): Inorganic gasses and fumes. Type P (White): Particles, dusts and aerosols

**Hand protection**: Impermeable and chemical resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary >8 hours before piercing: vinyle disposable.

**Remark**: Recommended impermeable goggles do not only depend of his matter. Other factors can have a signifiant effect on impermeability, like their thickness or specific use or temperature conditions. In all cases, matter certificates should be selected. Ask your supply if the goggles are appropriate to this use.

Eyes protection: Safety eyewear complying with an approved standard should be used when a risk assessment



Printed: 23/04/2015 VITALITE - PARFUM Revised: V1-R-1-CLP du 23/04/2015

indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Recommanded: Splash googles, safety glasses with side-shields.

**Skin protection**: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Body: Recommanded: lab coat (sarrau), general.

Type 3: Liquid impermeability Type 4: Aerosol impermeability

Type 6: Impermeability limited to liquid splashs

Foot: Recommanded: neoprene

Upper and sole resistant and impermeable (Hydrocarbure resistant).

## 9. SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance : Liquid

Color: Colourless to clear green translucent

Density at 20°C : **[0.826 ; 0.866]**Refractive index @ 20°C : **[1.373 ; 1.383]** 

Flash point (°C) (close cup): 21

9.2. Other information

Not applicable

## 10. SECTION 10 - STABILITY AND REACTIVITY

10.1. Reactivity

Avoid powerful oxidizing agents

10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

Avoid any potential source of heat.

10.5. Incompatible materials

Not applicable

10.6. Hazardous decomposition products

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications. **Dangerous decomposition products:** No dangerous decomposition products known.

### 11. SECTION 11 - TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological

#### 12. SECTION 12 - ECOLOGICAL INFORMATION



Printed: 23/04/2015 VITALITE - PARFUM Revised: V1-R-1-CLP du 23/04/2015

12.1. Toxicity

Do not leave the product, even diluted or in great quantity, penetrate the ground water, water or the drains.

12.2. Persistence and degradability

Not applicable

12.3. Bioaccumulative potential

Not applicable

12.4. Mobility in soil

PNEC sol

12.5. Results of PBT and vPvB assessment

vPvB : PBT :

12.6. Other adverse effects

No data

### 13. SECTION 13 - DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Product**: Does not have to be evacuated with the refuse. Not let it penetrate in the sewers.

**Not cleaned packing:** Evacuation according to local reglementation.

## 14. SECTION 14 - TRANSPORT INFORMATION

ADR:





IMDG:





IATA:



14.1. UN number

ADR: 1266 (Tunnel code (D/E))

IMDG:1266 IATA:ID8000

14.2. UN proper shipping name



Printed: 23/04/2015 VITALITE - PARFUM Revised: V1-R-1-CLP du 23/04/2015

ADR: Perfumery products IMDG:Perfumery products IATA:Consumer commodity

14.3. Transport hazard class(es)

ADR: 3 IMDG:3 IATA:9

14.4. Packing group

ADR : II IMDG:II

IATA: Not applicable

14.5. Environmental hazards

IMDG:

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

(Except particular case)

IBC Liquid substances

Metal (31A, 31B, 31N)

Plastic (31H1, 31H2)

**GRV Solid substances** 

Metal (11A, 11B, 21A, 21N)

Plastic (11H1, 11H2, 21H1, 21H2)

### 15. SECTION 15 - REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Custom tariff: 3303 00 10 00

15.2. Chemical safety assessment

## 16. SECTION 16 - OTHER INFORMATIONS

H225 Highly flammable liquid and vapour

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 Kann Schläfrigkeit und Benommenheit verursachen.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.



Printed: 23/04/2015 VITALITE - PARFUM Revised: V1-R-1-CLP du 23/04/2015

H412 Harmful to aquatic life with long lasting effects.

.....

**Key literature references and sources for data**Sources for data: Information from supplier

Literature references : ECHA

Literature references EU: Reg. 1272/2008

\_\_\_\_\_\_

Safety data sheet according to REG. 1272/2008/CE and its amendings

These indications are founded on the current state of our knowledge, but do not constitute a guarantee as for the

properties of the product and do not give place to a contractual legal report.