


HiLo MultiPro




TOP:

Top design	Four-piece adjustable top with round corners, three-layer foam, 3/4" plywood
Standard size top	30" x 73"
Foam	2" firm bottom layer + 1- 3/4" medium-density layer of urethane polymer
Polyester batting	1/2" fluffy polyester Dacron top layer
Frame	3/4" plywood frame reinforced for arm rests and face cradle
Adjustments	Easy gas/hydraulic lift adjustments of torso, knee, and upper body sections
Back tilt angle	0 to 60°
Knee tilt angle	0 to 30°



BASE & FRAME:

Carbon steel base	Sleek, contemporary design with white powder-coat finish
8" leg recess	8" recess from ends of table
Height range - standard	17" to 36" infinite motorized adjustment (ADA compliant)
Lifting weight	Lifting weight capacity 325 lbs.
Capacity	Static weight capacity 600 lbs.




MOTORS & CONTROLS

Base lift motor	One 24v DC, 5 amp max motor/actuator, UL recognized, powered through a 110v, 5 amp transformer
Controls	Foot control for lift motor Levers for mechanical cable operation of top adjusting cylinders

VINYL:

Ultra-Soft Touch - standard	Lightly textured, super-soft PU vinyl, fabric backed, environmentally friendly
-----------------------------	--




ACCESSORIES:

Sidearms	60-degree Sidearms
Face support	Deluxe FaceSpace II
Foot extension	Salon Footrest or Full Footrest
Neck Bolster	Facial Neck Bolster

GUARANTEES:

Structure	10 yrs.
Vinyl & foam	Guaranteed to arrive in good condition
Motor & controls	1 yr.



WEIGHTS:

Table Weight	235 lbs.
Shipping weight - boxed	295 lbs. (83" x 35" x 39" = 66 cu ft)

1/9/2009

www.TouchAmerica.com
(800) 678-6824 · (919) 732-6968
PO Box 1304 · Hillsborough · NC 27278

