### **SAFETY DATA SHEET**

Page 1 of 10 **SDS-334** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 9/19/2014

	T=	1. PRODUCT & COMPANY IDENTIFICATION								
1.1	Product Name:	OPI NAIL LACQUER								
1.2	Chemical Name:	Solvent Mixture								
1.3	Synonyms:	OPI Nail Lacquers								
1.4	Trade Names:	All Colors; Basecoats; Topcoats; and Treatments (except strengtheners)								
1.5	Product Use:	Cosmetic Use Only								
1.6	Distributor's Name:	OPI Products, Inc.								
1.7	Distributor's Address:	13034 Saticoy Street, No. Hollywood, CA 91605 USA								
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 16377)								
1.9	Business Phone / Fax:	+1 (818) 759-2400 / +1 (818) 759-5776								
		2. HAZARDS IDENTIFICATION								
2.1	Hazard Identification:	This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia).  DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS.  Hazard Statements (H): H225 – Highly flammable liquid and vapor. H317 – May cause an allergic skin reaction. H319 – Causes serious eye irritation. H335 – May cause respiratory irritation. H336 – May cause drowsiness or dizziness.  Precautionary Statements (P): P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P243 – Take precautionary measures against static discharge. P261 – Avoid breathing dust/fume/gas/mist/vapors/spray. P264 – Wash exposed skin areas thoroughly with soap and water after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/eye protection/face protection. P302+P352 – IF ON SKIN: Wash with soap and water. P305+P351+P338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and								
		easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).								
2.2	Effects of Exposure:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal								
	Effects of Exposure:  Symptoms of Overexposure:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion:  Ingestion:  Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact System. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingree Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headact nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected and section 2 (and irritation of affected and irritation if affected and irritation irritation if affected and irritation if affect								
1.3	Symptoms of Overexposure:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion:  Ingestion:  Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.  Skin:  May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficent breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingree Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headact nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.								
1.3		easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion:  Ingestion:  Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.  Skin:  May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficultation:  Inhalation:  Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficultation; Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingree Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headact nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause.								
2.3	Symptoms of Overexposure:  Acute Health Effects:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Skin: May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contains and inhalation: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiration system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingred Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headach nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can calcover the content of the product of								
2.3	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion:  If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems of the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Skin:  May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingree Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headact nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.								
2.3	Symptoms of Overexposure:  Acute Health Effects:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Skin: May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contains and inhalation: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiration system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingred Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headach nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can calcover the content of the product of								
2.3	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion:  If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated container. Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiration system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingred Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches and nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can call drowsiness, dizziness, headaches and nausea.  None known.  Eyes, skin and respiratory system.								
2.3	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> . Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems. Symptoms of overexposure may include redness, itching, irritation and watering. Skin: May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contains and the product may be slightly irritating to the nose, throat and other tissues of the respirations system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingred Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headach nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can call drowsiness, dizziness, headaches and nausea.  None known.  Eyes, skin and respiratory system.								
2.3	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion:  If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated container. Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiration system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingred Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches and nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can call drowsiness, dizziness, headaches and nausea.  None known.  Eyes, skin and respiratory system.								
2.3	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems depression.  Eyes: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.  Skin: May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated containal Inhalation: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respirations of vapors of this product may be slightly irritating to the nose, throat and other tissues of the respirations of vapors of the levels listed in Section 2 (Composition and Ingree Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaction and the product of the control of the product are redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can call drowsiness, dizziness, headaches and nausea.  None known.  Eyes, skin and respiratory system.   3. COMPOSITION & INGREDIENT INFORMATION  EXPOSURE LIMITS IN AIR (mg/m²)  ACGIH NOHSC OSHA								
2.3	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion:  If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems:  Skin:  May be irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Way be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated container. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingree Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headach anusea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cardrowsiness, dizziness, headaches and nausea.  None known.  Eyes, skin and respiratory system.  3. COMPOSITION & INGREDIENT INFORMATION  EXPOSURE LIMITS IN AIR (mg/m³)  ACGIH NOHSC OSHA  ppm								
2.4 2.5 2.6	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems. Skin: May be irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Way be irritating to the eyes. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficent breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingree Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headact nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected and overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can call drowsiness, dizziness, headaches and nausea.  None known.  Eyes, skin and respiratory system.  Since MPOSITION & INGREDIENT INFORMATION  Exposure LIMITS IN AIR (mg/m³)  ACGIH NOHSC OSHA  ppm								
2.3 2.4 2.5 2.6	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:  Target Organs:	easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.  Eyes: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Way be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contain Inhalation: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiration system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficent information) can cause central nervous system depression (e.g., drowsiness, dizziness, headach nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected and overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can concert to the concentrations of vapors can concentrate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can concentrate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can concentrate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can concentrate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can concentrate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can concentrate the part								
3 4 5 6	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:  Target Organs:	easy to do – continue rínsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact Inhalation: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respirations. Inhalation of overexposure can include coughing, wheezing, nasal congestion, and diffinite breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingree Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headac nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cardrowsiness, dizziness, headaches and nausea.  None known.  Eyes, skin and respiratory system.  3. COMPOSITION & INGREDIENT INFORMATION    EXPOSURE LIMITS IN AIR (mg/m³)   Ppm   P								
2.3 2.4 2.5 2.6 CHEN	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:  Target Organs:	easy to do – continue rínsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, Co <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion:  If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems.  Eyes:  Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.  May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contain Inhalation:  Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiration. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingree Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headach nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected are overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can carrowsiness, dizziness, headaches and nausea.  None known.  Eyes, skin and respiratory system.   3. COMPOSITION & INGREDIENT INFORMATION  Exposure Limits in Air (mg/m³)  ACGIH NOHSC OSHA ppm								
2.3 2.4 2.5 2.6 THY	Symptoms of Overexposure:  Acute Health Effects:  Chronic Health Effects:  Target Organs:  ICAL NAME(S)  - ACETATE	easy to do – continue rínsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (see section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO <sub>2</sub> , Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).  Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous systems: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Skin: May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contain Inhalation: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiraty system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficult breathing. Inhalation of vapors exceeding the levels listed in Section 2 (Composition and Ingree Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headact nausea).  Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected and Overexposure in eyes may cause redness, itching and watering.  Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can concover to make the content of								

NA = Not Available; ND = Not Determined; NE = Not Established; NF = Not Found; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2010 format.

5-10

400 400 400 200 NF NA NA 2000 400 TWA

NA

9004-70-0

Flam. Liq. 2; H225

NITROCELLULOSE

QW0970000

# **SAFETY DATA SHEET**

Page 2 of 10 **SDS-334** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 9/19/2014

Frepared to OSTIA, ACO, ANSI, NOT	100, 111 11110, 2	001/00 0 12/2/20	OO, LO Claridara			0001	CEVISIO	1. 1.1		0001	TOVIOIO	1 Dato.	9/19/2014
3.	COMPO	SITION 8	INGRED	IENT	INF	ORM	IATI						
										LIMITS IN AIR (mg/m³)			1
						GIH		NOHSC			OSHA		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	ppm STEL	IDLH	OTHER
MAY CONTAIN: RESIN/PLASTICIZE	R/EXCIPIENT			•			•	•					
ACETYL TRIBUTYL CITRATE	77-90-7	NA	201-067-0	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
	,	Muta. 1B; Carc. 1E	· · · · · · · · · · · · · · · · · · ·										
TRIMETHYLPENTANEDIYL DIBENZOATE	68052-23-3	NA	268-316-3	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
	25035-71-6	QW0970000	NA	5-10	NA	NA	NA	NA	NA	NA	NA	NA	
TOSYLAMIDE EPOXY RESIN					ı						1	ı	
TRIMETHYL PENTANYL DIISOBUTYRATE	6846-50-0	NA	226-934-9	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
TRIPHENYL PHOSPHATE	115-86-6	TC840000	204-112-2	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
TRIPHENTE PHOSPHATE	Aquatic Acute	1; Aquatic Chroni		1	,						,	,	
ADIPIC ACID / NEOPENTYL/	28407-73-0	NA	NA	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
GLYCOL / TRIMELLTIC ANHYDRIDE COPOLYMER	Skin Sens. 1; l	H317											
PROPYL ACETATE	109-60-4	AJ3675000	203-686-1	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
TROFIL AGEIATE	Flam. Liq. 2, E	ye Irrit. 2, STOT	SE 3; H225, H31	9, H336									
TOSYLAMIDE/FORMALDEHYDE RESIN	25035-716	QW0970000	NA	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
ETHYL TOSYLAMIDE	1077-56-1	NA	214-073-3	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
	71-36-3	EO1400000	200-751-6	5-10	NA	50	50	152	50	100	NA	1400	
N-BUTYL ALCOHOL		cute Tox. 4; Skin										1400	
	64-17-5	KQ6300000	200-578-6	5-10	1000			NF	NF	1000		3300	
ETHANOL (SB ALCOHOL 40-B)	Flam. Liq. 2; H	1225											
SUCROSE ACETATE ISOBUTYRATE	126-13-6	WN6550000	204-771-6	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
HEPTANE	142-82-5	MI7700000	205-563-8	5-10	400	500	400	1640	NF	500	NA	750	
THE TYME		kin Irrit. 2; STOT-											
CELLULOSE ACETATE BUTYRATE	9004-36-8	NA	NA	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
ADIPIC ACID/ISOPHTHALIC	25950-34-9	NA	INA	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
ACID/NEOPENTYL GLYCOL/TRIMETHYLOL PROPANE	200000.0	1.0.	1	10 .0	1								
COPOLYMER		1	I	1									
PHTHALIC ANHYDRIDE/TRIMELLITIC	NA	NA	NA	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
ANHYDRIDE/GLYCOLS COPOLYMER													
CAMPHOR	76-22-22	EX1225000	200-945-0	< 3.0	2	4	2	12	NF	NA	NA	200	
		cute Tox. 4; Skin											
DI-HEMA TRIMETHYLHEXYL DICARBAMATE	41137-60-4	NA	276-957-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
ETHYL TRIMETHYLBENZOYL PHENYLPHOSPHINATE	NA	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
MAY CONTAIN: COLOR / SHIMMER	/ GLITTER												
CI 77891 (TITANIUM DIOXIDE)	13463-67-7	XR2275000	236-675-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 19140 (YELLOW 5)	1934-21-0	CB7700000	201-353-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77120 (BARIUM SULFATE)	7727-43-7	CR0600000	231-784-4	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 15850 (RED 6)	5858-81-1	NA	215-111-1	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
MICA	12001-26-2	VV8760000	310-127-6	< 1.0	NA	NA	(2.5)	NF	NF	30	NA	NA	RESP FRAC
CI 15850 (RED 7)	5281-04-9	UQ6400000	217-699-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77491 (IRON OXIDES)	1309-37-1	UD3422500	248-666-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77499 (IRON OXIDES)	1309-37-9	NA	231-791-2	< 1.0	NE	NE	NF	NF	NF	NE	NE	NE	

# **SAFETY DATA SHEET**

Page 3 of 10 **SDS-334** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 9/19/2014

3	COMPO	OSITION 8	R INGREI	DIENT	INF	)RM	ΔΤΙ	ON -	- CO	nt'd			
			I IIIOILE		TIME OF IN		EXPOSURE LIMITS IN AIR (mg					n/m³)	
					ACC	GIH	NOHSC			OSHA			
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	рр	m		ppm			ppm		OTHER
CI 77510 (FERRIC	14038-43-5	NA	215-277-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
FERROCYANIDE)		•		1									
POLYVINYL BUTYRAL	63148-65-2	TR49550000	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
STYRENE / ACRYLATES	25133-97-5	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
COPOLYMER	1	e Irrit. 2; Aq. Chr											
TINIOVIDE	18282-10-5	XQ400000	242-159-0	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
TIN OXIDE	STOT SE 3; H	335	•						- I	i i			
CI 15880 (RED 34)	6417-83-0	NA	229-142-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77266 (BLACK 2)	1333-86-4	FF5800000	215-609-9	< 1.0	3.5	NA	3	NF	NF	3.5	NA	NA	
CITIZOO (BLACKZ)			_										
CI 77000 (ALUMINUM POWDER)	7429-90-5	CR0600000	231-784-4	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
POLYETHYLENE TEREPHTHALATE	25038-59-9	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
	05400 07 5	INIA	TNIA	1.10	NIA.	NIA	NE	NE	NIE	NIA	NIA	NIA	
ACRYLATES COPOLYMER	25133-97-5	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 60725 (VIOLET 2)	81-48-1	CB7700000	201-353-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
,	05007.47.0	Tara	000 040 0	1.40		N10	NE	NE	NE	NIA	NIA.	110	
CALCIUM ALUMINUM BOROSILICATE	65997-17-3	NA O	266-046-0	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
BOROSILICATE		re Irrit. 2A; Carc.			<u> </u>		NE	NIE	NIE	NIA	NIA	NIA	
PHOSPHORIC ACID	7664-38-2	Tb6300000	231-633-2	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
	Skin Corr. 1B;		223-339-8	1.10	NIA	NIA	NE	NIF	NIF	NIA	NIA	NIA	
CI 42090 (BLUE 1)	3844-45-9	BQ4725000	223-339-6	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
POLYURETHANE-11	NA	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
	12002 20 2	NA	234-426-5	< 1.0	NA	NIA	NF	NF	NF	NIA	NA	NA	
SYNTHETIC FLUORPHLOGOPITE	12003-38-2	INA	234-426-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 77163 (BISMUTH	7787-59-9	NO740000	215-168-2	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
OXYCHLORIDE)	7707 33 3	110740000	210 100 2	1.0	14/1	14/ (	141	141	141	14/ (	14/ (	147.	
	65997-17-3	NA	266-046-0	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CALCIUM SODIUM BOROSILICATE		•	•							1			
CI 77742 (MANGANESE VIOLET)	10101-66-3	NA	233-257-4	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 11142 (MANGANESE VIOLET)			_										
CI 77820 (SILVER)	7440-22-4	VW3500000	231-131-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
0.11020 (0.212.1)		T		1	1	1							
CI 77007 (ULTRAMARINES)	1302-83-6	NA	215-111-1	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
·	NA	NA	NA	< 1.0	NA	NIA	NF	NF	NF	NA	NA	NA	
POLYURETHANE-33	INA	INA	INA	< 1.0	INA	NA	INF	INF	INF	INA	INA	INA	
ALUMINUM CALCIUM SODIUM	1344-01-1	NA	215-685-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
ISILICATE	1344-01-1	JINA	210-000-0	1.0	INA	INA	INI	INI	INI	INA	INA	INA	
	8004-92-0	CG5796000	305-897-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 47005 (YELLOW 10)				1									
ALLIMINI IN LIVEROVIDE	21645-51-2	NA	244-492-7	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
ALUMINUM HYDROXIDE			•										
CI 45410 (RED 28)	13473-26-2	NA	236-747-6	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
OI 40410 (NEB 20)			•										
POLYBUTYLENE TEREPHTHALATE	26062-94-2	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
- OETBOTTEENE TERETTIMENE		T	_										
ETHYLENE/VA COPOLYMER	24937-78-8	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
DIS(CLYCIDOVVDLIENVL)	NA	NA	NA	Z 1 0	NA	NIA	NF	NF	NF	NIA	NIA	NA	
BIS(GLYCIDOXYPHENYL) PROPANE/	INA	INA	INA	< 1.0	INA	NA	INF	INF	INF	NA	NA	NΑ	
BISAMINOMETHYLNORBORNANE													
COPOLYMER													
TRIMETHYLSILOXYSILICATE	NA	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
Emiloniconic		T	1										
DIAMOND POWDER	7782-40-3	NA	231-953-2	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
	E06.03.0	I MEQCOOC	200 070 0	440	NIA.	NIA	NE	NE	NE	NIA	N/A	NI A	
CI 45370 (ORANGE 5)	596-03-2	LM5200000	209-876-0	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	

# **SAFETY DATA SHEET**

Page 4 of 10 **SDS-334** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 9/19/2014

001404	CITION	INODE	SIENIT	INITA		ATI	211		4.7 -1			
				ACG	HIE	-		OKE LI	MIISIN		g/m )	
CAS No.	RTECS No.	EINECS No.	%				ppm			ppm		OTHER
8003-22-3	NA	232-318-2	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	<b>U</b>
NIA	TNA	TNIA	1.10	NIA I	NIA	NE	NIE I	NE	NIA	NΙΔ	NIA	
NA	INA	INA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
518-47-8	NA	208-253-0	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
17372-87-1	NA	241-409-6	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
1344-28-1	BD1200000	215-691-6	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
25956-17-6	NA	247-368-0	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
7440-57-5	NA	231-165-9	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
9003-07-0	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
67924-34-9	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
4430-18-6	NA	224-618-7	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
7440-50-8	GL5325000	231-159-6	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
51274-00-1	NA	257-098-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
85-86-9	QK4250000	201-638-4	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
9002-88-4	TQ3325000	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
NA	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
14807-96-6	WW2710000	238-877-9	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
7439-89-6	NA	231-096-4	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
73-40-5	NA	200-799-8	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
Skin Irrit. 2, Ey	e Irrit. 2, STOT S	E 3; H315, H31	9, H335				•					
1390-65-4	FH8891000	215-724-4	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
1308-38-9	GB6475000	215-160-9	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
7440-06-4	TP2160000	231-116-1	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
3567-66-6	NA	222-656-9	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
518-47-8	NA	208-253-0	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
2783-94-0	ZF6680000	220-491-7	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
13-14-98-3	NA	215-251-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
2814-77-9	NA	220-562-2	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
17372-87-1	NA	241-409-6	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
2379-74-0	VV8760000	310-127-6	< 1.0	NA	NA	(2.5)	NF	NF	30	NA	NA	RESP FRAC
1308-14-1	NA	215-158-8	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
	CAS No. 8003-22-3 NA  518-47-8 17372-87-1 1344-28-1 25956-17-6 7440-57-5 9003-07-0 67924-34-9 4430-18-6 7440-50-8 51274-00-1 85-86-9 9002-88-4 NA 14807-96-6 73-40-5 Skin Irrit. 2, Ey 1390-65-4 1308-38-9 7440-06-4 3567-66-6 518-47-8 2783-94-0 13-14-98-3 2814-77-9 17372-87-1 2379-74-0	CAS No. RTECS No. 8003-22-3 NA  NA NA  NA NA  17372-87-1 NA  1344-28-1 BD1200000  25956-17-6 NA  7440-57-5 NA  9003-07-0 NA  67924-34-9 NA  4430-18-6 NA  7440-50-8 GL5325000  51274-00-1 NA  85-86-9 QK4250000  9002-88-4 TQ3325000  NA NA  14807-96-6 WW2710000  7439-89-6 NA  73-40-5 NA  Skin Irrit. 2, Eye Irrit. 2, STOT S 1390-65-4 FH8891000  1308-38-9 GB6475000  7440-06-4 TP2160000  7440-06-4 TP2160000	CAS No.         RTECS No.         EINECS No.           8003-22-3         NA         232-318-2           NA         NA         NA           518-47-8         NA         208-253-0           17372-87-1         NA         241-409-6           1344-28-1         BD1200000         215-691-6           25956-17-6         NA         247-368-0           7440-57-5         NA         231-165-9           9003-07-0         NA         NA           4430-18-6         NA         NA           440-50-8         GL5325000         231-159-6           51274-00-1         NA         257-098-5           85-86-9         QK4250000         201-638-4           9002-88-4         TQ3325000         NA           NA         NA         NA           14807-96-6         WW2710000         238-877-9           7439-89-6         NA         231-096-4           73-40-5         NA         200-799-8           Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315, H31         1390-65-4         FH8891000         215-724-4           1308-38-9         GB6475000         231-116-1         3567-66-6         NA         222-656-9           518-47-8	CAS No.         RTECS No.         EINECS No.         %           8003-22-3         NA         232-318-2         < 1.0	CAS No. RTECS No. EINECS No. 96 8003-22-3 NA 232-318-2 < 1.0 NA  NA NA NA   NA   S	CAS No.         RTECS No.         EINECS No.         %         ACGIH ppm           8003-22-3         NA         232-318-2         < 1.0	CAS NO.         RTECS NO.         EINECS NO.         %         ACIH   PPP         PPP           8003-22-3         NA         232-318-2         < 1.0	CAS NO.         RTECS NO.         EINECS NO.         %         CAGIH Depm North	CAS No.   RTECS No.   EINECS No.   W   MC   MCH   NOHSC   Ppm   Ppm	CAS No. RTECS No. BINECS No. BO03-22-3 NA 232-318-2 < 1.0 NA NA NA NF NF NF NF NA NA NA NA NF NF NF NA NA NA NA NA NA NF NF NF NA	CAS No.         RTECS No.         EINECS No.         %         AGGIH         NONSC         OSHA         OSHA           8003-22-3         NA         232-218-2         < 1.0	CAS NO.   RTEGS NO.   ENIECS NO.   SACIDI   COSHA   COSHA

### SAFETY DATA SHEET

Page 5 of 10 SDS-334

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 9/19/2014 4. FIRST AID MEASURES First Aid: Ingestion: If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water Eyes: for at least 15 minutes. If irritation occurs, contact a physician. If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough Skin: washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. Inhalation: Remove victim to fresh air at once. 4.2 Medical Conditions Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** 1 Aggravated by Exposure: target organs (eyes, skin, and respiratory system). **FLAMMABILITY** 3 PHYSICAL HAZARDS 0 В PROTECTIVE EQUIPMENT **EYES** SKIN 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR! Keep away from heat, lit cigarettes, 5.1 sparks & open flame. Keep container closed. 5.2 Extinguishing Methods: CO<sub>2</sub>, Halon (if permitted), Dry Chemical, Foam, as authorized. 5.3 Firefighting Procedures: This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. HazChem Code: 3(Y)E Hazard Identification Number: 33 6. ACCIDENTAL RELEASE MEASURES Spills: Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. 7.2 Storage & Handling: Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10). 7.3 Special Precautions: Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

9.10

9.11

9.12

9.13

9.14

9.15

Vapor Density:

Solubility:

Viscosity

Other Information:

Relative Density:

Partition Coefficient (log Pow):

Decomposition Temperature:

Autoignition Temperature:

ND

ND

ND

NA

ND

NA

Insoluble

1000 - 3000 cPs

### SAFETY DATA SHEET

Page 6 of 10 **SDS-334** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 9/19/2014 8. EXPOSURE CONTROLS & PERSONAL PROTECTION Ventilation & Engineering When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. 8.2 Respiratory Protection: No special respiratory protection is required under typical circumstances of use or handling. instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 8.3 Eye Protection: Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. 8.4 Hand Protection: AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.5 Body Protection: AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. However, no special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance: Viscous liquid, various colors Ester (fruity) odor 9.2 Odor: 9.3 Odor Threshold: ND 9.4 NA 9.5 Melting Point/Freezing Point: NA Initial Boiling Point/Boiling 9.6 NA 9.7 Flashpoint -4 °C (24.8 °F) estimated 9.8 Upper/Lower Flammability NA 9.9 Vapor Pressure NA

#### 10. STABILITY & REACTIVITY

10.1	Stability:	Stable under ambient conditions when stored properly (see Section 7, Storage and Handling).
10.2	Hazardous Decomposition Products:	If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO <sub>2</sub> ).
10.3	Hazardous Polymerization:	May occur, if exposed to extremely high temperatures.
10.4	Conditions to Avoid:	High temperatures, direct sunlight, sources of heat and incompatible materials.
10.5	Incompatible Substances:	This product is incompatible with strong oxidizers, (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), nitrates, or strong bases (e.g., lye, potassium hydroxide).

 $0.9 \cdot 1$ 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

### SAFETY DATA SHEET

SDS Revision: 1.1

Page 7 of 10 **SDS-334** 

SDS Revision Date: 9/19/2014

11. TOXICOLOGICAL INFORMATION Inhalation: YES Routes of Entry: 11.1 Ingestion: YES 11.2 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Ethyl Acetate:  $LD_{50}$  (oral, rat) = 5620 mg/kg;  $LD_{50}$  (oral, mouse) = 4100 mg/kg;  $LC_{50}$  (inh-6h, rat) = 16000 ppm 11.3 Acute Toxicity: See Section 2.4 11.4 Chronic Toxicity: See Section 2.5 This product contains <u>Ethyl Acetate</u>, and <u>Isopropyl Alcohol</u>, which are not carcinogenic to humans, but are listed as Group 3 carcinogens by the IARC. This product contains CI77266 (Carbon Black), as a California listed carcinogen 11.5 Suspected Carcinogen: (initial date 02/21/03, airborne, unbound particles of respirable size) and listed as an IARC Group 2B carcinogen. 11.6 Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. Irritancy of Product: 11.7 See Section 2.3 Biological Exposure Indices NE 11.9 Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. environmental data available for the components of this product are as follows: Ethyl Acetate:  $K_{OC} = 0.73$ . Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: Koc = 1.82. Water solubility: 120 parts H<sub>2</sub>O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log K<sub>OW</sub> = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated halflife in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. 12.2 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations. Special Considerations: 13.2 U.S. EPA Waste Number: D001 (characteristic - ignitable) 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) or CONSUMER COMMODITY, ORM-D - until 01/01/2021 14.2 IATA (AIR): ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) UN1263. PAINT. 3. II (IP VOL ≤ 1.0 L) IMDG (OCN): 14.3 UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) 14.4 TDGR (Canadian GND): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) ADR/RID (EU): 14.5 UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) 14.6 SCT (MEXICO): UN1263, PINTURA, 3, II, CANTIDAD LIMITADA (IP VOL ≤ 1.0 L) 14.7 ADGR (AUS): UN1263, PAINT, 3, II, LTD QTY (IP VOL  $\leq$  1.0 L) \* This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package)

# $\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$

# **SAFETY DATA SHEET**

Page 8 of 10 **SDS-334** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 9/19/2014

	45 DECULATORY INFORMATION						
	1	15. REGULATORY INFORMATION					
15.1	SARA Reporting Requirements:	This product contains <u>Isopropanol</u> , a substance subject to SARA Title III, section 313 reporting requirements. This product contains Ethyl Acetate, a substance that is subject to SARA Title III, section 304 reporting.					
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.					
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.					
15.4	CERCLA Reportable Quantity (RQ):	Ethyl Acetate: 2,270 kg (5,000 lbs); Butyl Acetate: 2,270 kg (5,000 lbs)					
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).					
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects)					
15.7	State Regulatory Information:	Butyl Acetate is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), New Jersey Right-to-Know List (NJ), New York List of Hazardous Substances (NY), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List for Air Contaminants (WA), Wisconsin Hazardous Substances List (WI).  Ethyl Acetate is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, and WA.  Isopropanol is found on the following state criteria lists: DE, MA, and PA.  Heptane is found on the following state criteria list: FL, MA, MN, PA and WA.  Camphor is found on the following state criteria list: FL, MA, MN, PA and WA.  No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).					
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC:  Ethyl Acetate: Flammable (F). Risk Phrases (R): 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system and skin. Safety Phrases (S): 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.  Butyl Acetate: Flammable (F). Risk Phrases (R): Flammable. Safety Phrases (S): 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.  Isopropanol: Flammable (F). Risk Phrases (R): 11-36/37 - Highly flammable. Irritating to eyes and respiratory system. Safety Phrases (S): 2-7-16-24/25/26 - Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.					

 $0.9 \cdot 1$ 

16.5

Prepared by:

**ShipMate, Inc.** P.O. Box 787

Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com

Sisters, Oregon 97759-0787 USA

### SAFETY DATA SHEET

Page 9 of 10 **SDS-334** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.1 SDS Revision Date: 9/19/2014 16. OTHER INFORMATION DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES 16 1 Other Information: MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE DROWSINESS OR SERIOUS EYE IRRITATION. DIZZINESS. Keep away from heat/sparks/open flame/hot surfaces - No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Avoid eye contact. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. Store in a well-ventilated place. Keep cool. Use only as directed. KEEP OUT OF REACH OF CHILDREN. Terms & Definitions 16.2 See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. 16.4 Prepared for: OPI Products, Inc. 13034 Saticov Street  $()\cdot P \cdot I$ No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 http://www.opi.com

### **SAFETY DATA SHEET**

Page 10 of 10 **SDS-334** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.1

SDS Revision Date: 9/19/2014

#### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### **GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number

#### **EXPOSURE LIMITS IN AIR:**

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

#### FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

#### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


#### **HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3	Severe Hazard		
4	Extreme Hazard		

**FLAMMABILITY** PHYSICAL HAZARDS PERSONAL PROTECTION

#### PERSONAL PROTECTION RATINGS:

Α			
В			
С		型	
D		型	
E			
F	T		





Splash Goggles



**Full Face Respirator** 















**Dust Respirator** 

#### OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition					
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

#### **HAZARD RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
ох	Oxidizer
TREFOIL	Radioactive



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>io</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TC <sub>o</sub> , LC <sub>io</sub> , & LC <sub>o</sub>	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

#### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

(	9	<b>③</b>	<b>(2)</b>		$\odot$	(4)		
CI	lass A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
	mpress ed	Flammabl e	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

#### EC (67/548/EEC) INFORMATION:

12		M	*			×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammabl e	Harmful	Oxidizing	Toxic	Irritant	Harmful

### CLP/GHS (1272/2008/EC) PICTOGRAMS:

		<b>®</b>	$\Diamond$			$\Diamond$	<b>***</b>	*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment