This form is regarded to be in compliance with 29 CFR Part 1910.1200

SECTION 1 : IDENTIFICATION

PRODUCT NAME: Cuccio Nail Solutions Matte Top Coat Product Use: Nail Top Coat Manufacturer's Name : Star Nail International, Inc. Address : 29120 Avenue Paine City, State, Zip : Valencia, CA 91355

Chemical Family : Proprietary Mix CAS# N/A

Preparation Date: January 02, 2020

24 HR. EMERGENCY TELEPHONE: CHEMTEL 1-813-248-0573

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225 Acute Tox. 4, H332 Eye Irrit. 2, H319 STOT SE 3, H336 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

aquatic environment: 26.7%

Ingredients of unknown
toxicity: Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 3.7%Ingredients of unknown
: Percentage of the mixture consisting of ingredient(s) of unknown hazards to the

Ingredients of unknown ecotoxicity

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Hazard pictograms : Signal word : Danger

SECTION 2: Hazards identification

Hazard statements	-	Highly flammable liquid and vapour. Harmful if inhaled. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.
Precautionary statements		
General	÷	Not applicable.
Prevention	:	Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Avoid release to the environment.
Response	:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
Storage	÷	Keep cool.
Disposal	1	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	1	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requireme	n	ts
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	1	Not applicable.
2.3 Other hazards		
Other hazards which do not result in classification	•	: None known.

[1] [2]

SECTION 3: Composition/information on ingredients

Substance/mixture	: Mixture				
Product/ingredient name	INCI Name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Туре
ethyl acetate	ETHYL ACETATE	EC: 205-500-4 CAS: 141-78-6 Index: 607-022-00-5	≥25 - <50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[1]
n-butyl acetate	BUTYL ACETATE	EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥10 - <15	Flam. Liq. 3, H226 Acute Tox. 2, H330 Eye Irrit. 2, H319 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066	[1]
isobutyl acetate	ISOBUTYL ACETATE	EC: 203-745-1	≥10 - <25	Flam. Liq. 2, H225	[1]
propyl acetate	PROPYL ACETATE	CAS: 110-19-0 Index: 607-026-00-7 EC: 203-686-1 CAS: 109-60-4 Index: 607-024-00-6	≥5 - <10	Eye Irrit. 2, H319 EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 Aquatic Chronic 3	5
		FO: 000 CC1 7	5 - 10	H412 EUH066	
propan-2-ol	ISOPROPYL ALCOHOL	EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0	≥5 - <10	Flam. Liq. 2, H228 Eye Irrit. 2, H319 STOT SE 3, H336	
Methyl ethyl ketone	МЕК	EC: 201-159-0 CAS: 78-93-3 Index: 606-002-00-3	≥5 - <10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	
		EC: 200-945-0 CAS: 76-22-2	≥1 - <3	Flam. Sol. 2, H228 Acute Tox. 4, H302 Acute Tox. 4, H332 STOT SE 2, H371 (central nervous system (CNS), kidneys and mucous membranes)	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health	effects
Eye contact	: Causes serious eye irritation.
Inhalation	: Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

4

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache dizziness/vertigo drowsiness/fatigue unconsciousness
Skin contact	: No specific data.
Ingestion	: No specific data.
4.3 Indication of any im	mediate medical attention and special treatment needed

Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures				
5.1 Extinguishing media				
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.			
Unsuitable extinguishing media	: Do not use water jet.			
5.2 Special hazards arising	from the substance or mixture			
Hazards from the substance or mixture	: Highly flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.			
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides			
5.3 Advice for firefighters				
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.			
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.			
	d in part on information provided by component suppliers and is believed to be correct as of the date			

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	r co	entainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections		See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest.
	Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid
	release to the environment. Use only with adequate ventilation. Wear appropriate
	respirator when ventilation is inadequate. Do not enter storage areas and confined
	spaces unless adequately ventilated. Keep in the original container or an approved
	alternative made from a compatible material, kept tightly closed when not in use.
	Store and use away from heat, sparks, open flame or any other ignition source. Use
	explosion-proof electrical (ventilating, lighting and material handling) equipment.
	Use only non-sparking tools. Take precautionary measures against electrostatic
	discharges. Empty containers retain product residue and can be hazardous. Do not
	reuse container.
accuracy at these data, the result	s to be obtained from the use of the material, or the bazards connected with such use. Since the intermation

accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Advice on general	: Eating, drinking and smoking should be prohibited in areas where this material is
occupational hygiene	handled, stored and processed. Workers should wash hands and face before
	eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional
	information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 13 to 26°C (55.4 to 78.8°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds (in tonnes)

<u> </u>		 	<u></u>	-
13	_	CLI	гаг	

• •	Notification and MAPP threshold	Safety report threshold
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b	5000	50000
C7b: Highly flammable (R11)	5000	50000

7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Methyl ethyl ketone	EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values TWA: 200 ppm 8 hours.
SECTION 8: Exposure of	ntrols/personal protection
procedures	is product contains ingredients with exposure limits, personal, workplace osphere or biological monitoring may be required to determine the effectiveness ne ventilation or other control measures and/or the necessity to use respiratory acctive equipment. Reference should be made to monitoring standards, such as following: European Standard EN 689 (Workplace atmospheres - Guidance for assessment of exposure by inhalation to chemical agents for comparison with a values and measurement strategy) European Standard EN 14042 (Workplace ospheres - Guide for the application and use of procedures for the assessment xposure to chemical and biological agents) European Standard EN 482 orkplace atmospheres - General requirements for the performance of procedures the measurement of chemical agents) Reference to national guidance uments for methods for the determination of hazardous substances will also be uired.
DNELs/DMELs No DNELs/DMELs available.	
PNECs	

No PNECs available

8.2 Exposure controls		
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection meas	ures	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

.

SECTION 9: Physical and chemical properties

9.1 Information on basic physic	al and chemical properties
Appearance	
Physical state	: Liquid. [Clear to slightly hazy liquid. Viscous liquid.]
Colour	: Not available.
Odour	: Fruity. Ester. [Strong]
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: 77°C
Flash point	: Closed cup: 20°C [Tagliabue.]
Upper/lower flammability or explosive limits	: Lower: 0.04%
Vapour pressure	: Not available.
Vapour density	: 1 [Air = 1]
Relative density	: 0.97
Solubility(ies)	: Insoluble in the following materials: cold water and hot water.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity		
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Product/ingredient name	Result	Species	Dose	Exposure
ethyl acetate	LD50 Oral	Rat	5620 mg/kg	-
n-butyl acetate	LC50 Inhalation Gas.	Rat	390 ppm	4 hours
-	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
isobutyl acetate	LD50 Dermal	Rabbit	>17400 mg/kg	-
-	LD50 Oral	Rat	13400 mg/kg	-
propyl acetate	LD50 Oral	Rat	9370 mg/kg	-
propan-2-ol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
Methyl ethyl ketone	LD50 Dermal	Rabbit	6480 mg/kg	-
	LD50 Oral	Rat	2737 mg/kg	-

Acute toxicity estimates

Route	ATE value
Oral	49522.5 mg/kg
Inhalation (gases)	3001.4 ppm
Inhalation (dusts and mists)	148.6 mg/l

Irritation/Corrosion

Date: January 02, 2020

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-butyl acetate	Eyes - Moderate irritant	Rabbit	-	100	-
				milligrams	
	Skin - Moderate irritant	Rabbit	-	24 hours 500	-
				milligrams	
isobutyl acetate	Eyes - Moderate irritant	Rabbit	-	24 hours 500	-
		Datati		milligrams	
	Skin - Mild irritant	Rabbit	-	500	-
	Okin Mederate irritent	Dabbit		milligrams	
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
propyl acetate	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
propyracelate	Lyes - wiid initant	Rabbit	-	milligrams	-
	Skin - Mild irritant	Rabbit	-	500	-
		, abbit		milligrams	
propan-2-ol	Eyes - Moderate irritant	Rabbit	-	10 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100	-
				milligrams	
	Skin - Mild irritant	Rabbit	-	500	-
				milligrams	
	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
		Detail		milligrams	
Methyl ethyl ketone	Skin - Mild irritant	Rabbit	-	24 hours 14	-
	Okin Madarata irritant	Dabbit		milligrams	
	Skin - Moderate irritant	Rabbit	-	24 hours 500	-
				milligrams	

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethyl acetate n-butyl acetate propyl acetate propan-2-ol Methyl ethyl ketone	Category 3 Category 3 Category 3 Category 3 Category 3 Category 2	Not applicable. Not applicable. Not applicable. Not applicable. Not applicable. Not determined	Narcotic effects Narcotic effects Narcotic effects Narcotic effects Narcotic effects central nervous system (CNS), kidneys and mucous membranes

Information on the likely routes of exposure	Not available.	
Potential acute health effects		
Eye contact	Causes serious eye irritation.	
Inhalation	Harmful if inhaled. Can cause central nervous system (CNS) depression. cause drowsiness or dizziness.	Мау
Skin contact	No known significant effects or critical hazards.	
Ingestion	Can cause central nervous system (CNS) depression.	

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache dizziness/vertigo drowsiness/fatigue unconsciousness
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Other information

: Not available.

Date: January 02, 2020

Product/ingredient name	Result	Species	Exposure
ethyl acetate	Acute EC50 2500000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute LC50 750000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 154000 µg/l Fresh water	Daphnia - Daphnia cucullata	48 hours
	Acute LC50 212500 µg/l Fresh water	Fish - Heteropneustes fossilis	96 hours
	Chronic NOEC 2400 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 75.6 mg/l Fresh water	Fish - Pimephales promelas -	32 days
		Embryo	-
n-butyl acetate	Acute LC50 32000 µg/I Marine water	Crustaceans - Artemia salina -	48 hours
-		Nauplii	
	Acute LC50 18000 µg/I Fresh water	Fish - Pimephales promelas	96 hours
propyl acetate	Acute LC50 60000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
propan-2-ol	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours
Methyl ethyl ketone	Acute EC50 >500000 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 5091000 µg/l Fresh water	Daphnia - Daphnia magna -	48 hours
		Larvae	
	Acute LC50 3220000 µg/l Fresh water	Fish - Pimephales promelas	96 hours

SECTION 12: Ecological information

12.1 Toxicity

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods			
Product			
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.		
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.		
Packaging			
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	UN1993	UN1993	UN1993	UN1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (ethyl acetate, n-butyl acetate)	FLAMMABLE LIQUID, N.O.S. (ethyl acetate, n-butyl acetate)	FLAMMABLE LIQUID, N.O.S. (ethyl acetate, n-butyl acetate)	FLAMMABLE LIQUID, N.O.S. (ethyl acetate, n-butyl acetate)
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	Ш	Ш	Ш	II
14.5 Environmental hazards	No.	Yes.	No.	No.
Additional information	Special provisions 640 (C) <u>Tunnel code</u> (D/E)	The product is only regulated as an environmentally hazardous substance when transported in tank vessels.	-	-

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not available.according to Annex II ofMARPOL 73/78 and the IBCCode

SECTION 15: Regulatory information

	lations/legislation specific for the substance or mixture
J Regulation (EC) No. 1907/2006 (REACH	—
Annex XIV - List of substances subject to	<u>o authorisation</u>
Annex XIV	
None of the components are listed.	
Substances of very high concern	
None of the components are listed.	
Annex XVII - Restrictions : Not applic	cable.
on the manufacture,	
placing on the market and use of certain	
dangerous substances,	
mixtures and articles	
Other EU regulations	
Europe inventory : Not deter	mined
Seveso Directive	inited.
This product is controlled under the Seves	so Directive
Danger criteria	
<u></u>	
Category	
P5c: Flammable liquids 2 and 3 not falling	ng under P5a or P5b
C7b: Highly flammable (R11)	

15.2 Chemical Safety Assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.		
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative 	

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225	On basis of test data
Acute Tox. 4, H332	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H : statements	H225 H226	Highly flammable liquid and vapour.
statements		Flammable liquid and vapour.
	H228	Flammable solid.
	H302	Harmful if swallowed.
	(oral)	
	H319	Causes serious eye irritation.
	H330	Fatal if inhaled.
	(inhalation)	
	H332	Harmful if inhaled.
	(inhalation)	
	H336	May cause drowsiness or dizziness.
	H371	May cause damage to organs. (central nervous system (CNS), kidneys
	(central	and mucous membranes)
	nervous	,
	system	
	(CNS),	
	kidneys	
	and	
	mucous	
	membranes)	

	H412 Harmful to aquatic life with long lasting effects.
Full text of classifications	: Acute Tox. 2, H330 ACUTE TOXICITY (inhalation) - Category 2
[CLP/GHS]	Acute Tox. 4, H302 ACUTE TOXICITY (oral) - Category 4
	Acute Tox. 4, H332 ACUTE TOXICITY (inhalation) - Category 4
	Aquatic Chronic 3, H412 LONG-TERM AQUATIC HAZARD - Category 3
	EUH066 Repeated exposure may cause skin dryness or cracking.
	Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
	Flam. Liq. 2, H225 FLAMMABLE LIQUIDS - Category 2
	Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3
	Flam. Sol. 2, H228 FLAMMABLE SOLIDS - Category 2
	STOT SE 2, H371 SPECIFIC TARGET ORGAN TOXICITY (SINGLE
	(central nervous system EXPOSURE) (central nervous system (CNS), kidneys
	(CNS), kidneys and and mucous membranes) - Category 2 mucous membranes)
	STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE
	EXPOSURE) (Narcotic effects) - Category 3
Date of printing	: 12/3/2015
Date of issue/ Date of	: 12/3/2015
revision	
Date of previous issue	: No previous validation
Version	: 1

DISCLAIMER: This SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design and the appropriate protective mechanisms to prevent employee exposure, property damage or release to the environment. Star Nail International assumes no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

END OF SDS