Star NailSAFETY DATA SHEETPRODUCT NAME: Cuccio Pro Powder Polish Dip System Step 8 Dipping Powder Remover

This form is regarded to be in compliance with 29 CFR Part 1910.1200

SECTION 1 : IDENTIFICATION

PRODUCT NAME: Cuccio Pro Powder Polish Dip System Step 8 Dipping Powder RemoverProduct Use: SolventManufacturer's Name :Star nail International, Inc.Address :29120 Avenue PaineCity, State, Zip :Valencia, CA 91355

Preparation Date: February 05, 2021

24 HR. EMERGENCY TELEPHONE: CHEMTEL 1-813-248-0573

SECTION 2: Hazardous Identification

ACETONE:

Classification:

Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3

Aspiration Hazard - Category 2

Skin Irritation - Category 3

Eye Irritation - Category 2A

Flammable Liquids Category 1

Acute toxicity Oral Category 5

Pictograms:



HAZARD STATEMENTS

H225 Highly Flammable H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness

Date: February 05, 2021

PRECAUTIONARY STATEMENT(S)

Prevention:

P271: Use only outdoors or in a well-ventilated area.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P270: Do no eat, drink or smoke when using this product.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P264 Wash skin thoroughly after handling.

Response:

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330: Rinse mouth.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P311: Call a POISON CENTER or doctor/physician.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

Disposal:

7944L501: Dispose of in a manner consistent with federal, state, and local regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Transparent blue colored liquid with mild odor.

IMMEDIATE CONCERNS: Irritating to eyes and respiratory system.

POTENTIAL HEALTH EFFECTS

EYES: Contact may cause eye irritation.

INGESTION: Substance may be harmful if swallowed.

INHALATION: Inhalation may cause headache, nausea, vomiting, and narcosis.

Precautionary Statements - Disposal:

Dispose of contents/container to disposal recycling center. Waste management should be in full compliance with federal, state and local laws.

NITROETHANE

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Oral), Category 4 Acute Toxicity (Inhalation), Category 4

Physical:

Flammable Liquids, Category 3

GHS LABEL ELEMENTS



SIGNAL WORD: Danger

HAZARD STATEMENTS

H302: Harmful if swallowed.H332: Harmful if inhaled.H226: Flammable liquid and vapour.

Hazardous Statements - Physical:

Extremely flammable liquid and vapor

Hazardous Statements - Health:

May cause drowsiness or dizziness

Maybe harmful if swallowed

May be harmful if swallowed and enters airways

Causes mild skin irritation

Causes serious eye irritation

Precautionary Statements - General:

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

s of the date

accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

PRECAUTIONARY STATEMENT(S)

Prevention:

P271: Use only outdoors or in a well-ventilated area.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P270: Do no eat, drink or smoke when using this product.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P264 Wash skin thoroughly after handling.

Response:

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330: Rinse mouth.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P311: Call a POISON CENTER or doctor/physician.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

Disposal:

7944L501: Dispose of in a manner consistent with federal, state, and local regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Transparent blue colored liquid with mild odor.

IMMEDIATE CONCERNS: Irritating to eyes and respiratory system.

POTENTIAL HEALTH EFFECTS

EYES: Contact may cause eye irritation.

INGESTION: Substance may be harmful if swallowed.

INHALATION: Inhalation may cause headache, nausea, vomiting, and narcosis.

Date: February 05, 2021

Precautionary Statements - Disposal:

Dispose of contents/container to disposal recycling center. Waste management should be in full compliance with federal, state and local laws.

SECTION 3: Composition/Information on Ingredients					
Chemical Name	% by Weight	CAS #.			
ACETONE	60-75%	67-64-1			
NITROETHANE	25-40%	79-24-3			

SECTION 4 : First Aid Measures

Inhalation:

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If victim is not breathing, call 911 and administer CPR as directed.

Eliminate all ignition sources if safe to do so.

Skin Contact:

Rinse/wash with lukewarm, gently flowing water (and mild soap) for 15-20 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

Eye Contact:

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. Take care not to rinse contaminated water into the unaffected eye or onto the face. Get immidiate medical attention.

Ingestion:

Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Immediately call 911 POISON CENTER/doctor/. Immediately transport to the nearest medical facility for treatment.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: May be mildly irritating to eyes.

INHALATION: Signs and symptoms of excessive exposure may be central nervous system effects such as

sleepiness and

unconsciousness.

CHRONIC EFFECTS: Prolonged or repeated overexposure may cause central nervous system, kidney, liver,

and lung

damage.

SECTION 5: Fire Fighting Measures

Suitable Extinguishing Media:

Dry chemical, foam, carbon dioxide or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destrovs the foam. Sand or earth may be used for small fires only.

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions:

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Additional Fire Fighting Measures:

HAZARDOUS COMBUSTION PRODUCTS: Combustion products may include and are not limited to: Carbon monoxide, Carbon dioxide and Nitrogen oxides.

EXPLOSION HAZARDS: Containers may rupture violently under fire temperatures. Cool containers with water if exposed to fire conditions.

FIRE FIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH

approved or equivalent) and full protective gear.

SENSITIVE TO STATIC DISCHARGE: Electrostatic charges may be generated during pumping. Ground all containers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition.

SECTION 6 : Accidental Release Measures

Emergency Procedure:

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

RELEASE CAN CAUSE FIRE/EXPLOSION. LIQUIDS/VAPORS MAY IGNITE.

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment:

Positive pressure, full-facepiece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions:

Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Use explosive proof equipment. Avoid inhalation of dust and contact with skin and eyes. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions:

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up:

Sand, clay and absorbent socks can be used to contain a spill.

Additional Accidental Release Measures:

SMALL SPILL: Remove all sources of ignition. Use spark-proof tools. Contain spilled liquid with sand or earth. DO NOT use

combustible materials such as sawdust. Absorb liquid and place in sealed container for disposal. Vapors can travel to an ignition

source.

LARGE SPILL: Wear self-contained breathing equipment and protective clothing/glasses/apron/boots, disposing into DOT

approved waste containers, which should have air space above the product. Keep out of sewers/drains/surface water and soil.

Date: February 05, 2021

Residues require similar disposal.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

GENERAL PROCEDURES: -Implement cleanup procedures.

-If in public area, keep public away and advise authorities.

-Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent.

SECTION 7 : Handling and Storage

General:

Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements:

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements:

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Ground and bond containers and receiving equipment. Avoid static electricity by grounding.

Electrostatic charges may be generated during pumping. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products.

Additional Handling and Storage:

HANDLING: Avoid direct contact with eyes and prolonged contact with skin. Wash hands with soap and water after use.

STORAGE: Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition.

STORAGE TEMPERATURE: Ambient room temperature (70F/21C).

LOADING TEMPERATURE: No data available on this product.

STORAGE PRESSURE: No data available on this product.

ELECTROSTATIC ACCUMULATION HAZARD: See Section 5 regarding electrostatic charges.

SECTION 8 : Exposure Controls/ Personal Protection

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Select a filter suitable for organic gases and vapors <booling point,65 °C 149 °F)> meeting EN371.

Skin Protection:

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over- boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder solled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Eye Protection:

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Appropriate Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA- Tables- Z1,2,3	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
ACETONE	1000	2400			1			250	590			

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
ACETONE	500	1188	750	1782	A4	A4; BEI	URT & eye irr; CNS impair; hematologi c eff

Star Nail SAFETY DATA SHEET PRODUCT NAME: Cuccio Pro Powder Polish Dip System Step 8 Dipping Powder Remover Date: February 05, 2021

Component	CAS-No.	Value	Control parameters	Basis				
Nitroethane	79-24-3	TWA	100.000000 ppm 310.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants				
	Remarks	The value	in mg/m3 is approx	ximate.				
		TWA	100.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)				
		Central Ne	rvous System imp	airment				
		Upper Res	Upper Respiratory Tract irritation					
		Liver dama	Liver damage					
		TWA	100 ppm	USA. ACGIH Threshold Limit Values (TLV)				
		Central Ne	rvous System imp	airment				
			piratory Tract irrita					
		Liver dama						
		TWA	100.000000 ppm 310.000000 mg/m3	USA. NIOSH Recommended Exposure Limits				
		PEL	100 ppm 310 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)				

SECTION 9 : Physical and Chemical Properties

ACETONE:

Physical and Chemical Properties

Density	6.61 lb/gal
% Solids By Weight	0.00%
Density VOC	0.00 lb/gal
% VOC	0.00%
VOC Actual	0.00 lb/gal
Specific Gravity	0.79

Appearance	Clear liquid
Odor Threshold	N/A
Odor Description	Chacteristic
pH	N/A
Water Solubility	N/A
Flammability	Flashpoint below 73 °F
Flash Point Symbol	N/A
Flash Point	-40 °F
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N/A
Decomposition Pt	0
Evaporation Rate	N/A
Coefficient Water/Oil	N/A
VOC Composite Partial Pressure	0.00279882 mmHg (Calculated @ 20 C/68 F)

NITROETHANE

PHYSICAL STATE: Liquid ODOR: Mild odor. APPEARANCE: Blue liquid. pH: 6 Notes: 0.01M aqueous solution (from literature) FLASHPOINT AND METHOD: 30 °C (87 °F) TCC FLAMMABLE LIMITS: 3.4% (V), 30C to N/A AUTOIGNITION TEMPERATURE: 414 °C (777 °F) VAPOR PRESSURE: 15.6 mmHg at 20 °C VAPOR DENSITY: 2.6 (Air=1) BOILING POINT: 114 °C (237 °F) FREEZING POINT: No data available on this product. MELTING POINT: No data available on this product. POUR POINT: No data available on this product. THERMAL DECOMPOSITION: No data available on this product. SOLUBILITY IN WATER: 4.5 % at 20 °C Notes: Based on literature. EVAPORATION RATE: 1.2 (n-Butyl Acetate=1) SPECIFIC GRAVITY: 1.05 (water=1) VISCOSITY: Not Available (VOC): 1050.000 g/L

SECTION 10 : Stability and Reactivity

Stability:

Stable under normal conditions of use.

Conditions to Avoid:

Avoid heat, sparks, open flames and other ignition sources.

Hazardous Reactions/Polymerization:

No data available.

Incompatible Materials:

Strong oxidizing agents.

Hazardous Decomposition Products:

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

ACETONE:

NITROETHANE:

STABILITY: Unstable at elevated temperatures and pressures.

POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Avoid temperatures exceeding 100F/38C and incompatible materials.

POSSIBILITY OF HAZARDOUS REACTIONS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition.

HAZARDOUS DECOMPOSITION PRODUCTS: Decomposition products can include and are not limited to: Ethylene, Nitrogen oxides.

INCOMPATIBLE MATERIALS: Avoid contact with amines, strong acids, strong oxidizing agents, heavy metal oxides, aldehydes

and reducing agents.

COMMENTS: REACTIVITY: No dangerous reaction known under conditions of normal use.

SECTION 11: Toxicological Information

ACETONE:

Acute toxicity:

Ingestion: May be harmful or fatal if swallowed.

Skin Corrosion/Irritation:

Causes mild skin irritation

Serious eye damage/irritation:

Causes serious eye irritation

Germ cell mutagenicity:

No data available

Respiratory/Skin Sensitization:

Slightly irritating to respiratory system.

Carcinogenicity:

No data available

Reproductive toxicity:

No data available

Specific Target Organ Toxicity - Repeated Exposure:

No data available

Specific Target Organ Toxicity - Single Exposure:

May cause drowsiness or dizziness

Aspiration hazard:

May be harmful if swallowed and enters airways

0000067-64-1 ACETONE

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m3 (4-hour exposure) (29) LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m3 (4-hour exposure) (29)

LD50 (oral, female rat): 5800 mg/kg (24)

LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31)

LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)

LD50 (oral, mouse): 3000 mg/kg (32, unconfirmed)

LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg) (30)

Potential Health Effects - Miscellaneous

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

NITROETHANE:

ACUTE

DERMAL LD₅₀: > 2000 mg/kg (rabbit)

ORAL LD₅₀: 1100 mg/kg (rat)

INHALATION LC₅₀: > 6.754 mg/L (6 hr) rat

NOTES: Inhalation may cause headache, nausea, vomiting, and narcosis.

EYE EFFECTS: Irritating to eyes.

SKIN EFFECTS: Irritating to skin.

CHRONIC: Overexposure may cause kidney and liver damage.

CARCINOGENICITY

IARC: None known.

NTP: None known.

OSHA: None known.

REPEATED DOSE EFFECTS: May cause methemoglobinemia, thereby impairing the blood's ability to transport oxygen. In animals, effects have been reported on the following organs: spleen, kidney, liver, nasal tissue.

IRRITATION: Slightly irritating to eyes and skin.

CORROSIVITY: None known.

SENSITIZATION: None known.

NEUROTOXICITY: None known.

GENETIC EFFECTS: None known.

REPRODUCTIVE EFFECTS: None known.

MUTAGENICITY: None known.

SECTION 12: Ecological Information

Bio-accumulative Potential:

No data available.

Persistence and Degradability:

No data available.

Mobility in Soil:

No data available.

Toxicity:

No data available

Other adverse effects:

No data available.

Bio-accumulative Potential

0000067-64-1 ACETONE

Does not bioaccumulate

Persistence and Degradability

0000067-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

ACETONE:

NITROETHANE:

ENVIRONMENTAL DATA: None known.

ECOTOXICOLOGICAL INFORMATION: None known.

BIOACCUMULATION/ACCUMULATION: None known.

AQUATIC TOXICITY (ACUTE): None known.

GENERAL COMMENTS: Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

SECTION 13: Disposal Considerations

·

Waste Disposal Method:

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14: Transport Information

ACETONE:

U.S. DOT Information:

UN1090, Acetone, 3, PG II

Emergency Response Guide (ERG):

Emergency Response Guide 127

NITROETHANE:

Star Nail

SAFETY DATA SHEET

PRODUCT NAME: Cuccio Pro Powder Polish Dip System Step 8 Dipping Powder Remover

DOT (DEPARTMENT OF TRANSPORTATION) PROPER SHIPPING NAME: NITROETHANE, LTD QTY PRIMARY HAZARD CLASS/DIVISION: 3 UN/NA NUMBER: 2842 PACKING GROUP: III PLACARDS: FLAMMABLE LIQUID AIR (ICAO/IATA) SHIPPING NAME: NITROETHANE UN/NA NUMBER: 2842 **PRIMARY HAZARD CLASS/DIVISION: 3** PACKING GROUP: III PLACARDS: FLAMMABLE LIQUID VESSEL (IMO/IMDG) SHIPPING NAME: NITROETHANE UN/NA NUMBER: 2842 PRIMARY HAZARD CLASS/DIVISION: 3 PACKING GROUP: III EmS: F-E, S-D PLACARDS: FLAMMABLE LIQUID

SECTION 15: Regulatory Information

CAS	Chemical Name	% By Weight	Regulation List
0000067-64-1	ACETONE	98.000% - 100.000%	CERCLA,SARA312,VOC_exempt,TSCA,RCRA,OSHA

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Immediate (acute) and/or delayed (chronic) health and fire hazards

FIRE: Yes PRESSURE GENERATING: No REACTIVITY: No ACUTE: Yes CHRONIC: Yes

313 REPORTABLE INGREDIENTS: None known.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: None known.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
NITROETHANE	79-24-3

TSCA STATUS: All ingredients in this mixture are in compliance with TSCA.

CLEAN AIR ACT

40 CFR PART 68--RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION: None known.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119--PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None known.

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



WHMIS CLASS: Class B2 - Flammable Liquid, Class D2B - Toxic (Irritant)

DOMESTIC SUBSTANCE LIST (INVENTORY): All components are listed on or are exempt from listing on the Domestic Substances List.

SECTION 16: ADDITIONAL REGULATORY INFORMATION

ACETONE:


16.2 HMIS


HEALTH	2
FLAMMABIL	ITY 3
PHYSICAL H	AZARD 0

HMIS Rating: Health: 2 (Moderate) Flammability: 3 (Serious) Physical Hazard: 0 (Minimum)

NITROETHANE:







DISCLAIMER: This SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design and the appropriate protective mechanisms to prevent employee exposure, property damage or release to the environment. All Season Professional assumes no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

END OF SDS