




## 4. FIRST AID MEASURES

4.1	First Aid:	<p><b>Ingestion:</b> If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p><b>Eyes:</b> Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.</p> <p><b>Skin:</b> If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.</p> <p><b>Inhalation:</b> Remove victim to fresh air at once.</p>															
4.2	Effects of Exposure:	<p><b>Ingestion:</b> If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.</p> <p><b>Eyes:</b> Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><b>Skin:</b> May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact.</p> <p><b>Inhalation:</b> Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 3 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).</p>															
4.3	Symptoms of Overexposure:	Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering.															
4.4	Acute Health Effects:	Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.															
4.5	Chronic Health Effects:	None known.															
4.6	Target Organs:	Eyes, Skin, Respiratory System.															
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system).															
		<table border="1"> <tr> <td colspan="2"><b>HEALTH</b></td> <td><b>1</b></td> </tr> <tr> <td colspan="2"><b>FLAMMABILITY</b></td> <td><b>3</b></td> </tr> <tr> <td colspan="2"><b>PHYSICAL HAZARDS</b></td> <td><b>0</b></td> </tr> <tr> <td colspan="2"><b>PROTECTIVE EQUIPMENT</b></td> <td><b>B</b></td> </tr> <tr> <td><b>EYES</b></td> <td><b>SKIN</b></td> <td></td> </tr> </table>	<b>HEALTH</b>		<b>1</b>	<b>FLAMMABILITY</b>		<b>3</b>	<b>PHYSICAL HAZARDS</b>		<b>0</b>	<b>PROTECTIVE EQUIPMENT</b>		<b>B</b>	<b>EYES</b>	<b>SKIN</b>	
<b>HEALTH</b>		<b>1</b>															
<b>FLAMMABILITY</b>		<b>3</b>															
<b>PHYSICAL HAZARDS</b>		<b>0</b>															
<b>PROTECTIVE EQUIPMENT</b>		<b>B</b>															
<b>EYES</b>	<b>SKIN</b>																

## 5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	<b>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR!</b> Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed.	
5.2	Extinguishing Methods:	CO <sub>2</sub> , Halon (if permitted), Dry Chemical, Foam, as authorized.	
5.3	Firefighting Procedures:	<p>This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.</p> <p>First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.</p> <p>HazChem Code: 3(Y)E Hazard Identification Number: 33</p>	

## 6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <u>small spills</u> (e.g., &lt; 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.</p>
-----	---------	---

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 10/6/2016

## 7. HANDLING &amp; STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.
7.2	Storage & Handling:	Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10).
7.3	Special Precautions:	Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

## 8. EXPOSURE CONTROLS &amp; PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m <sup>3</sup> )	ACGIH		NOHSC			OSHA			OTHER
		TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
	CHEMICAL NAME(S)									
	ETHYL ACETATE	400	400	200	400	NF	NA	NA	2000	400 TWA
	BUTYL ACETATE	150	200	150	200	NF	200	200	1700	100 NIOSH
	TOSYLAMIDE/ EPOXY RESIN	(10)	NE	NF	NF	NF	(10)	NE	NE	
	SILICA	NA	NA	NF	NF	NF	NA	NA	3000	RESP FRAC
	BUTYL ALCOHOL	NA	50	50	152	50	100	NA	1400	
8.2	Ventilation & Engineering Controls:	When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.								
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.								
8.4	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.								
8.5	Hand Protection:	AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.								
8.6	Body Protection:	AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. However, no special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.								

## 9. PHYSICAL &amp; CHEMICAL PROPERTIES

9.1	Appearance:	Viscous liquid
9.2	Odor:	Ester (fruity) odor
9.3	Odor Threshold:	ND
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	NA
9.7	Flashpoint:	- 4 °C (24.8 °F) estimated
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	ND
9.11	Relative Density:	ND
9.12	Solubility:	Insoluble
9.13	Partition Coefficient (log P <sub>ow</sub> ):	ND
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	ND
9.16	Viscosity:	1,000 – 3,000 cPs
9.17	Other Information:	NA

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 10/6/2016

**10. STABILITY & REACTIVITY**

10.1	Stability:	Stable under ambient conditions when stored properly (See Section 7, Storage and Handling).
10.2	Hazardous Decomposition Products:	If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO <sub>2</sub> ).
10.3	Hazardous Polymerization:	May occur, if exposed to extremely high temperatures.
10.4	Conditions to Avoid:	High temperatures, direct sunlight, sources of heat and incompatible materials.
10.5	Incompatible Substances:	This product is incompatible with strong oxidizers, (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), nitrates, or strong bases (e.g., lye, potassium hydroxide).

**11. TOXICOLOGICAL INFORMATION**

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document. Ethyl Acetate: LD <sub>50</sub> (oral, rat) = 11,300 mg/kg; Butyl Acetate: LD <sub>50</sub> (oral, rat) = 11,400 mg/kg		
11.3	Acute Toxicity:	See Section 4.4		
11.4	Chronic Toxicity:	See Section 4.5		
11.5	Suspected Carcinogen:	This product contains Ethyl Acetate and Silica, which are not carcinogenic to humans, but are listed as Group 3 carcinogens by the IARC.		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 4.3		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

**12. ECOLOGICAL INFORMATION**

12.1	Environmental Stability:	The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate: K <sub>OC</sub> = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: K <sub>OC</sub> = 1.82. Water solubility: 120 parts H <sub>2</sub> O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

**13. DISPOSAL CONSIDERATIONS**

13.1	Waste Disposal:	Waste disposal must be in accordance with appropriate Federal, state, and local regulations.
13.2	Special Considerations:	U.S. EPA Waste Number: D001 (characteristic - ignitable)

**14. TRANSPORTATION INFORMATION**

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 1.0 L) or CONSUMER COMMODITY, ORM-D – until 01/01/2021	
14.2	IATA (AIR):	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) UN1263, PAINT RELATED MATERIAL, 3, II (LTD QTY, IP ≤ 0.5 L)	
14.3	IMDG (OCN):	EXCEPTED QUANTITY (2008 IMO § 3.5.1) (≤ 30 ml) UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)	
14.5	ADR/RID (EU):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1263, PRODUCTOS PARA PINTURA, 3, II, (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)	



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0



SDS Revision Date: 10/6/2016

## 14. TRANSPORTATION INFORMATION


The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.7	ADGR (AUS):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)	
14.8	EXCEPTED QUANTITIES: *	THIS PRODUCT MAY BE SHIPPED AS AN EXCEPTED QUANTITY IP VOL ≤ 30 mL; TOTAL VOL PER PKG ≤ 1000 mL	

## 15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product contains <u>Ethyl Acetate</u> , a substance that is subject to SARA Title III, Section 304 reporting.
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.
15.4	CERCLA Reportable Quantity (RQ):	<u>Ethyl Acetate</u> : 2,270 kg (5,000 lbs); <u>Butyl Acetate</u> : 2,270 kg (5,000 lbs)
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects)  
15.7	State Regulatory Information:	<u>Ethyl Acetate</u> is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), New Jersey Right-to-Know List (NJ), New York List of Hazardous Substances (NY), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List for Air Contaminants (WA), Wisconsin Hazardous Substances List (WI). <u>Butyl Acetate</u> is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, and WA. <u>Silica</u> is found on the following state criteria list: MA, MN, and PA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).
15.8	Other Requirements:	NA

## 16. OTHER INFORMATION

16.1	Other Information:	<b>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.</b> Use as directed. Discontinue use if irritation develops. Keep away from heat/sparks/open flame/hot surfaces – No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Wash exposed skin areas thoroughly with soap and water after handling. Avoid eye contact. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs – Get medical advice/attention. Store in a well-ventilated place. Keep cool. Use only as directed. <b>KEEP OUT OF REACH OF CHILDREN.</b>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 <a href="http://www.opi.com">http://www.opi.com</a>	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 <a href="http://www.shipmate.com">http://www.shipmate.com</a>	

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 10/6/2016

## DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

### GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

### EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

### FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

### HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

<b>HEALTH</b>
<b>FLAMMABILITY</b>
<b>PHYSICAL HAZARDS</b>
<b>PERSONAL PROTECTION</b>

### PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	

G	
H	
I	
J	
K	
X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

### OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

### FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

### HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animals
ppm	Concentration expressed in parts of material per million parts
TD <sub>01</sub>	Lowest dose to cause a symptom
TCLO	Lowest concentration to cause a symptom
TD <sub>01</sub> , LD <sub>01</sub> , & LD <sub>01</sub> or TC, TC <sub>01</sub> , LC <sub>01</sub> , & LC <sub>01</sub>	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log K <sub>OW</sub> or log K <sub>OC</sub>	Coefficient of Oil/Water Distribution

### REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

### EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

### CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards


SDS Revision: 1.0

SDS Revision Date: 10/6/2016

## 4. FIRST AID MEASURES

4.1	First Aid:	<p><b>Ingestion:</b> If ingested, do not induce vomiting. Drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer plenty of water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time and amount of the substance that was swallowed.</p> <p><b>Eyes:</b> If product is in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. If problem persists, consult a physician.</p> <p><b>Skin:</b> If redness, dryness or other signs of irritation to the skin develop, wash affected skin areas with plenty of warm water and soap. If irritation persists, consult a physician.</p> <p><b>Inhalation:</b> Remove victim to fresh air at once.</p>															
4.2	Effects of Exposure:	<p><b>Ingestion:</b> If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.</p> <p><b>Eyes:</b> Irritating to eyes. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><b>Skin:</b> May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact.</p> <p><b>Inhalation:</b> Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 3 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).</p>															
4.3	Symptoms of Overexposure:	Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering.															
4.4	Acute Health Effects:	Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.															
4.5	Chronic Health Effects:	No chronic health effects are known, although symptoms and discomfort may occur for several days following overexposure.															
4.6	Target Organs:	Eyes, Skin, Respiratory System.															
4.7	Medical Conditions Aggravated by Exposure:	None known.															
		<table border="1"> <tr> <td colspan="2"><b>HEALTH</b></td> <td><b>1</b></td> </tr> <tr> <td colspan="2"><b>FLAMMABILITY</b></td> <td><b>3</b></td> </tr> <tr> <td colspan="2"><b>PHYSICAL HAZARDS</b></td> <td><b>0</b></td> </tr> <tr> <td colspan="2"><b>PROTECTIVE EQUIPMENT</b></td> <td><b>B</b></td> </tr> <tr> <td><b>EYES</b></td> <td><b>SKIN</b></td> <td></td> </tr> </table>	<b>HEALTH</b>		<b>1</b>	<b>FLAMMABILITY</b>		<b>3</b>	<b>PHYSICAL HAZARDS</b>		<b>0</b>	<b>PROTECTIVE EQUIPMENT</b>		<b>B</b>	<b>EYES</b>	<b>SKIN</b>	
<b>HEALTH</b>		<b>1</b>															
<b>FLAMMABILITY</b>		<b>3</b>															
<b>PHYSICAL HAZARDS</b>		<b>0</b>															
<b>PROTECTIVE EQUIPMENT</b>		<b>B</b>															
<b>EYES</b>	<b>SKIN</b>																

## 5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	<b>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR!</b> Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed.	
5.2	Extinguishing Methods:	CO <sub>2</sub> , Halon (if permitted), Dry Chemical, Foam, as authorized.	
5.3	Firefighting Procedures:	This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.	

## 6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <u>small spills</u> (e.g., &lt; 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.</p>
-----	---------	---

## 7. HANDLING &amp; STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.
7.2	Storage & Handling:	Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10).
7.3	Special Precautions:	Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.





Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 10/6/2016

## 8. EXPOSURE CONTROLS &amp; PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m <sup>3</sup> )	CHEMICAL NAME(S)	ACGIH		NOHSC			OSHA			OTHER
			TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ETHYL ACETATE	400	400	200	400	NF	NA	NA	2000	400 TWA
		BUTYL ACETATE	150	200	150	200	NF	200	200	1700	150 TWA
		ISOPROPYL ALCOHOL	400	500	400	500	NF	400	500	2000	400 TWA
8.2	Ventilation & Engineering Controls:	When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia.									
8.4	Eye Protection:	Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166.									
8.5	Hand Protection:	If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.									
8.6	Body Protection:	No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.									

## 9. PHYSICAL &amp; CHEMICAL PROPERTIES

9.1	Appearance:	Viscous liquid, various colors
9.2	Odor:	Ester (fruity) odor
9.3	Odor Threshold:	ND
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NA
9.6	Initial Boiling Point/Boiling Range:	NA
9.7	Flashpoint:	- 4 °C (24.8 °F) estimated
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	ND
9.11	Relative Density:	ND
9.12	Solubility:	Insoluble
9.13	Partition Coefficient (log P <sub>ow</sub> ):	ND
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	ND
9.16	Viscosity:	> 1,200 cPs
9.17	Other Information:	NA

## 10. STABILITY &amp; REACTIVITY

10.1	Stability:	This product is stable under ambient conditions when stored properly (See Section 7, Storage and Handling).
10.2	Hazardous Decomposition Products:	If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gasses (e.g., CO, CO <sub>2</sub> )
10.3	Hazardous Polymerization:	May occur, if exposed to extremely high temperatures.
10.4	Conditions to Avoid:	Open flames, sparks, high heat and direct sunlight. This product is incompatible with strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), strong bases (e.g., lye, potassium hydroxide).
10.5	Incompatible Substances:	None known.

## 11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	The product has NOT been tested on animals to obtain toxicological data. There are toxicology data for the components of this product, which are found in the scientific literature. This data has not been presented in this document.		
11.3	Acute Toxicity:	See Section 4.4		
11.4	Chronic Toxicity:	See Section 4.5		
11.5	Suspected Carcinogen:	This product contains <u>Isopropyl Alcohol</u> , which is not carcinogenic to humans but is listed as a Group 3 carcinogen by the IARC.		
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not reported to produce reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 4.3		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 10/6/2016

## 12. ECOLOGICAL INFORMATION


12.1	Environmental Stability:	The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: <u>Ethyl Acetate</u> : Koc = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. <u>Butyl Acetate</u> : Koc = 1.82. Water solubility: 120 parts H <sub>2</sub> O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. <u>Isopropyl Alcohol</u> : Log K <sub>ow</sub> = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large release of this product may be harmful or fatal to overexposed aquatic life.

## 13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Dispose of in accordance with federal, state and local regulations.
13.2	Special Considerations:	U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)


## 14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (IP VOL ≤ 1.0 L) CONSUMER COMMODITY, ORM-D – until 01/01/2021	
14.2	IATA (AIR):	UN1263, PAINT RELATED MATERIAL, 3, II LTD QTY (0.5L < IP VOL ≤ 1.0 L) CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L)	
14.3	IMDG (OCN):	UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (IP VOL ≤ 1.0 L) EXCEPTED QUANTITY (IP VOL ≤ 30 ml)	
14.4	TDGR (Canadian GND):	MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)	
14.5	ADR/RID (EU):	UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1263, PRODUCTOS PARA PINTURA, 3, II, CANTIDAD LIMITADA (≤ 1.0 L)	
14.7	ADGR (AUS):	UN1263, PAINT RELATED MATERIAL, 3, II, LTD QTY (IP VOL ≤ 1.0 L)	

\* This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package)

## 15. REGULATORY INFORMATION



15.1	SARA Reporting Requirements:	This product contains <u>isopropanol</u> , a substance subject to SARA Title III, Section 313 reporting requirements. This product contains <u>Ethyl Acetate</u> , a substance that is subject to SARA Title III, Section 304 reporting.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	Ethyl Acetate: 2,270 kg (5,000 lbs); Butyl Acetate: 2,270 kg (5,000 lbs)	
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List, WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects)	
15.7	State Regulatory Information:	<u>Butyl Acetate</u> is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), New Jersey Right-to-Know List (NJ), New York List of Hazardous Substances (NY), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List for Air Contaminants (WA), Wisconsin Hazardous Substances List (WI). <u>Ethyl Acetate</u> is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, and WA. <u>Isopropanol</u> is found on the following state criteria lists: CA, MA, MN, NJ, PA, and WA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).	
15.8	Other Requirements:	NA	

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 10/6/2016

## 16. OTHER INFORMATION

16.1	Other information:	<b>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL.</b> Keep away from heat/sparks/open flame/hot surfaces – No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/gas/mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs - Get medical advice/attention. Store in a well-ventilated place. Keep cool. <b>KEEP OUT OF REACH OF CHILDREN.</b>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 <a href="http://www.opi.com">http://www.opi.com</a>	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 <a href="http://www.shipmate.com">http://www.shipmate.com</a>	 <i>Dangerous Goods Training &amp; Consulting</i>

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 10/6/2016

**DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

**GENERAL INFORMATION:**

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

**EXPOSURE LIMITS IN AIR:**

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

**FIRST AID MEASURES:**

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

**HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS**

**HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

**HEALTH**  
**FLAMMABILITY**  
**PHYSICAL HAZARDS**  
**PERSONAL PROTECTION**

**PERSONAL PROTECTION RATINGS:**

<b>A</b>		<b>G</b>	
<b>B</b>		<b>H</b>	
<b>C</b>		<b>I</b>	
<b>D</b>		<b>J</b>	
<b>E</b>		<b>K</b>	
<b>F</b>		<b>X</b>	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

**OTHER STANDARD ABBREVIATIONS:**


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus
Flam.	Flammable
Liq.	Liquid
Sol.	Solid
Tox.	Toxicity
Irrit.	Irritation
Sens.	Sensitization
Ox.	Oxidizing
Corr.	Corrosion
Repr.	Reproductive (Harm)
Asp.	Aspiration
Inh.	Inhalation
Dam.	Damage
STOT SE	Specific Target Organ Toxicity - Single Exposure
STOT RE	Specific Target Organ Toxicity - Repeated Exposure

**NATIONAL FIRE PROTECTION ASSOCIATION: NFPA**

FLAMMABILITY LIMITS IN AIR:	
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

**HAZARD RATINGS:**

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



**TOXICOLOGICAL INFORMATION:**

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>01</sub>	Lowest dose to cause a symptom
TCLO	Lowest concentration to cause a symptom
TD <sub>01</sub> , LD <sub>01</sub> , & LD <sub>50</sub> or TC, TC <sub>01</sub> , LC <sub>01</sub> , & LC <sub>50</sub>	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log K <sub>ow</sub> or log K <sub>oc</sub>	Coefficient of Oil/Water Distribution

**REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

**WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:**

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

**EC (67/548/EEC) INFORMATION:**

C	E	F	N	O	T	XI	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

**CLP/GHS (1272/2008/EC) PICTOGRAMS:**

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 6/20/2016

**3. COMPOSITION & INGREDIENT INFORMATION – cont'd**

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m <sup>3</sup> )									OTHER
					ACGIH		NOHSC			OSHA				
					ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm		
TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH							
TRIMETHYLPENTANEDIYL DIBENZOATE	68052-23-3	NA	268-316-3	0.0-2.0	NA	NA	NF	NF	NF	NA	NA	NA		
PHOSPHORIC ACID	7664-38-2	Tb6300000	231-633-2	0.0-2.0	NA	NA	NF	NF	NF	NA	NA	NA		
	Skin Corr. 1B; H314													
MAY CONTAIN: COLORANTS				0.0-2.0										
CI 12085 (RED 36)	2814-77-9	NA	220-562-2	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 15850 (RED 6)	5858-81-1	CR0600000	231-784-4	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 15850 (RED 7)	5281-04-9	VV8760000	310-127-6	0.0-1.7	NA	NA	(2.5)	NF	NF	30	NA	NA	RESP FRAC	
CI 15880 (RED 34)	6417-83-0	NA	229-142-3	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 15985 (YELLOW 6)	5858-81-1	ZF6680000	227-497-9	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 17200 (RED 33)	3567-66-6	NA	222-656-9	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 19140 (YELLOW 5)	1934-21-0	XR2275000	236-675-5	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 42090 (BLUE 1)	3844-45-9	BQ4725000	223-339-8	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 45350 (YELLOW 7)	518-47-8	NA	208-253-0	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 45350 (YELLOW 8)	518-47-8	NA	208-253-0	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 45370 (ORANGE 5)	596-03-2	LM5200000	209-876-0	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 45380 (RED 21)	15086-94-9	NA	241-409-6	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 45380 (RED 22)	548-26-5	NA	241-409-6	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 45410 (RED 28)	18472-87-2	NA	236-747-6	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 47000 (YELLOW 11)	8003-22-3	NA	232-318-2	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 60725 (VIOLET 2)	81-48-1	CB7700000	201-353-5	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 60730 (EXT. VIOLET 2)	4430-18-6	NA	224-618-7	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 61565 (GREEN 6)	128-80-3	CB5775000	204-909-5	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 73360 (RED 30)	2379-74-0	VV8760000	310-127-6	0.0-1.7	NA	NA	(2.5)	NF	NF	30	NA	NA	RESP FRAC	
CI 75170 (GUANINE)	73-40-5	NA	200-799-8	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315, H319, H335													
CI 75470 (CARMINE)	1390-65-4	FH8891000	215-724-4	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77000 (ALUMINUM POWDER)	7429-90-5	CR0500000	231-784-4	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77007 (ULTRAMARINES)	1302-83-6	NA	215-111-1	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77163 (BISMUTH OXYCHLORIDE)	7787-59-9	NO7400000	215-168-2	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77266 (BLACK 2)	1333-86-4	FF5800000	215-609-9	0.0-1.7	3.5	NA	3	NF	NF	3.5	NA	NA		
CI 77288 (CHROMIUM OXIDE GREEN)	1308-38-9	GB6475000	215-160-9	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77289 (CHROMIUM HYDROXIDE GREEN)	1308-14-1	NA	215-158-8	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77400 (COPPER POWDER)	7440-50-8	GL5325000	231-159-6	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 6/20/2016

**3. COMPOSITION & INGREDIENT INFORMATION – cont'd**

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m <sup>3</sup> )									OTHER
					ACGIH		NOHSC			OSHA				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
CI 77491 (IRON OXIDES)	1309-37-1	UQ6400000	217-699-5	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77492 (IRON OXIDES - YELLOW)	51274-00-1	NA	257-098-5	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77499 (IRON OXIDES)	1309-37-9	UD3422500	248-666-3	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77510 (FERRIC FERROCYANIDE)	14038-43-5	NA	215-277-5	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77742 (MANGANESE VIOLET)	10101-66-3	NA	233-257-4	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77820 (SILVER)	1934-21-0	VW3500000	217-699-5	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CI 77891 (TITANIUM DIOXIDE)	13463-67-7	XR2275000	236-675-5	0.1-1	NA	NA	NF	NF	NF	NA	NA	NA		
MAY CONTAIN: SHIMMER, GLITTER, OPACIFIERS														
ACRYLATES COPOLYMER	25035-69-2	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
ALUMINA	1344-28-1	BD1200000	215-691-6	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
ALUMINUM CALCIUM SODIUM SILICATE	1344-01-1	NA	215-685-3	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
ALUMINUM HYDROXIDE	21645-51-2	NA	244-492-7	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
BARIUM SULFATE	7727-43-7	CB7700000	201-353-5	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
BIS(GLYCIDOPHENYL) PROPANE/BISAMINOMETHYLNORBORNANE COPOLYMER	NA	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
CALCIUM ALUMINUM BOROSILICATE	65997-17-3	NA	266-046-0	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA	Skin Irrit. 2; Eye Irrit. 2A; Carc. 2; STOT-SE 3; H315, H319, H335, H351	
CALCIUM SODIUM BOROSILICATE	65997-17-3	NA	266-046-0	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA	Skin Irrit. 2; Eye Irrit. 2A; Carc. 2; STOT-SE 3; H315, H319, H335, H351	
DIAMOND POWDER	7782-40-3	NA	231-953-2	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
ETHYLENE/VA COPOLYMER	24937-78-8	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
IRON POWDER	7439-89-6	NA	231-096-4	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
ISOBUTYLPHENOXY EPOXY RESIN	67924-34-9	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
ISOPHORONE DIAMINE/ISOPHTHALIC ACID/TROMETHAMINE COPOLYMER	NA	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
LUMINESCENT ZINC SULFIDE	NA	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
MICA	12001-26-2	NA	215-111-1	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
PLATINUM POWDER	7440-06-4	TP2160000	231-116-1	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
POLYBUTYLENE TEREPHTHALATE	26062-94-2	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
POLYETHYLENE	9002-88-4	TQ3325000	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
POLYETHYLENE TEREPHTHALATE	25038-59-9	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
POLYMETHYLPHENYLSILSESQUOXANE SILICATE	NA	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
POLYPROPYLENE	9003-07-0	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		
POLYURETHANE-11	68258-82-8	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA		

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards | SDS Revision: 1.0 | SDS Revision Date: 6/20/2016

**3. COMPOSITION & INGREDIENT INFORMATION – cont'd**

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m <sup>3</sup> )								
					ACGIH		NOHSC			OSHA			OTHER
					ppm		ppm			ppm			
POLYURETHANE-33	125826-44-0	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA	
POLYVINYL BUTYRAL	63148-65-2	TR49550000	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA	
SYNTHETIC FLUORPHLOGOPITE	12003-38-2	NA	234-426-5	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA	
TALC	14807-96-6	WW2710000	238-877-9	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA	
TIN OXIDE	18282-10-5	XQ400000	242-159-0	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA	
TRIMETHYLSILOXYSILICATE	STOT SE 3; H335												
	NA	NA	NA	0.0-1.7	NA	NA	NF	NF	NF	NA	NA	NA	

**4. FIRST AID MEASURES**

4.1	First Aid:	<p><b>Ingestion:</b> If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p><b>Eyes:</b> Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.</p> <p><b>Skin:</b> If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.</p> <p><b>Inhalation:</b> Remove victim to fresh air at once.</p>												
4.2	Effects of Exposure:	<p><b>Ingestion:</b> If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.</p> <p><b>Eyes:</b> Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p><b>Skin:</b> May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact.</p> <p><b>Inhalation:</b> Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 3 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).</p>												
4.3	Symptoms of Overexposure:	Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering.												
4.4	Acute Health Effects:	Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.												
4.5	Chronic Health Effects:	None known.												
4.6	Target Organs:	Eyes, Skin, Respiratory System.												
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin, and respiratory system).												
		<table border="1"> <tr> <td><b>HEALTH</b></td> <td><b>1</b></td> </tr> <tr> <td><b>FLAMMABILITY</b></td> <td><b>3</b></td> </tr> <tr> <td><b>PHYSICAL HAZARDS</b></td> <td><b>0</b></td> </tr> <tr> <td><b>PROTECTIVE EQUIPMENT</b></td> <td><b>B</b></td> </tr> <tr> <td><b>EYES</b></td> <td></td> </tr> <tr> <td><b>SKIN</b></td> <td></td> </tr> </table>	<b>HEALTH</b>	<b>1</b>	<b>FLAMMABILITY</b>	<b>3</b>	<b>PHYSICAL HAZARDS</b>	<b>0</b>	<b>PROTECTIVE EQUIPMENT</b>	<b>B</b>	<b>EYES</b>		<b>SKIN</b>	
<b>HEALTH</b>	<b>1</b>													
<b>FLAMMABILITY</b>	<b>3</b>													
<b>PHYSICAL HAZARDS</b>	<b>0</b>													
<b>PROTECTIVE EQUIPMENT</b>	<b>B</b>													
<b>EYES</b>														
<b>SKIN</b>														

**5. FIREFIGHTING MEASURES**

5.1	Fire & Explosion Hazards:	<b>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR!</b> Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed.
5.2	Extinguishing Methods:	CO <sub>2</sub> , Halon (if permitted), Dry Chemical, Foam, as authorized.
5.3	Firefighting Procedures:	<p>This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.</p> <p>First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product.</p> <p>HazChem Code: 3(Y)E Hazard Identification Number: 33</p>





Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 6/20/2016

## 6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <b>small spills</b> (e.g., &lt; 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <b>large spills</b> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use <b>ONLY</b> non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.</p>
-----	---------	--

## 7. HANDLING &amp; STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.
7.2	Storage & Handling:	Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10).
7.3	Special Precautions:	Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

## 8. EXPOSURE CONTROLS &amp; PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m <sup>3</sup> )		ACGIH		NOHSC			OSHA			OTHER
		CHEMICAL NAME(S)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ETHYL ACETATE	400	400	200	400	NF	NA	NA	2000	400 TWA
		BUTYL ACETATE	150	200	150	200	NF	200	200	1700	100 NIOSH
		NITROCELLULOSE	400	400	400	200	NF	NA	NA	2000	400 TWA
		ISOPROPYL ALCOHOL	400	500	400	500	NF	400	500	2000	400 TWA
		SILICA	(10)	NA	NF	NF	NF	(6)	NA	NA	
		DIACETONE ALCOHOL	50	240	238	NF	NF	20	240	1800	
		CI 15850 (RED 7)	NA	NA	(2.5)	NF	NF	30	NA	NA	RESP FRAC
		CI 73360 (RED 30)	NA	NA	(2.5)	NF	NF	30	NA	NA	RESP FRAC
CI 77266 (BLACK 2)	3.5	NA	3	NF	NF	3.5	NA	NA			
8.2	Ventilation & Engineering Controls:	When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.									
8.4	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.									
8.5	Hand Protection:	<b>AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL.</b> If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states.									
8.6	Body Protection:	<b>AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL.</b> However, no special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA.									

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 6/20/2016

## 9. PHYSICAL &amp; CHEMICAL PROPERTIES

9.1	Appearance:	Viscous liquid
9.2	Odor:	Characteristic
9.3	Odor Threshold:	ND
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	NE
9.6	Initial Boiling Point/Boiling Range:	NA
9.7	Flashpoint:	4.4 °C (40 °F)
9.8	Upper/Lower Flammability Limits:	NA
9.9	Vapor Pressure:	NA
9.10	Vapor Density:	NA
9.11	Relative Density:	NA
9.12	Solubility:	Insoluble
9.13	Partition Coefficient (log P <sub>ow</sub> ):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	300 - 500 cPs
9.17	Other Information:	NA

## 10. STABILITY &amp; REACTIVITY

10.1	Stability:	Stable under ambient conditions when stored properly (See Section 7, Storage and Handling).
10.2	Hazardous Decomposition Products:	If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO <sub>2</sub> ).
10.3	Hazardous Polymerization:	May occur, if exposed to extremely high temperatures.
10.4	Conditions to Avoid:	High temperatures, direct sunlight, sources of heat and incompatible materials.
10.5	Incompatible Substances:	This product is incompatible with strong oxidizers, (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), nitrates, or strong bases (e.g., lye, potassium hydroxide).

## 11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. These data have not been presented in this document. Ethyl Acetate: LD <sub>50</sub> (oral, rat) = 11,300 mg/kg; Butyl Acetate: LD <sub>50</sub> (oral, rat) = 11,400 mg/kg; Isopropyl Alcohol: LD <sub>50</sub> (oral, rat) = 5,840 mg/kg		
11.3	Acute Toxicity:	See Section 4.4		
11.4	Chronic Toxicity:	See Section 4.5		
11.5	Suspected Carcinogen:	This product contains Calcium Aluminum Borosilicate, Ethyl Acetate, Isopropyl Alcohol, and Silica which are not carcinogenic to humans but is listed as a Group 3 carcinogen by the IARC.		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product contains Calcium Aluminum Borosilicate which is reported to cause teratogenic effects in certain animal species.		
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 4.3		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

## 12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Ethyl Acetate: K <sub>oc</sub> = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: K <sub>oc</sub> = 1.82. Water solubility: 120 parts H <sub>2</sub> O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log K <sub>ow</sub> = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate.
12.2	Effects on Plants & Animals:	There are no specific data available for this product.
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 6/20/2016

## 13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Waste disposal must be in accordance with appropriate Federal, state, and local regulations.
13.2	Special Considerations:	U.S. EPA Waste Number: D001 (characteristic - ignitable)

## 14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 1.0 L) or CONSUMER COMMODITY, ORM-D – until 01/01/2021	
14.2	IATA (AIR):	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) UN1263, PAINT RELATED MATERIAL, 3, II (LTD QTY, IP ≤ 0.5 L)	or
14.3	IMDG (OCN):	EXCEPTED QUANTITY (2008 IMO § 3.5.1) (≤ 30 ml) UN1263, PAINT, 3, II (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)	
14.5	ADR/RID (EU):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1263, PRODUCTOS PARA PINTURA, 3, II, (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1263, PAINT RELATED MATERIAL, 3, II, (LTD QTY, IP VOL ≤ 1.0 L)	
14.8	EXCEPTED QUANTITIES: *	THIS PRODUCT MAY BE SHIPPED AS AN EXCEPTED QUANTITY IP VOL ≤ 30 mL; TOTAL VOL PER PKG ≤ 1000 mL	

## 15. REGULATORY INFORMATION


15.1	SARA Reporting Requirements:	This product contains <u>Isopropanol</u> , a substance subject to SARA Title III, Section 313 reporting requirements. This product contains <u>Ethyl Acetate</u> , a substance that is subject to SARA Title III, Section 304 reporting.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	<u>Ethyl Acetate</u> : 2,270 kg (5,000 lbs); <u>Butyl Acetate</u> : 2,270 kg (5,000 lbs)	
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDL. None of the components of this product are listed on the Priorities Substances List, WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects)	
15.7	State Regulatory Information:	<p><u>Butyl Acetate</u> is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), New Jersey Right-to-Know List (NJ), New York List of Hazardous Substances (NY), Pennsylvania Right-to-Know List (PA), and Washington Permissible Exposures List for Air Contaminants (WA), Wisconsin Hazardous Substances List (WI).</p> <p><u>Ethyl Acetate</u> is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, and WA.</p> <p><u>Isopropanol</u> is found on the following state criteria lists: CA, MA, MN, NJ, PA, and WA.</p> <p><u>Nitrocellulose</u> is found on the following state criteria lists: DE, MA, and PA.</p> <p><u>Silica</u> is found on the following state criteria list: MA, MN, and PA.</p> <p><u>Heptane</u> is found on the following state criteria list: FL, MA, MN, PA and WA.</p> <p><u>Camphor</u> is found on the following state criteria list: FL, MA, MN, PA and WA.</p> <p>No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).</p>	

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 &amp; 1272/2008/EC Standards


SDS Revision: 1.0

SDS Revision Date: 6/20/2016

## 15. REGULATORY INFORMATION – cont'd

15.8	Other Requirements:	<p>The primary components of this product are listed in Annex I of EU Directive 67/548/EEC:</p> <p><b>Ethyl Acetate:</b> Flammable (F). <b>Risk Phrases (R):</b> 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system and skin. <b>Safety Phrases (S):</b> 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.</p> <p><b>Butyl Acetate:</b> Flammable (F). <b>Risk Phrases (R):</b> Flammable. <b>Safety Phrases (S):</b> 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.</p> <p><b>Isopropanol:</b> Flammable (F). <b>Risk Phrases (R):</b> 11-36/37 – Highly flammable. Irritating to eyes and respiratory system. <b>Safety Phrases (S):</b> 2-7-16-24/25/26 – Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</p>	
------	---------------------	--	---

## 16. OTHER INFORMATION

16.1	Other information:	<p><b>DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS.</b> Keep away from heat/sparks/open flame/hot surfaces – No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Avoid eye contact. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs – Get medical advice/attention. Store in a well-ventilated place. Keep cool. Use only as directed. <b>KEEP OUT OF REACH OF CHILDREN.</b></p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	<p>This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's &amp; OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.</p>	
16.4	Prepared for:	<p><b>OPI Products, Inc.</b> 13034 Saticoy Street No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 <a href="http://www.opi.com">http://www.opi.com</a></p>	
16.5	Prepared by:	<p><b>ShipMate, Inc.</b> P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 <a href="http://www.shipmate.com">http://www.shipmate.com</a></p>	

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

**HEALTH**  
**FLAMMABILITY**  
**PHYSICAL HAZARDS**  
**PERSONAL PROTECTION**

PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	

G	
H	
I	
J	
K	
X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Synthetic Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autolgn/ton Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC <sub>50</sub>	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD <sub>01</sub>	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD <sub>01</sub> , LD <sub>01</sub> & LD <sub>50</sub> or TC, TC <sub>01</sub> , LC <sub>01</sub> & LC <sub>50</sub>	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL <sub>m</sub>	Median threshold limit
log K <sub>ow</sub> or log K <sub>oc</sub>	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment