



AMERICAN INTERNATIONAL INDUSTRIES

Safety Data Sheet Nail Tek 10 Speed

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name	Nail Tek 10 Speed
Product number	55522, 55522I, 55523, 55826, 55827, NK31000, NK31040

Other means of identification

Uses: Personal Beauty Product

Details of the supplier of the safety data sheet

Name	American International Industries
Address	2220 Gaspar Ave Los Angeles, CA 90040 USA
Telephone	323-728-2999

Emergency telephone number

Chem-Tel: 1(800) 255-3924

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP) and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3, H336
- Flammable liquids (chapter 2.6), Cat. 2, H225
- Serious eye damage/eye irritation (chapter 3.3), Cat 2B , H320

For the full text corresponding to the "H"-codes displayed in this section, refer to Section 16.

Label elements

Labeling according to Regulation (EC) No 1272/2008 [CLP] and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

Safety Data Sheet

Nail Tek 10 Speed

Hazard pictograms



Signal word

Warning!

Hazard statement(s)

H226 Flammable liquid and vapor
H336 May cause drowsiness or dizziness
H320 Causes eye irritation

Precautionary statement(s)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

Other hazards

None

SECTION 3: Composition/information on ingredients

Mixtures

Components

Component	Concentration
Non Hazardous Ingredients	90 - 100 %
CLASSIFICATIONS: Not classified HAZARDS: Non-hazardous	
Isopropyl Alcohol (CAS no.: 67-63-0)	10 - 25 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H226 - Flammable liquid and vapor; H336 - May cause drowsiness or dizziness; H320-Causes eye irritation	

SECTION 4: First aid measures

Description of first aid measures

General notes Consult a physician. Show this safety data sheet to the doctor in attendance.

Following inhalation Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Following skin contact Wash off with soap and plenty of water.

Following eye contact Flush eyes with water as a precaution.

SECTION 5: Firefighting measures

Extinguishing media

Dry chemical, carbon dioxide, Halon foam. Water may be ineffective. Water spray may be used to keep fire exposed containers cool and to disperse vapors.

Special hazards arising from the substance or mixture

Safety Data Sheet

Nail Tek 10 Speed

Vapors can travel to a source of ignition and flashback. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Advice for firefighters

First responders should wear eye protection. Structural fire-fighters must wear MSHA/NIOSH approved SCBA and full protective equipment. Use a water spray or fog to reduce vapors. Water may not be effective in extinguishing a fire involving this product.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Household: Absorb with inert material and place in a appropriate waste disposal

Industrial: Avoid contact with skin, eyes, and clothing. Remove all sources of ignition. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system

Environmental precautions

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid exposure to skin and eye. Good standards of safe working practice and industrial hygiene should be observed.

Conditions for safe storage, including any incompatibilities

Keep this material away from heat, sparks, and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of the product; therefore handle empty container with care.

Store containers in a cool dry place, away from direct sunlight, other light sources, or any intense heat. Store away from incompatible materials as appropriate.

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 67-63-0

Isopropanol

Cal/OSHA: 400 ppm, (ST) 500 ppm PEL inhalation; NIOSH: 400 ppm, (ST) 500 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 980 mg/m³ PEL inhalation

Exposure controls

Appropriate engineering controls

General industrial hygiene practice.

Personal protection equipment

Safety Data Sheet

Nail Tek 10 Speed

Eye and face protection

Eye/Face Protection: None required with normal household use. Industrial Setting: For splash protection, use chemical goggles. Eye wash fountain is recommended.

Skin protection

Distribution, Workplace and Household Settings: No special protective equipment required. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid/clear
Odour	Solvent
Odour threshold	No data
pH	Not applicable
Melting point / freezing point	No data
Initial boiling point and boiling range	No data
Flash point	11.5 C (53 F)
Evaporation rate	No data
Flammability (solid, gas)	Flammable
Upper/lower flammability limits	No data
VOC	1.30 lb/gal
Vapour pressure	No data
Vapour density	No data
Relative density	No data
Solubility	Moderate
Partition coefficient: n-octanol/water	No data
Auto-ignition temperature	No data
Decomposition temperature	No data
Viscosity	No data
Explosive properties	No data
Oxidizing properties	No data
Specific gravity	0.96

SECTION 10: Stability and reactivity

Reactivity

None under normal use conditions.

Chemical stability

Unstable, may polymerize at elevated temperatures Possibility of hazardous reactions

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/irritation

May cause eye irritation

Safety Data Sheet

Nail Tek 10 Speed

Respiratory or skin sensitization

No data available

Carcinogenicity

This product does not contain a component that is classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

Toxicity

No known hazards

SECTION 13: Disposal considerations

Waste treatment methods

Disposal of the product

Collect all waste in suitable and labeled containers and dispose according to local legislation.

SECTION 14: Transport information

DOT (US)

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

IMDG

UN Number: 1263

Class: 3

Packing Group: II

Proper Shipping Name: Paint

IATA

UN ID: ID8000

Class: 9

Packing Instructions: Y963

Proper Shipping Name: Consumer Commodity

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Toxic Substances Control Act (TSCA) Inventory

Safety Data Sheet

Nail Tek 10 Speed

The components of this product are listed on the TSCA Inventory as appropriate.

SARA 311/312 Hazards

No SARA hazards.

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

New Jersey Right To Know Components

No components are subject to the New Jersey Right to Know Act.

Pennsylvania Right To Know Components

No components are subject to the Pennsylvania Right to Know Act.

WHMIS (Canada)

D2B - Eye irritation

Included for disclosure at 1% or greater (CAS#: 67-63-0 /2-Propanol)

SECTION 16: Other information

Hazard statement(s)

H335

May cause respiratory irritation

H226

Flammable liquid and vapor

H320

Causes eye irritation

Further information/disclaimer

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.