

# SAFETY DATA SHEET

Issuing Date No data available

Revision Date 07-Apr-2015

Revision Number 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is ©2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name 8oz Hand Sanitizer - Original

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Hand sanitizer

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name Ningbo Rejoice I/E Co., Ltd.  
Supplier Address Rm402, Unit 4, North Bank Fortune Centre, Jiangbei, Ningbo, 315020, China  
Ningbo  
Zhejiang  
315020  
CN  
Supplier Phone Number Phone: 0086-13586668388  
Fax: 0086-574-87170180  
Contact Phone 0086-13586668388  
Supplier Email powerwell2000@hotmail.com  
Emergency telephone number

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
-------------------	------------

### GHS Label elements, including precautionary statements

#### Emergency Overview

Signal word	Danger
-------------	--------



Highly flammable liquid and vapor



**Appearance** Clear

**Physical State** Viscous liquid Liquid

**Odor** Fresh

#### **Precautionary Statements - Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ ventilating/ lighting/ equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary Statements - Response**

##### **Skin**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

##### **Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Hazards not otherwise classified (HNOC)**

Not applicable

#### **Unknown Toxicity**

0.503% of the mixture consists of ingredient(s) of unknown toxicity

#### **Other information**

Toxic to aquatic life  
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION  
May cause slight eye irritation

#### **Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Ethyl alcohol	64-17-5	40 - 70	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

#### First aid measures

#### General Advice

Call 911 or emergency medical service. Remove and isolate contaminated clothing and shoes.

#### Eye Contact

In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.

#### Skin Contact

Wash skin with soap and water.

#### Inhalation

Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult.

#### Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting.

#### Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

#### Most important symptoms and effects, both acute and delayed

**Most Important Symptoms and Effects** No information available.

#### Indication of any immediate medical attention and special treatment needed

#### Notes to Physician

Keep victim warm and quiet.

## 5. FIRE-FIGHTING MEASURES

### **Suitable Extinguishing Media**

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam. Water spray, fog or alcohol-resistant foam. Use water spray or fog; do not use straight streams.

### **Unsuitable extinguishing media**

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

### **Specific Hazards Arising from the Chemical**

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

#### **Uniform Fire Code**

Flammable Liquid: I-B

### **Hazardous Combustion Products**

Carbon oxides.

### **Explosion Data**

**Sensitivity to Mechanical Impact** No.

**Sensitivity to Static Discharge** Yes.

### **Protective equipment and precautions for firefighters**

Move containers from fire area if you can do it without risk.

## 6. ACCIDENTAL RELEASE MEASURES

### **Personal precautions, protective equipment and emergency procedures**

#### **Personal Precautions**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.

#### **Other Information**

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

### **Environmental Precautions**

#### **Environmental Precautions**

Prevent entry into waterways, sewers, basements or confined areas.

### **Methods and material for containment and cleaning up**

#### **Methods for Containment**

A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

#### **Methods for cleaning up**

Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### Handling

Handle in accordance with good industrial hygiene and safety practice. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Avoid contact with skin, eyes or clothing.

### Conditions for safe storage, including any incompatibilities

#### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

#### Incompatible Products

None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm 10% LEL TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

#### Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

### Appropriate engineering controls

#### Engineering Measures

Showers  
Eyewash stations  
Ventilation systems

### Individual protection measures, such as personal protective equipment

#### Eye/Face Protection

None required for consumer use.

#### Skin and Body Protection

None required for consumer use.

#### Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

#### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of

the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical and Chemical Properties

<b>Physical State</b>	Viscous liquid, Liquid	<b>Odor</b>	Fresh
<b>Appearance</b>	Clear	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		

Property	Values	Remarks	Method
<b>pH</b>	7	None known	
<b>Melting / freezing point</b>	No data available	None known	
<b>Boiling point / boiling range</b>	No data available	None known	
<b>Flash Point</b>	22 C / 72 F	None known	
<b>Evaporation Rate</b>	No data available	None known	
<b>Flammability (solid, gas)</b>	No data available	None known	
<b>Flammability Limit in Air</b>			
<b>Upper flammability limit</b>	No data available		
<b>Lower flammability limit</b>	No data available		
<b>Vapor pressure</b>	No data available	None known	
<b>Vapor density</b>	No data available	None known	
<b>Specific Gravity</b>	No data available	None known	
<b>Water Solubility</b>	Soluble in water	None known	
<b>Solubility in other solvents</b>	No data available	None known	
<b>Partition coefficient: n-octanol/water</b>	No data available	None known	
<b>Autoignition temperature</b>	No data available	None known	
<b>Decomposition temperature</b>	No data available	None known	
<b>Kinematic viscosity</b>	No data available	None known	
<b>Dynamic viscosity</b>	No data available	None known	
<b>Explosive properties</b>	No data available		
<b>Oxidizing Properties</b>	No data available		

### Other Information

<b>Softening Point</b>	No data available
<b>VOC Content (%)</b>	No data available
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available.

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Hazardous Polymerization

Hazardous polymerization does not occur.

### Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

None known based on information supplied.

### Hazardous Decomposition Products

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	Specific test data for the substance or mixture is not available.
<b>Eye Contact</b>	Specific test data for the substance or mixture is not available. Contact with eyes may cause irritation.
<b>Skin Contact</b>	Specific test data for the substance or mixture is not available.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available.

#### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl alcohol 64-17-5	-	-	= 124.7 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** May cause redness and tearing of the eyes.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.

**Mutagenic Effects** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethyl alcohol 64-17-5	A3	Group 1	Known	X

*ACGIH (American Conference of Governmental Industrial Hygienists)*

*A3 - Animal Carcinogen*

*IARC (International Agency for Research on Cancer)*

*Group 1 - Carcinogenic to Humans*

*Group 3 - Not Classifiable as to Carcinogenicity in Humans*

*NTP (National Toxicology Program)*

*Known - Known Carcinogen*

*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*

*X - Present*

**Reproductive Toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic Toxicity** No known effect based on information supplied. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

**Target Organ Effects**

Blood. Central Nervous System (CNS). Eyes. Liver. Reproductive System. Respiratory system. Skin.

**Aspiration Hazard**

No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (inhalation-dust/mist)**

201.10 mg/l

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic organisms.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Ethyl alcohol 64-17-5		96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 13400 - 15100 mg/L (Pimephales promelas) 96h LC50: 12.0 - 16.0 mL/L (Oncorhynchus mykiss)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	48h LC50: 9268 - 14221 mg/L 48h EC50: = 2 mg/L 24h EC50: = 10800 mg/L

**Persistence and Degradability**

No information available.

**Bioaccumulation**

Chemical Name	Log Pow
Ethyl alcohol 64-17-5	-0.32

**Other adverse effects**

No information available.



### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

<b>Disposal methods</b>	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
<b>Contaminated Packaging</b>	Dispose of contents/containers in accordance with local regulations.
<b>US EPA Waste Number</b>	D001

#### **California Hazardous Waste Codes 331**

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ethyl alcohol 64-17-5	Toxic Ignitable

### 14. TRANSPORT INFORMATION

#### DOT

<b>Proper Shipping Name</b>	CONSUMER COMMODITY
<b>Hazard Class</b>	ORM-D
<b>Description</b>	CONSUMER COMMODITY, ORM-D
<b>Emergency Response Guide Number</b>	127

#### TDG

<b>UN-No.</b>	UN1170
<b>Proper Shipping Name</b>	ETHANOL SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1170, ETHANOL SOLUTION, 3, II

#### MEX

<b>UN-No.</b>	UN1170
<b>Proper Shipping Name</b>	ETHANOL IN SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1170, ETHANOL IN SOLUTION, 3, II

#### ICAO

<b>UN-No.</b>	UN1170
<b>Proper Shipping Name</b>	ETHANOL SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1170, ETHANOL SOLUTION, 3, II

#### IATA

<b>UN-No.</b>	UN1170
<b>Proper Shipping Name</b>	ETHANOL SOLUTION
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1170, ETHANOL SOLUTION, 3, II



**IMDG/IMO**

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	II
EmS-No.	F-E, S-D
Description	UN1170, ETHANOL SOLUTION, 3, II

**RID**

UN-No.	UN1170
Proper Shipping Name	ETHANOL
Hazard Class	3
Packing Group	II
Classification code	F1
Description	UN1170, ETHANOL, 3, II

**ADR**

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	II
Classification code	F1
Tunnel restriction code	(D/E)
Description	UN1170, ETHANOL SOLUTION, 3, II

**ADN**

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	II
Classification code	F1
Special Provisions	144, 601
Description	UN1170, ETHANOL SOLUTION, 3, II
Hazard Labels	3
Limited Quantity	1 L
Ventilation	VE01

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.
IECSC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No



**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethyl alcohol - 64-17-5	Carcinogen Developmental

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Ethyl alcohol 64-17-5		X			
Triethanolamine 102-71-6	X	X	X		
Glycerin 56-81-5	X	X	X	X	

**International Regulations****Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Ethyl alcohol 64-17-5 ( 40 - 70 )		Mexico: TWA 1000 ppm Mexico: TWA 1900 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

**Canada****WHMIS Hazard Class**

B2 - Flammable liquid

D2A - Very toxic materials

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b> 1	<b>Flammability</b> 4	<b>Instability</b> 0	<b>Physical and Chemical Hazards - Personal Protection</b> X
<b>HMIS</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 4	<b>Physical Hazard</b> 0	

**Prepared By**

Product Stewardship  
23 British American Blvd.  
Latham, NY 12110



**Revision Date** 1-800-572-6501  
**Revision Note** 07-Apr-2015  
No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**