

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

1 Identification

- **Product identifier**
- **Trade name:** *OPI Nature Strong Force of Nailure*
- **Article number:** 99300019766, ENG103288, 314002000928
- **Application of the substance / the mixture** *Cosmetic product*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Wella International Operations Switzerland Sàrl, Chemin Louis-Hubert 1-3, 1213 Petit-Lancy, Switzerland
- **Information department:** *Wella SDS Info Team*
- **Emergency telephone number:**
CHEMTREC Emergency number: +1-703-527-3887
CHEMTREC US/NA Emergency number(toll free): 800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

Butyl acetate

Adipic Acid/Neopentyl Glycol/Trimellitic Anhydride Copolymer

ethyl acetate

- **Hazard statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailure

(Contd. of page 1)

- Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|------------|--|------------|
| 123-86-4 | Butyl acetate | >25-≤50% |
| 141-78-6 | ethyl acetate | ≥20-≤25% |
| 9004-70-0 | Nitrocellulose | >10-≤25% |
| 28407-73-0 | Adipic Acid/Neopentyl Glycol/Trimellitic Anhydride Copolymer | >2.5-≤10% |
| 64-17-5 | ethyl alcohol | >2.5-≤10% |
| 13463-67-7 | titanium dioxide | ≥0.1-≤2.5% |
| 1333-86-4 | Carbon black | ≥0.1-≤2.5% |

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
 Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailture

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

| | | |
|------------|--------------------------------|----------------------|
| 123-86-4 | Butyl acetate | 5 ppm |
| 141-78-6 | ethyl acetate | 1,200 ppm |
| 64-17-5 | ethyl alcohol | 1,800 ppm |
| 13463-67-7 | titanium dioxide | 30 mg/m ³ |
| 67-63-0 | isopropyl alcohol | 400 ppm |
| 1333-86-4 | Carbon black | 9 mg/m ³ |
| 123-42-2 | 4-hydroxy-4-methylpentan-2-one | 150 ppm |
| 66-25-1 | hexanal | 6 ppm |
| 7664-38-2 | Phosphoric Acid | 3 mg/m ³ |
| 71-36-3 | n-Butyl alcohol | 60 ppm |
| 7631-86-9 | Silica | 18 mg/m ³ |

· **PAC-2:**

| | | |
|------------|------------------|-----------------------|
| 123-86-4 | Butyl acetate | 200 ppm |
| 141-78-6 | ethyl acetate | 1,700 ppm |
| 64-17-5 | ethyl alcohol | 3300* ppm |
| 13463-67-7 | titanium dioxide | 330 mg/m ³ |

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailure

(Contd. of page 3)

| | | |
|-----------|--------------------------------|-----------------------|
| 67-63-0 | isopropyl alcohol | 2000* ppm |
| 1333-86-4 | Carbon black | 99 mg/m ³ |
| 123-42-2 | 4-hydroxy-4-methylpentan-2-one | 350 ppm |
| 66-25-1 | hexanal | 66 ppm |
| 7664-38-2 | Phosphoric Acid | 30 mg/m ³ |
| 71-36-3 | n-Butyl alcohol | 800 ppm |
| 7631-86-9 | Silica | 740 mg/m ³ |

· PAC-3:

| | | |
|------------|--------------------------------|-------------------------|
| 123-86-4 | Butyl acetate | 3000* ppm |
| 141-78-6 | ethyl acetate | 10000** ppm |
| 64-17-5 | ethyl alcohol | 15000* ppm |
| 13463-67-7 | titanium dioxide | 2,000 mg/m ³ |
| 67-63-0 | isopropyl alcohol | 12000** ppm |
| 1333-86-4 | Carbon black | 590 mg/m ³ |
| 123-42-2 | 4-hydroxy-4-methylpentan-2-one | 2100* ppm |
| 66-25-1 | hexanal | 86 ppm |
| 7664-38-2 | Phosphoric Acid | 150 mg/m ³ |
| 71-36-3 | n-Butyl alcohol | 8000** ppm |
| 7631-86-9 | Silica | 4,500 mg/m ³ |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailture

(Contd. of page 4)

At this time, the other constituents have no known exposure limits.

| | |
|-------------------------------|---|
| 123-86-4 Butyl acetate | |
| PEL | Long-term value: 710 mg/m ³ , 150 ppm |
| REL | Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm |
| TLV | Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm |
| 141-78-6 ethyl acetate | |
| PEL | Long-term value: 1400 mg/m ³ , 400 ppm |
| REL | Long-term value: 1400 mg/m ³ , 400 ppm |
| TLV | Long-term value: 1440 mg/m ³ , 400 ppm |
| 64-17-5 ethyl alcohol | |
| PEL | Long-term value: 1900 mg/m ³ , 1000 ppm |
| REL | Long-term value: 1900 mg/m ³ , 1000 ppm |
| TLV | Short-term value: 1880 mg/m ³ , 1000 ppm |
| 1333-86-4 Carbon black | |
| PEL | Long-term value: 3.5 mg/m ³ |
| REL | Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C |
| TLV | Long-term value: 3* mg/m ³ *inhalable fraction |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailure

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

| | |
|-------------------|------------------------------------|
| Form: | Viscous |
| Color: | According to product specification |
| · Odor: | Characteristic |
| · Odor threshold: | Not determined. |

· pH-value: Not determined.

· Change in condition

| | |
|------------------------------|---------------------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 77-78 °C (170.6-172.4 °F) |

· Flash point: -1 °C (30.2 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 425 °C (797 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

| | |
|--------|------------|
| Lower: | 1.2 Vol % |
| Upper: | 11.5 Vol % |

· Vapor pressure at 20 °C (68 °F): 97 hPa (72.8 mm Hg)

· Density: Not determined.

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

| | |
|------------|-----------------|
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |

· Solvent content:

| | |
|-------------------|-------------------------|
| Organic solvents: | 71.2 % |
| VOC content: | 71.17 % |
| | 711.7 g/l / 5.94 lb/gal |

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailture

(Contd. of page 6)

Solids content: 13.2 %

Other information No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

123-86-4 Butyl acetate

| | | |
|------------|----------|-----------------------|
| Oral | LD50 | 13,100 mg/kg (rat) |
| Dermal | LD50 | >5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >21 mg/l (rat) |

141-78-6 ethyl acetate

| | | |
|------------|----------|----------------------|
| Oral | LD50 | 5,620 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 1,600 mg/l (rat) |

64-17-5 ethyl alcohol

| | | |
|------------|----------|-------------------------------------|
| Oral | LD50 | 10,470 mg/kg (rat) (bw (OECD 401)) |
| Inhalative | LC50/4 h | 116.9 mg/l (rat) (air (//OECD 403)) |

13463-67-7 titanium dioxide

| | | |
|------------|----------|------------------------------------|
| Oral | LD50 | >5,000 mg/kg (rat) (bw (OECD 425)) |
| Dermal | LD50 | >10,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >3.43 mg/l (rat) (air (OECD 403)) |

1333-86-4 Carbon black

| | | |
|------|------|--------------------|
| Oral | LD50 | 10,000 mg/kg (rat) |
|------|------|--------------------|

· **Primary irritant effect:**

· **on the skin:** No irritant effect.

· **on the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

| | | |
|---------|---------------|--|
| 64-17-5 | ethyl alcohol | |
|---------|---------------|--|

I

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailture

(Contd. of page 7)

| | | |
|------------|---------------------------------------|----|
| 13463-67-7 | titanium dioxide | 2B |
| 67-63-0 | isopropyl alcohol | 3 |
| 1333-86-4 | Carbon black | 2B |
| 61790-53-2 | Diatomaceous earth (Silica-Amorphous) | 3 |
| 7631-86-9 | Silica | 3 |

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|----------------------------------|--------|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · IMDG, IATA | PAINT |

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailure

(Contd. of page 8)

· **Transport hazard class(es)**· **DOT**

· **Class** 3 Flammable liquids
 · **Label** 3

· **IMDG, IATA**

· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**
 · **DOT, IMDG, IATA** II

· **Environmental hazards:** Not applicable.· **Special precautions for user** Warning: Flammable liquids· **Hazard identification number (Kemler code):** 33· **EMS Number:** F-E, S-E· **Stowage Category** B

· **Transport in bulk according to Annex II of
 MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

· **IMDG**· **Limited quantities (LQ)** 5L· **Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

67-63-0 isopropyl alcohol

(Contd. on page 10)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailture

(Contd. of page 9)

| | |
|-----------|---|
| 7664-38-2 | Phosphoric Acid |
| 71-36-3 | n-Butyl alcohol |
| 7446-19-7 | zinc sulphate (hydrous) (mono-, hexa-and hepta hydrate) |

· TSCA (Toxic Substances Control Act):

| | | |
|------------|--|--------|
| 123-86-4 | Butyl acetate | ACTIVE |
| 141-78-6 | ethyl acetate | ACTIVE |
| 9004-70-0 | Nitrocellulose | ACTIVE |
| 28407-73-0 | Adipic Acid/Neopentyl Glycol/Trimellitic Anhydride Copolymer | ACTIVE |
| 77-90-7 | Tributyl acetylacrylate | ACTIVE |
| 64-17-5 | ethyl alcohol | ACTIVE |
| 13463-67-7 | titanium dioxide | ACTIVE |
| 67-63-0 | isopropyl alcohol | ACTIVE |
| 1333-86-4 | Carbon black | ACTIVE |
| 123-42-2 | 4-hydroxy-4-methylpentan-2-one | ACTIVE |
| 25869-00-5 | Ferric Ammonium Ferrocyanide | ACTIVE |
| 110-44-1 | hexa-2,4-dienoic acid | ACTIVE |
| 66-25-1 | hexanal | ACTIVE |
| 6417-83-0 | CI 15880 | ACTIVE |
| 7664-38-2 | Phosphoric Acid | ACTIVE |
| 69-65-8 | D-mannitol | ACTIVE |
| 61790-53-2 | Diatomaceous earth (Silica-Amorphous) | ACTIVE |
| 71-36-3 | n-Butyl alcohol | ACTIVE |
| 7631-86-9 | Silica | ACTIVE |
| 1934-21-0 | CI 19140 | ACTIVE |

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

| | |
|------------|------------------|
| 13463-67-7 | titanium dioxide |
| 1333-86-4 | Carbon black |

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

| | |
|---------|---------------|
| 64-17-5 | ethyl alcohol |
|---------|---------------|

· Carcinogenic categories

· EPA (Environmental Protection Agency)

| | | |
|-----------|---|----------|
| 71-36-3 | n-Butyl alcohol | D |
| 7446-19-7 | zinc sulphate (hydrous) (mono-, hexa-and hepta hydrate) | D, I, II |

· TLV (Threshold Limit Value)

| | | |
|---------|---------------|----|
| 64-17-5 | ethyl alcohol | A3 |
|---------|---------------|----|

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailure

(Contd. of page 10)

| | | |
|------------|-------------------|----|
| 13463-67-7 | titanium dioxide | A4 |
| 67-63-0 | isopropyl alcohol | A4 |
| 1333-86-4 | Carbon black | A4 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

| | |
|------------|------------------|
| 13463-67-7 | titanium dioxide |
| 1333-86-4 | Carbon black |

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Butyl acetate

Adipic Acid/Neopentyl Glycol/Trimellitic Anhydride Copolymer

ethyl acetate

· **Hazard statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2021

Reviewed on 06/02/2021

Trade name: OPI Nature Strong Force of Nailure

(Contd. of page 11)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Abteilung Umweltschutz

· **Contact:** Hr. Dr. Speckbacher

· **Date of preparation / last revision** 06/02/2021 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3